

Datasheet

IPM for Three-phase Motor Control ES9676AH

Fortior Technology Co., Ltd

Contents

Explanation of Symbols.....	18
Abbreviations.....	19
1 System Introduction	21
1.1 Features	21
1.2 Applications	22
1.3 Overview	22
1.4 Functional Block Diagram	23
1.4.1 ES9676AH	23
1.5 Memory Organization.....	24
1.5.1 Program Memory	24
1.5.2 Data Memory.....	24
1.5.3 SFR	25
1.5.4 XSFR	26
2 Pin Definitions	29
2.1 ES9676AH WBQHFBP-45L Pins.....	29
2.2 ES9676AH WBQHFBP-45L Pinout Diagram	32
3 Package Information.....	33
3.1 WBQHFBP-45L_12X12	33
4 Ordering Information.....	35
5 Electrical Characteristics	36
5.1 Absolute Maximum Ratings	36
5.2 Recommended Operating Conditions.....	36
5.3 Global Electrical Characteristics.....	37
5.4 GPIO Electrical Characteristics	37
5.5 ADC Electrical Characteristics	38
5.6 VREF and VHALF Electrical Characteristics.....	38
5.7 Operational Amplifier Electrical Characteristics	38
5.8 BEMF Electrical Characteristics.....	39
5.9 OSC Electrical Characteristics.....	39
5.10 Reset Electrical Characteristics	39
5.11 LDO Electrical Characteristics	40
5.12 Package Thermal Resistance.....	40
6 Reset Control.....	41

6.1 Reset Source (RST_SRC)	41
6.2 Reset Enable.....	41
6.3 External Reset and Power-on Reset.....	41
6.4 Low Voltage Detector reset	41
6.5 Watchdog Timer Reset.....	41
6.6 Flash Error Detector Reset.....	41
6.7 Debug Reset.....	41
6.8 Reset Registers.....	42
6.8.1 RST_SR (0xC9).....	42
7 Interrupt	43
7.1 Interrupt Introduction.....	43
7.2 Interrupt Enable.....	43
7.3 External Interrupt.....	43
7.4 Interrupt Summary	44
7.5 Interrupt Registers.....	45
7.5.1 IE (0xA8).....	45
7.5.2 IP0 (0xB8).....	45
7.5.3 IP1 (0xC0).....	46
7.5.4 IP2 (0xC8).....	46
7.5.5 IP3 (0xD8)	46
7.5.6 TCON (0x88).....	46
7.5.7 P1_IE (0xD1)	47
7.5.8 P1_IF (0xD2).....	48
7.5.9 P4_IE (0xD3)	48
7.5.10 P4_IF (0xD4).....	49
8 SPI.....	50
8.1 SPI Introduction	50
8.2 SPI Operations.....	50
8.2.1 Signal Descriptions.....	50
8.2.1.1 Master Output, Slave Input (MOSI).....	50
8.2.1.2 Master Input, Slave Output (MISO).....	50
8.2.1.3 Serial Clock (SCLK)	51
8.2.1.4 Slave Select (NSS)	51
8.2.2 SPI Master Mode	52
8.2.2.1 Master Mode Configurations	52

8.2.3 SPI Slave Mode	52
8.2.3.1 Slave Mode Configurations	53
8.2.4 SPI Interrupt Sources	53
8.2.5 Serial Clock Timing	53
8.3 SPI Registers.....	55
8.3.1 SPI_CRO (0x4030).....	55
8.3.2 SPI_CR1 (0x4031).....	56
8.3.3 SPI_CLK (0x4032)	56
8.3.4 SPI_DR (0x4033)	57
9 UART.....	58
9.1 UART Introduction	58
9.2 UART Operations.....	58
9.2.1 UART Mode0.....	58
9.2.2 UART Mode1.....	59
9.2.3 UART Mode2.....	59
9.2.4 UART Mode3.....	59
9.2.5 UART Interrupt Sources	59
9.3 UART Registers.....	60
9.3.1 UT_CR (0x98)	60
9.3.2 UT_DR (0x99).....	60
9.3.3 UT_BAUD (0x9A,0x9B).....	60
10 MDU.....	62
10.1 Multiplication Configurations	62
10.2 Division Configurations	62
10.3 Important Matters	62
10.4 MDU Registers	64
10.4.1 MDU_CR (0xC1)	64
10.4.2 MD_MBL (0xCA)	64
10.4.3 MD_MBH (0xCB).....	64
10.4.4 MD_MAL (0xC2).....	64
10.4.5 MD_MAH (0xC3).....	65
10.4.6 MD_DA0 (0xC4)	65
10.4.7 MD_DA1 (0xC5)	65
10.4.8 MD_DA2 (0xC6)	65
10.4.9 MD_DA3 (0xC7)	65

10.4.10 MD_DB0 (0xCC)	65
10.4.11 MD_DB1 (0xCD)	66
11 PI	67
11.1 PI Introduction	67
11.2 PI Operations	67
11.3 PI Registers.....	68
11.3.1 PI_LPF_CR (0xF9)	68
11.3.2 PI_EK (0xEA, 0xEB).....	68
11.3.3 PI_UK (0xEC, 0xED)	68
11.3.4 PI_KP (0xEE, 0xEF)	69
11.3.5 PI_KI (0xF2, 0xF3)	69
11.3.6 PI_UKMAX (0xF4, 0xF5)	69
11.3.7 PI_UKMIN (0xF6, 0xF7)	70
12 LPF	71
12.1 LPF Operations.....	71
12.2 LPF Registers	71
12.2.1 PI_LPF_CR (0xF9)	71
12.2.2 LPF_K (0xDD)	71
12.2.3 LPF_X (0xDE, 0xDF).....	71
12.2.4 LPF_Y (0xE6, 0xE7).....	72
13 SMDU.....	73
13.1 SMDU Features	73
13.2 SMDU Instructions	73
13.2.1 SMDU Operations.....	73
13.2.2 16-bit Signed Multiplication with the Result Shifted Left by One-bit.....	73
13.2.3 16-bit Signed Multiplication	74
13.2.4 16-bit Unsigned Multiplication.....	74
13.2.5 32-bit/16-bit Unsigned Division.....	74
13.2.6 SMDU LPF	75
13.2.7 Coordinate Transformation (SIN/COS)	75
13.2.8 Arctangent.....	76
13.2.9 PI.....	77
13.2.9.1 PI Introduction	77
13.2.9.2 PI Features.....	77
13.2.9.3 PI Operations.....	77

13.3 SMDU Registers	79
13.3.1 MDU_CR (0xC1)	79
13.3.2 TIM234_CTRL(0x40f1)	79
13.3.3 MUL0_MA (0x03C8, 0x03C9).....	80
13.3.4 MUL0_MB (0x03CA, 0x03CB)	80
13.3.5 MUL0_MC (0x03CC, 0x03CD, 0x03CE, 0x03CF).....	81
13.3.6 MUL1_MA (0x03C0, 0x03C1).....	81
13.3.7 MUL1_MB (0x03C2, 0x03C3).....	81
13.3.8 MUL1_MC (0x03C4, 0x03C5, 0x03C6, 0x03C7)	82
13.3.9 MUL2_MA (0x0370, 0x0371).....	82
13.3.10 MUL2_MB (0x0372, 0x0373)	82
13.3.11 MUL2_MC (0x0374, 0x0375, 0x0376, 0x0377).....	83
13.3.12 MUL3_MA (0x0368, 0x0369).....	83
13.3.13 MUL3_MB (0x036A, 0x036B).....	83
13.3.14 MUL3_MC (0x036C, 0x036D, 0x036E, 0x036F)	84
13.3.15 DIV0_DA (0x03B4, 0x03B5, 0x03B6, 0x03B7).....	84
13.3.16 DIV0_DB (0x03B8, 0x03B9).....	85
13.3.17 DIV0_DQ (0x03BA, 0x03BB, 0x03BC, 0x03BD)	85
13.3.18 DIV0_DR (0x03BE, 0x03BF).....	85
13.3.19 DIV1_DA (0x03A8, 0x03A9, 0x03AA, 0x03AB).....	86
13.3.20 DIV1_DB (0x03AC, 0x03AD).....	86
13.3.21 DIV1_DQ (0x03AE, 0x03AF, 0x03B0, 0x03B1)	86
13.3.22 DIV1_DR (0x03B2, 0x03B3).....	87
13.3.23 DIV2_DA (0x035C, 0x035D, 0x035E, 0x035F)	87
13.3.24 DIV2_DB (0x0360, 0x0361).....	88
13.3.25 DIV2_DQ (0x0362, 0x0363, 0x0364, 0x0365)	88
13.3.26 DIV2_DR (0x0366, 0x0367).....	88
13.3.27 DIV3_DA (0x0350, 0x0351, 0x0352, 0x0353)	89
13.3.28 DIV3_DB (0x0354, 0x0355).....	89
13.3.29 DIV3_DQ (0x0356, 0x0357, 0x0358, 0x0359)	89
13.3.30 DIV3_DR (0x035A, 0x035B)	90
13.3.31 SCAT0_COS (0x0346, 0x0347)	90
13.3.32 SCAT0_SIN (0x0348, 0x0349).....	90
13.3.33 SCAT0_THE (0x034A, 0x034B)	91
13.3.34 SCAT0_RES1 (0x034C, 0x034D)	91

13.3.35 SCAT0_RES2 (0x034E, 0x034F)	91
13.3.36 SCAT1_COS (0x033C, 0x033D).....	92
13.3.37 SCAT1_SIN (0x033E, 0x033F).....	92
13.3.38 SCAT1_THE (0x0340, 0x0341).....	92
13.3.39 SCAT1_RES1 (0x0342, 0x0343)	92
13.3.40 SCAT1_RES2 (0x0344, 0x0345)	93
13.3.41 SCAT2_COS (0x0332, 0x0333)	93
13.3.42 SCAT2_SIN (0x0334, 0x0335).....	93
13.3.43 SCAT2_THE (0x0336, 0x0337).....	94
13.3.44 SCAT2_RES1 (0x0338, 0x0339)	94
13.3.45 SCAT2_RES2 (0x033A, 0x033B).....	94
13.3.46 SCAT3_COS (0x0328, 0x0329)	94
13.3.47 SCAT3_SIN (0x032A, 0x032B)	95
13.3.48 SCAT3_THE (0x032C, 0x032D)	95
13.3.49 SCAT3_RES1 (0x032E, 0x032F)	95
13.3.50 SCAT3_RES2 (0x0330, 0x0331)	96
13.3.51 LPF0_K (0x03F8, 0x03F9)	96
13.3.52 LPF0_X (0x03FA 0x03FB)	96
13.3.53 LPF0_Y (0x03FC, 0x03FD, 0x03FE, 0x03FF).....	96
13.3.54 LPF1_K (0x03F0, 0x03F1)	97
13.3.55 LPF1_X (0x03F2, 0x03F3)	97
13.3.56 LPF1_Y (0x03F4, 0x03F5, 0x03F6, 0x03F7)	97
13.3.57 LPF2_K (0x03A0, 0x03A1)	98
13.3.58 LPF2_X (0x03A2, 0x03A3)	98
13.3.59 LPF2_Y (0x03A4, 0x03A5, 0x03A6, 0x03A7	99
13.3.60 LPF3_K (0x0398, 0x0399)	99
13.3.61 LPF3_X (0x039A, 0x039B)	99
13.3.62 LPF3_Y (0x039C, 0x039D, 0x039E, 0x039F)	100
13.3.63 PIO_KP (0x03E0, 0x03E1)	100
13.3.64 PIO_EK1 (0x03E2, 0x03E3)	100
13.3.65 PIO_EK (0x03E4, 0x03E5)	101
13.3.66 PIO_KI (0x03E6, 0x03E7)	101
13.3.67 PIO_UKH (0x03E8, 0x03E9)	101
13.3.68 PIO_UKL (0x03EA, 0x03EB)	101
13.3.69 PIO_UKMAX (0x03EC, 0x03ED)	102

13.3.70 PIO_UKMIN (0x03EE, 0x03EF).....	102
13.3.71 PI1_KP (0x03D0, 0x03D1)	102
13.3.72 PI1_EK1 (0x03D2, 0x03D3)	103
13.3.73 PI1_EK (0x03D4, 0x03D5)	103
13.3.74 PI1_KI(0x03D6, 0x03D7)	103
13.3.75 PI1_UKH (0x03D8, 0x03D9)	103
13.3.76 PI1_UKL (0x03DA, 0x03DB)	104
13.3.77 PI1_UKMAX (0x03DC, 0x03DD)	104
13.3.78 PI1_UKMIN (0x03DE, 0x03DF).....	104
13.3.79 PI2_KP (0x0388, 0x0389)	105
13.3.80 PI2_EK1 (0x038A, 0x038B).....	105
13.3.81 PI2_EK (0x038C, 0x038D).....	105
13.3.82 PI2_KI (0x038E, 0x038F)	105
13.3.83 PI2_UKH (0x0390, 0x0391)	106
13.3.84 PI2_UKL (0x0392, 0x0393)	106
13.3.85 PI2_MAX (0x0394, 0x0395)	106
13.3.86 PI2_MIN (0x0396, 0x0397)	107
13.3.87 PI3_KP (0x0378, 0x0379).....	107
13.3.88 PI3_EK1 (0x037A, 0x037B).....	107
13.3.89 PI3_EK (0x037C, 0x037D).....	107
13.3.90 PI3_KI (0x037E, 0x037F)	108
13.3.91 PI3_UKH (0x0380, 0x0381).....	108
13.3.92 PI3_UKL (0x0382, 0x0383)	108
13.3.93 PI3_UKMAX (0x0384, 0x0385)	109
13.3.94 PI3_UKMIN (0x0386, 0x0387)	109
14 FOC	110
14.1 FOC Overview.....	110
14.1.1 FOC Introduction	110
14.1.2 Reference Voltage (VREF) Input	110
14.1.3 PI Controller.....	111
14.1.4 Coordinate Transformation.....	111
14.1.4.1 Inverse Park Transformation.....	111
14.1.4.2 Inverse Clarke Transformation.....	112
14.1.4.3 Clarke Transformation	112
14.1.4.4 Park Transformation	112

14.1.5 SVPWM.....	113
14.1.5.1 Continuous SVPWM	114
14.1.5.2 Discontinuous SVPWM.....	114
14.1.6 Overmodulation	115
14.1.7 Deadtime Compensation.....	115
14.1.8 Current and Voltage Sampling.....	115
14.1.8.1 Single-shunt Current Sampling Mode	115
14.1.8.2 Dual/Triple-shunt Current Sampling Mode.....	116
14.1.8.3 Current Sampling Offset.....	117
14.1.9 Angle Mode	118
14.1.9.1 Forced Ramping Angle	118
14.1.9.2 Forced Pulling Angle.....	118
14.1.9.3 Estimator Output Angle	119
14.1.9.3.1 Estimated Angle of Estimator	119
14.1.9.3.2 Forced Angle of Estimator	120
14.1.9.3.3 Angle Smooth Switching	120
14.1.9.3.4 Angle Compensation.....	121
14.1.10 Motor Real-time Parameters.....	121
14.1.10.1 Tailwind/headwind Detection.....	121
14.1.10.2 BEMF Detection	121
14.1.10.3 Motor Power	122
14.2 FOC Registers	122
14.2.1 FOC_CR1 (0x40A0).....	122
14.2.2 FOC_CR2 (0x40A1).....	122
14.2.3 FOC_TSMIN (0x40A2)	123
14.2.4 FOC_TGLI (0x40A3).....	123
14.2.5 FOC_TBLO (0x40A4).....	124
14.2.6 FOC_TRGDLY (0x40A5)	124
14.2.7 FOC_CS0 (0x40A6, 0x40A7)	124
14.2.8 FOC_RTHESTEP (0x40A8, 0x40A9).....	125
14.2.9 FOC_RTHeACC (0x40AA, 0x40AB).....	125
14.2.10 FOC_RTHeCNT (0x40AC).....	126
14.2.11 FOC_THECOR (0x40AD) (Shared with BLDC Motors).....	126
14.2.12 FOC_THECOMP (0x40AE, 0x40AF).....	126
14.2.13 FOC_DMAX (0x40B0, 0x40B1)	126

14.2.14 FOC_DMIN (0x40B2, 0x40B3).....	127
14.2.15 FOC_QMAX (0x40B4, 0x40B5).....	127
14.2.16 FOC_QMIN (0x40B6, 0x40B7).....	127
14.2.17 FOC_UD (0x40B8, 0x40B9)	128
14.2.18 FOC_UQ (0x40BA, 0x40BB).....	128
14.2.19 FOC_ID (0x40BC, 0x40BD)	128
14.2.20 FOC_IQ (0x40BE, 0x40BF).....	129
14.2.21 FOC_IBET (0x40C0, 0x40C1)	129
14.2.22 FOC_VBET (0x40C2, 0x40C3)	129
14.2.23 FOC_VALP (0x40C4, 0x40C5)	130
14.2.24 FOC_IC (0x40C6, 0x40C7)	130
14.2.25 FOC_IB (0x40C8, 0x40C9)	130
14.2.26 FOC_IA (0x40CA, 0x40CB).....	131
14.2.27 FOC_THETA (0x40CC, 0x40CD)	131
14.2.28 FOC_ETHETA (0x40CE, 0x40CF)	131
14.2.29 FOC_EALP (0x40D0, 0x40D1).....	132
14.2.30 FOC_EBET (0x40D2, 0x40D3).....	132
14.2.31 FOC_EOME (0x40D4, 0x40D5).....	132
14.2.32 FOC_ESQU (0x40D6, 0x40D7).....	133
14.2.33 FOC_POW (0x40D8, 0x40D9).....	133
14.2.34 FOC_EKP (0x4074, 0x4075) (Shared with BLDC Motors).....	133
14.2.35 FOC_EKI (0x4076, 0x4077) (Shared with BLDC Motors)	134
14.2.36 FOC_EBMFK (0x407C, 0x407D) (Shared with BLDC Motors)	134
14.2.37 FOC_KSLIDE (0x4078, 0x4079) (Shared with BLDC Motors)	134
14.2.38 FOC_EKLPFMIN (0x407A, 0x407B) (Shared with BLDC Motors)	135
14.2.39 FOC_OMEKLPF (0x407E, 0x407F)	135
14.2.40 FOC_FBASE (0x4080, 0x4081).....	135
14.2.41 FOC_EFREQACC (0x4082, 0x4083) (Shared with BLDC Motors)	136
14.2.42 FOC_EFREQMIN (0x4084 0x4085) (Shared with BLDC Motors)	136
14.2.43 FOC_EFREQHOLD (0x4086, 0x4087) (Shared with BLDC Motors)	136
14.2.44 FOC_EK3 (0x4088, 0x4089).....	137
14.2.45 FOC_EK4 0x408A, 0x408B)	137
14.2.46 FOC_EK1 (0x408C, 0x408D)	138
14.2.47 FOC_EK2 (0x408E, 0x408F).....	138
14.2.48 FOC_IDREF (0x4090, 0x4091) (Shared with BLDC Motors)	138

14.2.49 FOC_IQREF (0x4092, 0x4093) (Shared with BLDC Motors)	139
14.2.50 FOC_DQKP (0x4094, 0x4095) (Shared with BLDC Motors)	139
14.2.51 FOC_DQKI (0x4096, 0x4097) (Shared with BLDC Motors)	139
14.2.52 FOC__UDCFLT (0x4098, 0x4099)	140
14.2.53 FOC_CR3 (0x40ee)	140
14.2.54 FOC_DKP (0x409c, 0x409d)	141
14.2.55 FOC_DKI (0x409e, 0x409f)	141
14.2.56 FOC__Iamax (0x40da, 0x40db)	141
14.2.57 FOC__IBMAX (0x40dc, 0x40dd)	142
14.2.58 FOC__ICMAX (0x40de, 0x40df)	142
14.2.59 FOC__EMF (0x40e0, 0x40e1)	143
14.2.60 FOC__UDCPs (0x40e2, 0x40e3)	143
14.2.61 FOC__UQCPS (0x40e4, 0x40e5)	143
14.2.62 FOC__UQEX (0x40e6, 0x40e7)	144
14.2.63 FOC_ID_LPFK (0x40e8)	144
14.2.64 FOC_IQ_LPFK (0x40e9)	144
14.2.65 FOC_KFG (0x40ea, 0x40eb)	145
15 Timer1.....	146
15.1 Timer1 Operations	146
15.1.1 Timer1 Counter Module	147
15.1.1.1 Prescaler	147
15.1.1.2 Base Timer	148
15.1.1.3 Reload Timer	148
15.1.2 Position Detection	149
15.1.2.1 Position Detection Event	149
15.1.2.1.1 Sampling	151
15.1.2.1.2 Filtering	152
15.1.3 Write Timing Interrupt	152
15.1.4 Timer1 Interrupt	152
15.2 Square-wave Control Based BLDC Motor	153
15.2.1 Six-Step Phase Commutation of Square Wave Control	154
15.2.2 Working Principle of BLDC Motor	155
15.2.2.1 60° Commutation Base Time	155
15.2.2.2 Phase Commutation	155
15.2.2.3 Forced Commutation at 60°	156

15.2.2.4 Diode Freewheeling Masking	156
15.2.2.5 Angle of ZCP to Phase Commutation (Delayed Commutation).....	157
15.2.2.6 Cycle-by-cycle Current Limiting.....	157
15.2.3 BLDC Motor Debugging	157
15.2.3.1 Comparator Debugging	157
15.2.3.2 Debugging on Diode Freewheeling Masking and Phase Commutation	158
15.3 Phase Commutation Signals by ADC.....	158
15.4 Timer1 Registers	159
15.4.1 TIM1_CRO (0x4068)	159
15.4.2 TIM1_CR1 (0x4069)	160
15.4.3 TIM1_CR2 (0x406A).....	160
15.4.4 TIM1_CR3 (0x406B)	161
15.4.5 TIM1_CR4 (0x406C)	161
15.4.6 TIM1_IER (0x406D).....	162
15.4.7 TIM1_SR (0x406E).....	162
15.4.8 TIM1_BC0R (0x4070, 0x4071).....	163
15.4.9 TIM1_DBRx (x=1~7)(0x4074+2*x, 0x4075+2*x).....	164
15.4.10 TIM1__BCNTR (0x4082, 0x4083).....	165
15.4.11 TIM1__BCCR (0x4084, 0x4085)	165
15.4.12 TIM1__BARR (0x4086, 0x4087)	166
15.4.13 TIM1__RARR (0x4088, 0x4089)	166
15.4.14 TIM1__RCNTR (0x408A, 0x408B)	166
15.4.15 TIM1__ITRIP (0x4098, 0x4099).....	167
15.4.16 TIM1__UCOP (0x408C, 0x408D)	167
15.4.17 TIM1__UFLP (0x408E, 0x408F)	167
15.4.18 TIM1__URES (0x4090, 0x4091)	168
15.4.19 TIM1__UIGN (0x4092, 0x4093)	168
15.4.20 TIM1_KF (0x4094, 0x4095).....	168
15.4.21 TIM1_KR (0x4096, 0x4097).....	169
15.4.22 EXTO (0x40f0).....	169
16 Timer2.....	170
16.1 Timer2 Instructions	170
16.1.1 Prescaler	170
16.1.2 Reading, Writing and Counting of TIM2__CNTR	171
16.1.3 Output Mode	171

16.1.3.1 Reading and Writing of TIM2__ARR/TIM2__DR	171
16.1.3.2 High-/Low-level Output Mode	171
16.1.3.3 PWM Generation	171
16.1.3.4 Interrupt Event.....	172
16.1.4 Input Signal Filtering and Edge Detection	172
16.1.5 Input Capture Mode	173
16.1.6 Input Counter Mode.....	174
16.1.7 QEP&RSD Mode.....	175
16.1.7.1 RSD Comparator Sampling	177
16.1.8 Step Mode	178
16.2 Timer2 Registers	179
16.2.1 TIM2_CRO (0xA1)	179
16.2.2 TIM2_CR1 (0xA9)	180
16.2.3 PI_LPF_CR (0xF9)	181
16.2.4 TIM2__CNTR (0xAA, 0xAB)	181
16.2.5 TIM2__DR (0xAC, 0xAD)	182
16.2.6 STIM2__ARR (0xAE, 0xAF)	182
17 Timer3/Timer4 (Timer4 supports timing only and does not support input and output)	183
17.1 Timer3 Instructions	183
17.2 Timer4 Instructions	183
17.2.1 Prescaler	183
17.2.2 Reading, Writing and Counting of TIMx__CNTR.....	184
17.2.3 Output Mode	184
17.2.3.1 High-/Low-level Output Mode	184
17.2.3.2 PWM Generation	184
17.2.3.3 Interrupt Event.....	184
17.2.4 Input Signal Filtering and Edge Detection	185
17.2.5 Input Capture Mode	186
17.3 Timer3/Timer4 Registers	187
17.3.1 TIMx_CRO (0x9C/0x9E) (x=3/4).....	187
17.3.2 TIM3_CR1 (0x9D/0x9F).....	187
17.3.3 TIM3__CNTR (0xA2,0xA3/0x92,0x93)	188
17.3.4 TIM3__DR (0xA4,0xA5/0x94,0x95).....	189
17.3.5 TIM3__ARR (0xA6,0xA7/0x96,0x97).....	189
18 Systick	190

18.1 Systick Instructions	190
18.2 Systick Registers.....	190
18.2.1 DRV_SR (0x4061).....	190
18.2.2 SYST_ARR (0x4064,0x4065).....	190
19 Driver	191
19.1 Driver Instructions	191
19.1.1 Driver Introduction.....	191
19.1.2 Output Control Module	192
19.1.2.1 Count and Compare Module.....	192
19.1.2.2 Deadtime Module	193
19.1.2.3 Enable and Polarity of Output Signals.....	193
19.1.2.4 Main Output Enable (MOE).....	195
19.1.2.5 Interrupt.....	195
19.1.2.5.1 Compare Match Interrupt.....	195
19.1.2.5.2 FG Interrupt	196
19.2 Driver Registers.....	197
19.2.1 DRV_CR (0x4062).....	197
19.2.2 DRV_SR (0x4061).....	197
19.2.3 DRV_OUT (0xF8)	198
19.2.4 DRV_CMRR (0x405C, 0x405D).....	199
19.2.5 DRV_ARR (0x405E, 0x405F).....	200
19.2.6 DRV_COMR (0x405A, 0x405B).....	200
19.2.7 DRV_DR (0x4058, 0x4059).....	201
19.2.8 DRV_DTR (0x4060)	201
20 WDT	202
20.1 WDT Notes	202
20.2 WDT Operations.....	202
20.3 WDT Registers.....	202
20.3.1 WDT_CR (0x4026).....	202
20.3.2 WDT_REL (0x4027)	203
21 RTC and Clock Calibration.....	204
21.1 RTC Functional Block Diagram	204
21.2 RTC Operations	204
21.3 RTC Registers	204
21.3.1 RTC_TM (0x402c, 0x402d)	204

21.3.2 RTC_STA (0x402e).....	205
21.4 Clock Calibration	205
21.4.1 Introduction.....	205
21.4.2 Clock Calibration Register.....	206
21.4.2.1 CAL_CR (0x4044, 0X4045)	206
22 IO	207
22.1 IO Introduction.....	207
22.2 IO Operations.....	207
22.3 IO Registers	208
22.3.1 P0_OE (0xFC)	208
22.3.2 P1_OE (0xFD)	208
22.3.3 P2_OE (0xFE).....	208
22.3.4 P3_OE (0xFF).....	209
22.3.5 P1_AN (0x4050).....	209
22.3.6 P2_AN (0x4051).....	209
22.3.7 P3_AN (0x4052).....	210
22.3.8 P0_PU (0x4053)	210
22.3.9 P1_PU (0x4054)	210
22.3.10 P2_PU (0x4055)	210
22.3.11 P3_PU (0x4056)	211
22.3.12 PH_SEL (0x404C).....	211
22.3.13 P0 (0x80)/P1 (0x90)/P2 (0xA0)/P3 (0xB0) /P4 (0xE8).....	212
23 ADC	213
23.1 ADC Block Diagram	213
23.2 ADC Operations.....	213
23.2.1 Sequential Sampling Mode.....	213
23.2.2 ADC Triggered Sampling Mode.....	214
23.3 ADC Registers	216
23.3.1 ADC_CR (0x4039).....	216
23.3.2 ADC_MASK (0x4036, 0x4037).....	216
23.3.3 ADC_MASKH (0x4036)	217
23.3.4 ADC_SCYCL (0x4038)	217
23.3.5 ADC0_DR (0x0300, 0x0301).....	218
23.3.6 ADC1_DR (0x0302, 0x0303).....	218
23.3.7 ADC2_DR (0x0304, 0x0305).....	218

23.3.8 ADC4_DR (0x0308, 0x0309).....	219
23.3.9 ADC5_DR (0x030A, 0x030B)	219
23.3.10 ADC7_DR (0x030E, 0x030F).....	219
23.3.11 ADC8_DR (0x0310, 0x0311).....	220
23.3.12 ADC9_DR (0x0312, 0x0313).....	220
23.3.13 ADC10_DR (0x0314, 0x0315).....	220
23.3.14 ADC11_DR (0x0316, 0x0317).....	221
24 DAC	222
24.1 DAC Functional Block Diagram.....	222
24.2 DAC Registers.....	222
24.2.1 DAC_CR (0x4035).....	222
24.2.2 DAC_DR (0x404B)	223
25 DMA.....	224
25.1 DMA Instructions	224
25.2 DMA Registers.....	225
25.2.1 DMA0_CRO (0x403A)	225
25.2.2 DMA1_CRO (0x403B)	225
25.2.3 DMA0_CR1 (0x403C)	226
25.2.4 DMA1_CR1 (0x403E)	227
26 VREF.....	228
26.1 VREF Instructions	228
26.2 VREF Register	229
26.2.1 VREF_VHALF_CR (0x404F)	229
27 VHALF	230
27.1 VHALF Instructions.....	230
27.2 VHALF Register.....	230
28 Operational Amplifier	231
28.1 Operational Amplifier Instructions	231
28.1.1 Bus Current Sampling Operational Amplifier (AMP0)	231
28.1.2 Phase Current Operational Amplifier (AMP1/AMP2).....	232
28.1.2.1 AMP1.....	232
28.1.2.2 AMP2.....	232
28.1.3 PGA Differential Input Mode	233
28.2 Operational Amplifier Registers.....	235
28.2.1 AMP_CR (0x404E).....	235

28.2.2 CMP_AMP (0x40f2)	235
28.2.3 TSD_ADJ (0x40f3)	235
29 Comparator	237
29.1 Comparator Operations	237
29.1.1 Comparator CMP3	237
29.1.1.1 Overcurrent Protection	239
29.1.1.2 Cycle-by-cycle Current Limiting.....	240
29.1.2 Comparator CMPO	241
29.1.3 Comparator Sampling.....	245
29.1.4 Comparator Output	246
29.2 Comparator Registers	246
29.2.1 CMP_CRO (0xD5).....	246
29.2.2 CMP_CR1 (0xD6).....	246
29.2.3 CMP_CR2 (0xDA)	247
29.2.4 CMP_CR3 (0xDC)	249
29.2.5 CMP_SAMR (0x40AD)	249
29.2.6 CMP_SR (0xD7).....	250
29.2.7 EVT_FILT (0xD9).....	251
30 Power Supply.....	252
30.1 LDO.....	252
30.1.1 LDO Operations	252
30.2 Low Voltage Detector (LVD).....	253
30.2.1 LVD Introduction	253
30.2.2 LVD Registers	254
30.2.2.1 CCFG2:RST_MOD (0x401D)	254
30.2.2.2 CCFG1:CK_RST_CFG (0x401E)	254
30.2.2.3 LVSR(0xDB).....	254
36 Revision History.....	269

Explanation of Symbols

- The symbol “[]” following a register indicates a bit in the register. For example, ABCD[XY] indicates the XY bit in ABCD register.
- The symbol “x” in a register name indicates similar registers. For example, TIMx_CR0 indicates TIM3_CR0 and TIM4_CR0.
- [m:n] indicates a range of bits. For example, [3:0] means the bits from bit3 to bit0.
- Pm.n indicates the nth port of the Portm. P0.0 indicates the 0th port of Port0.
- Register read and write symbols:
 - R: Read only
 - W: Write only
 - R/W: Read/write
 - W0: Only 0 can be written
 - W1: Only 1 can be written
- The symbol “-” indicates an uncertainty value or invalid value.
- The RMW instruction cannot be used for registers with different read and written representations.
- Q (number) format is to store floating-point numbers using fixed-point numbers. MSB is the sign bit, followed by integer bits and fraction bits, where lower Q bits are assigned to the fractional part and the remaining bits are assigned to the integer part. For example, for Q12, bit15 is the sign bit, bit14 ~ bit12 represent the integer part and bit11 ~ bit0 represent the fraction part. The Q12 format has a decimal range -8 ~ 7.9998 (corresponding to 0x8000 ~ 0x7FFF).

Abbreviations

ADC	Analog to Digital Convertor
BEMF	Back Electromotive Force
BLDC	Brushless Direct Current
CRC	Cyclic Redundancy Check
DAC	Digital to Analog Convertor
DMA	Direct Memory Access
FG	Frequency Generator
FICE	Fortior Interactive Connectivity Establishment
FOC	Field Oriented Control
FOSC	Fast Oscillator
GPIO	General Purpose Input Output
IC	Integrated Circuit
IRAM	Internal RAM
IDE	Integrated Development Environment
LDO	Low Dropout Regulator
LPF	Low Pass Filter
LVD	Low Voltage Detection
MDU	Multiplication Division Unit
ME	Motor Engine
MSB	Most Significant Bit
MOSFET	Metal Oxide Semiconductor Field Effect Transistor
NC	Not Connected
PFC	Power Factor Correction
PGA	Programmable Gain Amplifier
PI/PID	Proportional Integral/Proportional Integral Derivative
PLL	Phase Locked Loop
PWM	Pulse Width Modulation
QEP	Quadrature Encoder Pulse
RAM	Random Access Memory
RMW	Read Modified Write
ROM	Read Only Memory
RSD	Rotating State Detection
RTC	Real Time Clock

SCL	Serial Clock Line
SDA	Serial Data Line
SFR	Special Function Register
SMO	Sliding Mode Observer
SOSC	Slow Oscillator
SPI	Serial Peripheral Interface
SVPWM	Space Vector PWM
TSD	Temperature Sensor Detect
UART	Universal Asynchronous Receiver/Transmitter
WDT	Watch Dog Timer
XRAM	External RAM
XSFR	External SFR

1 System Introduction

1.1 Features

- Power supply:
 - External power supply 12V~20V is connected to VCC pin, and internal LDO supplies VDD5 voltage.
- MOSFET:
 - N-Channel:
 - ◆ $V_{DS} = 600V$
 - ◆ $I_D = 4A$
 - ◆ $R_{DS} = 1.1\Omega$
- Dual core: 8051 core and ME core. ME core achieves automatic calculation of FOC or square-wave control by the hardware for BLDC motors, and 8051 core is used for parameter configuration and routine processing.
- An instruction cycle mostly takes 1 or 2 system clock cycle(s)
- 16kB Flash ROM with CRC, self-program and code protection
- 256 bytes IRAM and 768 bytes XRAM
- ME: Core integrating LPF module, PI regulator, BLDC module, FOC module, MDU auxiliary computing module
- 1T 16x16 multiplier, 16T 32/16 divider
- 15 interrupt sources with 4 configurable priority levels
- 18*GPIOs
- Timers:
 - 2*Programmable timers with capture feature
 - 1*QEP decoding programmable timer
 - 1*BLDC motor dedicated timer
 - 1*General-purpose timer
 - 1*RTC
- Communication interfaces:
 - 1*SPI
 - 1*UART, supporting single-wire mode
 - Dual-channel DMA: supporting data transmission via SPI/UART
- Analog peripherals:
 - 12-bit ADC, operating with 1 μ s conversion time and internal VREF or external VREF selectable as reference voltage

- Number of ADC channels: 10
- Internal VREF. 3V, 4V, 4.5V and VDD5 can be selected as the internal reference.
- Three standalone operational amplifiers
- 2-channel analog comparator
- 9-bit DAC
- FOC module supports single/dual/triple-shunt current sampling
- FOC module supports overmodulation
- System clock
 - Built-in 20MHz high-speed RC oscillator
 - Built-in 32.8kHz low-speed RC oscillator
- WDT
- LVD
- TSD
- Two-wire FICE protocol based in-circuit emulation

1.2 Applications

The chip can be used for the drive of sensorless or sensored BLDC/PMSM motors, single-phase/three-phase induction motors and servo motors.

Applications: High-voltage indoor and outdoor units, high-voltage water pumps, high-voltage vacuum cleaners, high-voltage exhausters, etc.

1.3 Overview

ES9676AH is a fully-integrated IPM with motor controller, driver and power IC. Its high-performance motor drive chip incorporates ME core and 8051 core. ME core integrates FOC, MDU, LPF, PI and SVPWM modules that allow for automatic calculation of FOC or square-wave control by the hardware for sensored/sensorless BLDC/PMSM motors. 8051 core is used for parameter configuration and routine processing. Most of 8051 core instruction cycle takes 1T or 2T clock cycle(s). The dual cores work in parallel to achieve high-performance motor control. The chip integrates high-speed operational amplifiers, comparators, high-speed ADC, CRC, UART, Timers, PWM module and built-in high-voltage LDO, which are suitable for FOC or square-wave based BLDC/PMSM motors.

Package of ES9676AH: WBQHFBP-45L.

1.4 Functional Block Diagram

1.4.1 ES9676AH




Figure 1-1 ES9676AH Functional Block Diagram

1.5 Memory Organization

The internal storage space is divided into Program Memory and Data Memory, which are independently addressed.




Figure 1-2 Memory Organization

1.5.1 Program Memory

The chip implements this program memory as Flash memory with a block from addresses 0x0000 to 0x3FFF to store control programs. CPU starts from 0x0000 after reset.

1.5.2 Data Memory

The data memory is divided into External Data Memory and Internal Data Memory&SFRs.

The External Data Memory is addressed from 0x0000 to 0x02FF, which can be accessed with MOVX instructions only.

The Internal Data Memory is shown in Figure 1-2. Locations 0x00~0x1F are addressable as 4 banks of general-purpose registers, each bank consisting of 8 registers. Locations 0x20~0x2F are 16-bit addressable, and locations 0x30~0x7F support direct and indirect addressing. When locations 0x80~0xFF are accessed by indirect addressing, it points to RAM. When locations 0x80~0xFF are accessed by direct addressing, it points to SFRs. Stack space is located in the Internal Data Memory.

1.5.3 SFR

Table 1-1 SFR Address Mapping

Addr	0(8)	1(9)	2(A)	3(B)	4(C)	5(D)	6(E)	7(F)
0xF8	DRV_OUT	PI_LPF_CR			P0_OE	P1_OE	P2_OE	P3_OE
0xF0	B		PI_KIL	PI_KIH	PI_UKMAXL	PI_UKMAXH	PI_UKMINL	PI_UKMINH
0xE8	P4	P4_OE	PI_EKL	PI_EKH	PI_UKL	PI_UKH	PI_KPL	PI_KPH
0xE0	ACC						LPF_YL	LPF_YH
0xD8	IP3	EVT_FILTER	CMP_CR2	LVSR	CMP_CR3	LPF_K	LPF_XL	LPF_XH
0xD0	PSW	P1_IE	P1_IF	P2_IE	P2_IF	CMP_CR0	CMP_CR1	CMP_SR
0xC8	IP2	RST_SR	MDU_MBL	MDU_MBH	MDU_DB0	MDU_DB1		
0xC0	IP1	MDU_CR	MDU_MAL	MDU_MAII	MDU_DA0	MDU_DA1	MDU_DA2	MDU_DA3
0xB8	IP0							
0xB0	P3							
0xA8	IE	TIM2_CR1	TIM2__CNTRL	TIM2__CNTRH	TIM2__DRL	TIM2__DRH	TIM2__ARLL	TIM2__ARRH
0xA0	P2	TIM2_CR0	TIM3__CNTRL	TIM3__CNTRH	TIM3__DRL	TIM3__DRH	TIM3__ARLL	TIM3__ARRH
0x98	UT_CR	UT_DR	UT_BAUDL	UT_BAUDH	TIM3_CR0	TIM3_CR1	TIM4_CR0	TIM4_CR1
0x90	P1		TIM4__CNTRL	TIM4__CNTRH	TIM4__DRL	TIM4__DRH	TIM4__ARLL	TIM4__ARRH
0x88	TCON							
0x80	P0	SP	DPL	DPH	FLA_KEY	FLA_CR		PCON

Notes:

- Registers with 4 low-order bits as 0 or 8 support addressing access.
- Registers containing the symbol “__” shall be read using variables. If it is read directly, the value will be incorrect.

1.5.4 XSFR

Table 1-2 XSFR Address Mapping

Addr	0(8)	1(9)	2(A)	3(B)	4(C)	5(D)	6(E)	7(F)
0x40f0	EXT0	TIM234_CTRL	CMP_AMP	TSD_ADJ				
0x40e8	FOC_ID_LPFK	FOC_IQ_LPFK	FOC_KFGH	FOC_KFGL			FOC_CR3	
0x40e0	FOC_EMFH	FOC_EMFL	FOC_UDCPSH	FOC_UDCPSL	FOC_UQCPSH	FOC_UQCPSL	FOC_UQEXH	FOC_UQEXL
0x40d8	FOC_POWH	FOC_POWL	FOC_IAMAXH	FOC_IAMAXL	FOC_IBMAXH	FOC_IBMAXL	FOC_ICMAXH	FOC_ICMAXL
0x40d0	FOC_EALPH	FOC_EALPL	FOC_EBETH	FOC_EBETL	FOC_EOMEH	FOC_EOMEL	FOC_ESQUH	FOC_ESQL
0x40c8	FOC_IBH	FOC_IBL	FOC_IAH	FOC_IAL	FOC_THETAH	FOC_THETAL	FOC_ETHETAH	FOC_ETHETAL
0x40c0	FOC_IBETH	FOC_IBETL	FOC_VBETH	FOC_VBETL	FOC_VALPH	FOC_VALPL	FOC_ICH	FOC_ICL
0x40b8	FOC_UDH	FOC_UDL	FOC_UQH	FOC_UQL	FOC_IDH	FOC_IDL	FOC_IQH	FOC_IQL
0x40b0	FOC_DMAXH	FOC_DMAXL	FOC_DMINH	FOC_DMINL	FOC_QMAXH	FOC_QMAXL	FOC_QMINH	FOC_QMINL
0x40a8	FOC_RTHESTEPH	FOC_RTHESTEPL	FOC_RTHeACCH	FOC_RTHeACCL	FOC_RTHeCNT	FOC_THECOR/ CMP_SAMR	FOC_THECOMPH	FOC_THECOMPL
0x40a0	FOC_CR1	FOC_CR2	FOC_TSMIN	FOC_TGLI	FOC_TBLO	FOC_TRGDLY	FOC_CSOH	FOC_CSOL
0x4098	FOC_UDCFLTH/ TIM1_ITRIPH	FOC_UDCFLTL/ TIM1_ITRIPL						
0x4090	FOC_IDREFH	FOC_IDREFL	FOC_IQREFH	FOC_IQREFL	FOC_DQKPH	FOC_DQKPL	FOC_DQKIH	FOC_DQKIL
0x4088	FOC_EK3H/ TIM1_RARRH	FOC_EK3L/ TIM1_RARRL	FOC_EK4H/ TIM1_RCNTRH	FOC_EK4L/ TIM1_RCNTRL	FOC_EK1H	FOC_EK1L	FOC_EK2H	FOC_EK2L
0x4080	FOC_FBASEH/ TIM1_DBR7H	FOC_FBASEL/ TIM1_DBR7L	FOC_EFREQACCH/ TIM1_BCNTRH	FOC_EFREQACCL/ TIM1_BCNTRL	FOC_EFREQMINH/ TIM1_BCCRH	FOC_EFREQMINL/ TIM1_BCCRL	FOC_EFREQHOLDH/ TIM1_BARRH	FOC_EFREQHOLDL/ TIM1_BARRL
0x4078	FOC_KSLIDEH/ TIM1_DBR3H	FOC_KSLIDEL/ TIM1_DBR3L	FOC_EKLPFMINH/ TIM1_DBR4H	FOC_EKLPFMINL/ TIM1_DBR4L	FOC_EBMFKH/ TIM1_DBR5H	FOC_EBMFKL/ TIM1_DBR5L	FOC_OMEKLPFH/ TIM1_DBR6H	FOC_OMEKLPFL/ TIM1_DBR6L
0x4070	TIM1_BCORH	TIM1_BCORL			FOC_EKPH/ TIM1_DBR1H	FOC_EKPL/ TIM1_DBR1L	FOC_EKIH/ TIM1_DBR2H	FOC_EKIL/ TIM1_DBR2L
0x4068	TIM1_CR0	TIM1_CR1	TIM1_CR2	TIM1_CR3	TIM1_CR4	TIM1_IER	TIM1_SR	
0x4060	DRV_DTR	DRV_SR	DRV_CR		SYST_ARRH	SYST_ARRL		
0x4058	DRV_DRH	DRV_DRL	DRV_COMRH	DRV_COMRL	DRV_CMRH	DRV_CMRL	DRV_ARRH	DRV_ARRL
0x4050	P1_AN	P2_AN	P3_AN	P0_PU	P1_PU	P2_PU	P3_PU	P4_PU
0x4048				DAC_DR	PH_SEL		AMP_CR	VREF_VHALF_CR
0x4040	CAL_CR0	CAL_CR1						
0x4038	ADC_SCYC	ADC_CR	DMA0_CR0	DMA1_CR0	DMA0_CR1H	DMA0_CR1L	DMA1_CR1H	DMA1_CR1L

Addr	0(8)	1(9)	2(A)	3(B)	4(C)	5(D)	6(E)	7(F)
0x4030	SPI_CR0	SPI_CR1	SPI_CLK	SPI_DR		DAC_CR	ADC_MASK_SYSCH	ADC_MASK_SYSCL
0x4028					RTC_TMH	RTC_TML	RTC_STA	
0x4020		CRC_DIN	CRC_CR	CRC_DR	CRC_BEG	CRC_CNT	WDT_CR	WDT_REL
0x4018	CCFG7	CCFG6	CCFG5	CCFG4	CCFG3	CCFG2	CCFG1	CCFG0
0x0310	AD8_DRH	AD8_DRL	AD9_DRH	AD9_DRL	AD10_DRH	AD10_DRL	AD11_DRH	AD11_DRL
0x0308	AD4_DRH	AD4_DRL	AD5_DRH	AD5_DRL			AD7_DRH	AD7_DRL
0x0300	AD0_DRH	AD0_DRL	AD1_DRH	AD1_DRL	AD2_DRH	AD2_DRL		
<hr/>								
0x03f8	LPF0_K		LPF0_X		LPF0_YH		LPF0_YL	
0x03f0	LPF1_K		LPF1_X		LPF1_YH		LPF1_YL	
0x03e8	PI0_UKH		PI0_UKL		PI0_UKMAX		PI0_UKMIN	
0x03e0	PI0_KP		PI0_EK1		PI0_EK		PI0_KI	
0x03d8	PI1_UKH		PI1_UKL		PI1_UKMAX		PI1_UKMIN	
0x03d0	PI1_KP		PI1_EK1		PI1_EK		PI1_KI	
0x03C8	MUL0_MA		MUL0_MB		MUL0_MCH		MUL0_MCL	
0x03C0	MUL1_MA		MUL1_MB		MUL1_MCH		MUL1_MCL	
0x03B8	DIV0_DB		DIV0_DQH		DIV0_DQL		DIV0_DR	
0x03B0	DIV1_DQL		DIV1_DR		DIV0_DAH		DIV0_DAL	
0x03A8	DIV1_DAH		DIV1_DAL		DIV1_DB		DIV1_DQH	
0x03A0	LPF2_K		LPF2_X		LPF2_YH		LPF2_YL	
0x0398	LPF3_K		LPF3_X		LPF3_YH		LPF3_YL	
0x0390	PI2_UKH		PI2_UKL		PI2_UKMAX		PI2_UKMIN	
0x0388	PI2_KP		PI2_EK1		PI2_EK		PI2_KI	
0x0380	PI3_UKH		PI3_UKL		PI3_UKMAX		PI3_UKMIN	
0x0378	PI3_KP		PI3_EK1		PI3_EK		PI3_KI	
0x0370	MUL2_MA		MUL2_MB		MUL2_MCH		MUL2_MCL	
0x0368	MUL3_MA		MUL3_MB		MUL3_MCH		MUL3_MCL	
0x0360	DIV2_DB		DIV2_DQH		DIV2_DQL		DIV2_DR	
0x0358	DIV3_DQL		DIV3_DR		DIV2_DAH		DIV2_DAL	

Addr	0(8)	1(9)	2(A)	3(B)	4(C)	5(D)	6(E)	7(F)
0x0350	DIV3_DAH		DIV3_DAL		DIV3_DB		DIV3_DQH	
0x0348	SCAT0_SIN		SCAT0_THE		SCAT0_RES1		SCAT0_RES2	
0x0340	SCAT1_THE		SCAT1_RES1		SCAT1_RES2		SCAT0_COS	
0x0338	SCAT2_RES1		SCAT2_RES2		SCAT1_COS		SCAT1_SIN	
0x0330	SCAT3_RES2		SCAT2_COS		SCAT2_SIN		SCAT2_THE	
0x0328	SCAT3_COS		SCAT3_SIN		SCAT3_THE		SCAT3_RES1	

Note: Registers containing the symbol “_” shall be read using variables. If it is read directly, the value will be incorrect. The SFR is mapped partly to SFR sector of the Internal Data Memory, and partly to External Data Memory (also known as XSFR).

2 Pin Definitions

The IO types are defined as follows:

- DI = Digital Input
- DO = Digital Output
- DB = Digital Bidirectional
- AI = Analog Input
- AO = Analog Output
- P = Power Supply

2.1 ES9676AH WBQHFBP-45L Pins

Table 2-1 ES9676AH WBQHFBP-45L Pin Descriptions

Pin	ES9676AH WBQHFBP- 45L	IO Type	Function Description
VDRV	1	P	6N pre-driver power supply, with a 10μF external capacitor
VCC	2	P	Power input, with an external filter capacitor of 10μF or above. <ul style="list-style-type: none"> ■ High-voltage single-power supply mode: External power supply 12V~20V is connected to VCC pin, and internal LDO supplies VDD5 voltage.
VDD5	3	P	Medium-voltage power input or 5V LDO power output, with a 1μF ~4.7μF external capacitor. When VCC > 5.5V, VDD5 outputs 5V power supply.
RSTN/ FICEK	4	DI/ DI	Input of external reset; Built-in pull-up resistor; Schmit input FICE SCL
VDD18	5	P	1.85V LDO output with an external 1μF ~ 4.7μF capacitor
P1.2/ FICED	6	DB/ DB	GPIO, configurable as INT1 input FICE SDA
P1.3/ HBIAS/ C1PS	7	DB/ DO/ AI	GPIO Hall bias power supply, internally connected to VDD5 via a switch CMP1 positive input after function switching
P1.4/ COP/ AD10/ HALL0S	8	DB/ AI/ AI/ DI	GPIO, configurable as ITN1 input with a 4.7k pull-up resistor CMP0 positive input Input of ADC channel 10 Hall0 logic level input after function switching
P1.5/ COM	9	DB/ AI	GPIO, configurable as ITN1 input with a 4.7k pull-up resistor CMP0 negative input
P1.6/ C1P/ A1P/ AD9/ HALL1S	10	DB/ AI/ AI/ AI/ DI	GPIO, configurable as ITN1 input with a 4.7k pull-up resistor CMP1 positive input AMP1 positive input for voltage signals generated by phase current 1 Input of ADC channel 9 Hall1 logic level input after function switching
P2.1/ C2P/ A2P/ AD8/ HALL2S	11	DB/ AI/ AI/ AI/ DI	GPIO, configurable as ITN1 input with a 4.7k pull-up resistor CMP2 positive input AMP2 positive input for voltage signals generated by phase current 2 Input of ADC channel 8 Hall2 logic level input after function switching
P2.4/ AD2	12	DB/ AI	GPIO, configurable as INT1 input Input of ADC channel 2 or bus voltage signal
P2.6/ C3M/ DA0/ AD11	13	DB/ AI/ AO/ AI	GPIO, configurable as INT1 input Over-current reference signal input; CMP3 negative input Internal DAC voltage, without Buffer output Input of ADC channel 11

Pin	ES9676AH WBQHFBP- 45L	IO Type	Function Description
P2.7/ AD4/ C3P/ A0O	14	DB/ AI/ AI/ AO	GPIO, configurable as INT1 input Input of ADC channel 4 for collecting the amplified bus current signal CMP3 positive input for bus current sampling to detect overcurrent AMP0 output, the voltage output after the bus current is amplified
P3.0/ A0M	15	DB/ AI	GPIO AMP0 negative input for amplifying the bus current signal
P3.1/ A0P	16	DB/ AI	GPIO AMP0 positive input for amplifying the bus current signal
P3.2/ AD5/ VHALF	17	DB/ AI/ AO	GPIO Input of over-temperature signal or ADC channel 5 1/2 VDD5 or 1/2 VREF output with an external 1μF capacitor
P3.4/ AD7/ C3PS/ TXDS	18	DB/ AI/ AI/ DO	GPIO Analog voltage input for speed control or input of ADC channel7 CMP3 positive input after function switching UART TXD after function switching
P3.5/ VREF	19	DB/ AI	GPIO ADC external VREF input or internal VREF output, with a 1μF~4.7μF external capacitor
GND	20	P	Ground
P0.5/ TXD/ MOSI	21	DB/ DO/ DB	GPIO, configurable as INT0 input UART1 TXD SPI MOSI, master output or slave input
P0.6/ RXD/ SCLK	22	DB/ DB/ DB	GPIO, configurable as INT0 input UART1 RXD input in two-wire mode or TXD output/RXD input in single-wire mode SPI SCLK
P0.7/ MISO/ CXO/ TIM2S/ P1.0/ TIM2	23	DB/ DB/ DO/ DB/ DB/ DB	GPIO P0.7 SPI MISO, master input or slave output Test pin for comparator output Timer2 input capture mode or PWM output after function switching GPIO P1.0, configurable as INT1 input Timer2 input capture mode or PWM output
P1.1/ TIM3	24	DB/ DB	GPIO, configurable as INT0/INT1 input Timer3 input capture mode
SU	25	P	U-phase ground
SU	26	P	
U	27	DO	U-phase output
U	28	DO	
VM	29	P	Input of MOS power supply or high-voltage power supply
VM	30	P	
VM	31	P	
VM	32	P	
V	33	DO	V-phase output
V	34	DO	
SV	35	P	V-phase ground
SV	36	P	
VM	37	P	Input of MOS power supply or high-voltage power supply
VM	38	P	
SW	39	P	W-phase ground
SW	40	P	
W	41	DO	W-phase output
W	42	DO	

Pin	ES9676AH WBQHFBP- 45L	IO Type	Function Description
BW	43	P	W-phase high-side bootstrap supply
BV	44	P	V-phase high-side bootstrap supply
BU	45	P	U-phase high-side bootstrap supply

2.2 ES9676AH WBQHFBP-45L Pinout Diagram




Figure 2-1 ES9676AH WBQHFBP-45L Pinout Diagram

3 Package Information

3.1 WBQHFBP-45L_12X12




Figure 3-1 WBQHFBP-45L_12X12 Package Drawings

Table 3-1 WBQHFBP-45L Package Dimensions

Symbol	Dimensions In Millimeters			Dimensions In Inches		
	Min.	Nor.	Max.	Min.	Nor.	Max.
A	0.700	0.750	0.800	0.028	0.030	0.031
A1	0.000	-	0.050	0.000	-	0.002
A2	0.203REF.			0.008REF.		
D	12.000BSC.			0.472BSC.		
D1	5.340	5.440	5.540	0.210	0.214	0.218
D2	2.650	2.750	2.850	0.104	0.108	0.112
D3	2.650	2.750	2.850	0.104	0.108	0.112
D4	2.550	2.650	2.750	0.100	0.104	0.108
D5	2.650	2.750	2.850	0.104	0.108	0.112
E	12.000BSC.			0.472BSC.		
E1	4.319	4.419	4.519	0.170	0.174	0.178
E2	2.576	2.676	2.776	0.101	0.105	0.109
E3	1.450	1.550	1.650	0.057	0.061	0.065
E4	2.250	2.350	2.450	0.089	0.093	0.096
E5	3.350	3.450	3.550	0.132	0.136	0.140
L	0.400	0.500	0.600	0.016	0.020	0.024
L1	0.400	0.500	0.600	0.016	0.020	0.024
K	1.525REF.			0.060REF.		
K1	0.550REF.			0.022REF.		
K2	1.300REF.			0.051REF.		
K3	1.300REF.			0.051REF.		
K4	1.350REF.			0.053REF.		
K5	0.250REF.			0.010REF.		
K6	1.300REF.			0.051REF.		
K7	1.300REF.			0.051REF.		
K8	1.300REF.			0.051REF.		
K9	1.050REF.			0.041REF.		
K10	0.600REF.			0.024REF.		
K11	1.299REF.			0.051REF.		
K12	1.435REF.			0.056REF.		
K13	1.300REF.			0.051REF.		
K14	1.300REF.			0.051REF.		
K15	1.880REF.			0.074REF.		
b	0.200	0.250	0.300	0.008	0.010	0.012
b1	0.350	0.400	0.450	0.014	0.016	0.018
b2	0.600	0.650	0.700	0.024	0.026	0.028
e	0.500BSC.			0.020BSC.		
e1	0.925BSC.			0.036BSC.		
e2	0.900BSC.			0.035BSC.		
e3	1.951BSC.			0.077BSC.		
e4	0.900BSC.			0.035BSC.		
e5	2.349BSC.			0.092BSC.		
e6	0.900BSC.			0.035BSC.		
e7	0.900BSC.			0.035BSC.		
e8	2.350BSC.			0.093BSC.		
e9	0.900BSC.			0.035BSC.		
e10	1.750BSC.			0.069BSC.		
e11	1.775BSC.			0.070BSC.		
e12	0.975BSC.			0.038BSC.		
e13	1.550BSC.			0.061BSC.		

4 Ordering Information

Table 4-1 Model Selections

Model	R_{dson} (H+L) (Ω)	MIPS (Peak)	Flash (kByte)	XRAM (kByte)	Clock Circuit		Driver Type	Analog Peripherals								Package						
					Internal Fast Clock	Internal Slow Clock		ADC		DAC		V_{REF}	Operational Amplifier	Comparator	Lead-free							
					Square Wave	FOC	SPI/UART	DMA	GPIO	Timer	Number	Channel	Bits	Number	Bits	Number	Bits					
ES9676AH	2.2	24	16	0.75	√	√	√	√	√	√	18	6	1	10	12	1	9	√	3	2	√	WBQHFBD-45L (12x12mm)

5 Electrical Characteristics

5.1 Absolute Maximum Ratings

Table 5-1 Absolute Maximum Ratings^[1]

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
MOSFET Drain-to-Source Voltage V _{DSS}		600	-	-	V
Continuous Drain Current I _{DMAX(DC)} of Single MOS	T _C = 25°C	-	-	4 ^[2]	A
Pulse Drain Current I _{DMAX(PLS)} of Single MOS	T _C = 25°C	-	-	11 ^{[2][3]}	A
Power Dissipation P _d of Single MOS ^[4]	T _C = 25°C	-	-	64.4	W
High-side VDC Supply Voltage V _{DC}		-0.3	-	600 ^[2]	V
U/V/W-phase Output Voltage V _U , V _V , V _W		-0.3	-	600 ^[2]	V
High-side Floating Absolute Voltage V _{BU} , V _{BV} , V _{BW}		-0.3	-	600 ^[2]	V
High-side Floating Supply Voltage V _{BU} - V _U , V _{BV} - V _V , V _{BW} - V _W		-0.3	-	22	V
Operating Ambient Temperature T _A		-40	-	85	°C
Operating Junction Temperature T _J		-40	-	150	°C
Storage Temperature		-55	-	150	°C
VCC to VSS Voltage		-0.3	-	36	V
VDRV to VSS Voltage		-0.3	-	22	V
VDD5 to VSS Voltage		-0.3	-	6.5	V
RSTN/GPIO to VSS Voltage		-0.3	-	VDD5 + 0.3	V

Notes:

[1] Stress values greater than "Absolute Maximum Ratings" listed above may cause irremediable damages to the device. These are stress ratings only, and it is NOT recommended to use your device in conditions that go beyond these stress ratings. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

[2] Power dissipation shall not exceed P_d or ASO;

[3] P_w ≤ 10μs and duty cycle ≤ 1%;

[4] T0252 package is applied to single-channel MOS at ambient temperature of 25°C.

5.2 Recommended Operating Conditions

Table 5-2 Recommended Operating Conditions

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
High-side VDC Supply Voltage V _{DC}		-	310	400	V
High-side Floating Supply Voltage V _{BU} - V _U , V _{BV} - V _V , V _{BW} - V _W		12	15	20	V
VCC/VDRV to VSS Voltage		11	15	20	V
Junction Temperature T _J		-	-	125	°C

5.3 Global Electrical Characteristics

Table 5-3 Global Electrical Characteristics

($T_A = 25^\circ\text{C}$ and $VCC = 12V \sim 20V$ unless otherwise specified)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
VCC/VDRV Operating Voltage ^{[1][2]}		12	-	20	V
Drain-to-source Leakage Current IDSS of Single-channel MOS		-	-	100	μA
Static Drain-to-source On Resistance of Single-channel MOS		-	1.1	1.5	Ω
Drain-to-source Diode Forward Voltage Drop of Single-channel MOS		-	-	1.4	V
I_{VCC} Operating Current ^[3]		-	24	-	mA
I_{VCC} Standby Current ^[3]		-	6	-	mA
I_{VCC} Sleep-mode Current		-	210	-	μA

Notes:

[1] VCC voltage rise rate ranges from $0.5\text{V}/\mu\text{s}$ to $0.1\text{V}/\text{s}$ depending on samples batches.

[2] VDD5 must be in the range of $5\text{V} \sim 5.5\text{V}$ during Flash write or erase.

[3] Characteristics may vary with different configurations.

5.4 GPIO Electrical Characteristics

Table 5-4 GPIO Electrical Characteristics

($T_A = 25^\circ\text{C}$ and $VCC = 12V \sim 20V$ unless otherwise specified)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Output Rise Time	50pF load, from 10% to 90%, $T_A = 25^\circ\text{C}$	-	15	-	ns
Output Fall Time	50pF load, from 90% to 10%, $T_A = 25^\circ\text{C}$	-	13	-	ns
V_{OH} High-level Output Voltage	$I_{OH} = 4\text{mA}$, $T_A = 40^\circ\text{C} \sim 85^\circ\text{C}$	VDD5 - 0.7	-	-	V
V_{OL} Low-level Output Voltage	$I_{OL} = 4\text{mA}$, $T_A = 40^\circ\text{C} \sim 85^\circ\text{C}$	-	-	VSS + 0.7	V
V_{IH} High-level Input Voltage ^[1]		0.7*VDD5	-	-	V
V_{IL} Low-level Input Voltage		-	-	0.2*VDD5	V
Pull-up Resistor ^[2]		-	33	-	k Ω
Pull-up Resistor ^[3]		-	5.6	-	k Ω

Notes:

[1] When VDD5 = 5V, minimum value of V_{IH} is $0.6 * VDD5$.

[2] GPIOs except P1[6:3] and P2[1].

[3] P1[6:3] and P2[1].

5.5 ADC Electrical Characteristics

Table 5-5 ADC Electrical Characteristics

($T_A = 25^\circ\text{C}$ and $VCC = 12V \sim 20V$ unless otherwise specified)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
INL (Integral Nonlinearity)	12-bit	-	2	-	LSB
DNL (Differential Nonlinearity)	12-bit	-	1.5	-	LSB
OFFSET (Offset Error)	12-bit	-	6	-	LSB
SNR (Signal-to-noise Ratio)	$f_{IN} = 350\text{kHz}$	-	70.8	-	dB
ENOB (Effective Number of Bits)	$f_{IN} = 350\text{kHz}$	-	10.5	-	Bit
SFDR (Spurious-free Dynamic Range)	$f_{IN} = 350\text{kHz}$	-	68.2	-	dB
THD (Total Harmonic Distortion)	$f_{IN} = 350\text{kHz}$	-	67	-	dB
R_{IN} Input Resistance		-	800	-	Ω
C_{IN} Input Capacitance		-	30	-	pF
Conversion Time		-	13	-	ADCLK ^[1]
Sampling Time		3	-	63	ADCLK ^[1]

Note:

[1] ADCLK = 12MHz

5.6 VREF and VHALF Electrical Characteristics

Table 5-6 VREF and VHALF Electrical Characteristics

($T_A = -40^\circ\text{C} \sim 85^\circ\text{C}$ and $VCC = 12V \sim 20V$)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
VREF	VREF_CR[VREFSEL] = 00	4.3	4.5	4.7	V
	VREF_CR[VREFSEL] = 01	-	VDD5	-	V
	VREF_CR[VREFSEL] = 11	-	4	-	V
	VREF_CR[VREFSEL] = 10	-	3	-	V
VHALF	VREF_CR[VHALFSEL] = 00	-	VREF/8	-	V
	VREF_CR[VHALFSEL] = 01	-	VREF/4	-	V
	VREF_CR[VHALFSEL] = 10	-	25*VREF/64	-	V
	VREF_CR[VHALFSEL] = 11	VREF/2 - 0.2	VREF/2	VREF/2 + 0.2	V

5.7 Operational Amplifier Electrical Characteristics

Table 5-7 Operational Amplifier Electrical Characteristics

($T_A = 25^\circ\text{C}$ and $VCC = 12V \sim 20V$ unless otherwise specified)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{ICMR} Common-mode Input Voltage Range		0	-	VDD5 - 1.5	V
V _{OS} Operational Amplifier Offset Voltage	$T_A = 25^\circ\text{C}$	-	5	10	mV
A _{OL} Open-loop Gain	$R_L = 100\text{k}\Omega$	-	80	-	dB
Unity-gain Bandwidth (UGBW)	$C_L = 40\text{pF}$	6	10	-	MHz

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Slew Rate (SR)	$C_L = 40\text{pF}$	10	15	-	$\text{V}/\mu\text{s}$
Operational Amplifier Gain ^[1]	AMP_CR1[AMP0_GAIN] = 001	1.88	2	2.12	-
	AMP_CR1[AMP0_GAIN] = 010	3.76	4	4.24	-
	AMP_CR1[AMP0_GAIN] = 011	7.5	8	8.5	-
	AMP_CR1[AMP0_GAIN] = 100	15	16	17	-

Note:

[1] The operational amplifier gain is measured when both positive and negative inputs of the operational amplifier are connected in series with $1\text{k}\Omega$ resistors. The operational amplifier gain varies with external resistors.

5.8 BEMF Electrical Characteristics

Table 5-8 BEMF Electrical Characteristics

($T_A = 25^\circ\text{C}$, VCC_MODE = 0 and VCC = 12V ~ 20V unless otherwise specified)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
BEMF Built-in Resistor		5.4	6.8	8.2	$\text{k}\Omega$
Relative Accuracy between BEMF Built-in Resistors		-	1	-	%

5.9 OSC Electrical Characteristics

Table 5-9 OSC Electrical Characteristics

($T_A = -40^\circ\text{C} \sim 85^\circ\text{C}$, VCC_MODE = 0 and VCC = 12V ~ 20V)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
System Clock Rate		23.5	24	24.5	MHz
Low-speed Clock Rate		29	32.8	37	kHz

Note: SYSCLK refers to system clock rate, and T to system clock cycle. Unless otherwise specified, the system clock rate of chip is 24MHz and T = 1/SYSCLK.

5.10 Reset Electrical Characteristics

Table 5-10 Reset Electrical Characteristics

($T_A = 25^\circ\text{C}$, VCC_MODE = 0 and VCC = 12V ~ 20V unless otherwise specified)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Minimum Time for RSTN Released to Low		50	-	-	μs
VDD5 Reset Threshold	Reset Voltage LVR = 3.0V	2.8	3.0	3.2	V

5.11 LDO Electrical Characteristics

Table 5-11 LDO Electrical Characteristics

(TA = 25°C, VCC_MODE = 0 and VCC = 12V ~ 20V unless otherwise specified)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
VDD5 Voltage	VCC = 12V ~ 20V and VCC_MODE = 0	4.7	5	5.3	V
VDD18 Voltage		1.65	1.85	2.0	V

5.12 Package Thermal Resistance

Table 5-12 Package Thermal Resistance

Parameter	Test Conditions	Value	Unit
Junction-to-ambient Temperature Thermal Resistance $\theta_{JA}^{[1]}$	JEDEC standard, 2S2P PCB	27.7	°C/W

Note:

[1] The actual measurements may vary depending on the conditions.

6 Reset Control

6.1 Reset Source (RST_SRC)

The chip includes a reset circuitry with 6 reset sources:

- Power on reset (RSTPOW)
- External pin reset (RSTEXT)
- Low voltage detector reset (RSTLVD)
- Watchdog timer reset (RSTWDT)
- Flash error detector reset (RSTFED)
- Debug reset (RSTDBG)

The reset flag is queryable and recorded in register RST_SR. Following the last reset, the affected reset flag is set to “1” and all other reset flags are cleared to “0”. You can set RST_SR[RSTCLR] flag to “1” in the software to clear the reset flag RST_SR[7:3].

6.2 Reset Enable

See corresponding control registers. Reset sources of LVD and WDT are always enabled.

6.3 External Reset and Power-on Reset

The chip resets if RSTN pin remains low for 50μs. After reset, MCU starts the program from address 0x0000. The chip also resets after the chip powers on and the voltage settles above the reset threshold.

6.4 Low Voltage Detector reset

The chip’s internal circuitry monitors VDD5. When VDD5 voltage drops to a level below the reset threshold V_{RST} , the internal monitor circuitry sends a LVD reset signal to reset the chip.

Configuring corresponding register enables VDD5 monitor circuitry and sets V_{RST} .

6.5 Watchdog Timer Reset

After the watchdog timer (WDT) is enabled, the system is reset if WDT is not initialized before it gets overflowed. In this case, when WDT reaches its maximum value, it generates an output pulse to reset the chip, which ensures the software runs normally.

6.6 Flash Error Detector Reset

The Flash memory can be programmed by the software using MOVX instruction for read/write/erase operations (See section 34 Code Protection). A Flash error detector reset (RSTFED) occurs if a Flash erase is attempted targeting the last sector (0x3F80~0x3FFF). RSTFED is always enabled and cannot be disabled.

6.7 Debug Reset

Click **Reset** button of IDE to send a debug reset signal when the chip enters the debug state.

6.8 Reset Registers

6.8.1 RST_SR (0xC9)

Bit	7	6	5	4	3	2	1	0
Name	RSTPOR	RSTEXT	RSTLVD	RSV	RSTWDT	RSTFED	RSTDBG	RSTCLR
Type	R	R	R	-	R	R	R	W1
Reset	-	-	-	-	-	-	-	0
Bit	Name	Description						
[7]	RSTPOW	Power-On Reset Flag 0: Last reset was not a power-on reset. 1: Last reset was a power-on reset.						
[6]	RSTEXT	External Reset Flag 0: Last reset was not an external reset. 1: Last reset was an external reset.						
[5]	RSTLVD	Low Voltage Detection (LVD) Reset Flag 0: Last reset was not an LVD reset. 1: Last reset was an LVD reset.						
[4]	RSV	Reserved						
[3]	RSTWDT	WDT Reset Flag 0: Last reset was not a WDT reset. 1: Last reset was a WDT reset.						
[2]	RSTFED	Flash Error Detector Reset Flag 0: Last reset was not a Flash error detector reset. 1: Last reset was a Flash error detector reset.						
[1]	RSTDBG	Debug Reset Flag 0: Last reset was not a debug reset. 1: Last reset was a debug reset.						
[0]	RSTCLR	Clear Analog Reset Flags Register The reset flags [7:3] are cleared after “1” is written to this bit. This bit has no effect when it is read.						

7 Interrupt

7.1 Interrupt Introduction

The chip includes an interrupt system with a total of 15 interrupt sources. Each interrupt source can be individually programmed in IP0 ~ IP3 registers with one of four priority levels. Interrupt flags (IF) are located in an SFRs or XSFRs. The associated IF is set by the hardware to 1 when the internal circuitry or an external source meets the interrupt conditions. If IE[EA] = 1 and both the associated interrupt EA and IF bits are set to “1”, an interrupt request is generated and sent to CPU. If no other interrupt service routine (ISR) of greater priority is currently being serviced, the system enters interrupt state to service the requesting ISR.

Each interrupt source except the Reset Interrupt can be assigned a priority level. A low priority interrupt can be interrupted by a high priority interrupt. The low priority interrupt will not be serviced until the ISR for the high priority interrupt completes. An interrupt will not be preempted by another of the same priority level. Each interrupt source can be individually configured to one of four priority levels in the Interrupt Priority (IP) register. Priority level assigned ascends from 0 to 3 and is defaulted to 0. If two interrupt requests are generated at the same time, the interrupt with the higher priority is serviced first. If two interrupt sources have the same priority level, a fixed priority order is used to arbitrate. See Table 7-1 Interrupt Summary for the interrupt sources and default priority orders, where the lower the mark the higher the priority level.

7.2 Interrupt Enable

IE[EA] is the global interrupt enable bit. The MCU does not respond to any interrupt request when IE[EA] = 0.

Each interrupt source can be individually enabled or disabled by configuring the corresponding interrupt enable bit in an SFR or XSFR. When the enable bit of the global interrupt or an interrupt is cleared, the interrupt flag that is set to “1” is held in a pending state. Once the enable bit is set to “1”, MCU immediately enters the interrupt subroutine. Therefore, make sure to clear corresponding interrupt flag bit before enabling the interrupt.

7.3 External Interrupt

The external interrupt has 2 interrupt sources: INT0 and INT1. They both can be configured as interrupt on rising edge, interrupt on falling edge or interrupt on edge changes (rise or fall).

The digital input signals from P0.5 ~ P0.6 and P1.1 can be used to trigger an INT0. The interrupt source is selected through LVSR[EXT0CFG] bit. These trigger sources share one interrupt entry point, one interrupt flag bit TCON[IF0] and one interrupt enable bit IE[EX0]. TCON[IT0] bit selects the interrupt edge. IP0[PX0] bit configures the priority level.

The digital input signals from P1.0 ~ 1.6, P2.1, P2.4 and P2.6 ~ 2.7 can be used to trigger an INT1. P1_IF and P4_IF are interrupt flag bits, and P1_IE and P4_IE are interrupt enable bits. Each trigger source

has a corresponding interrupt flag bit and an interrupt enable bit. INT1 can select multiple trigger sources that are recognized by P1_IF and P4_IF in the interrupt subroutine. These 15 interrupt sources share one interrupt entry and one interrupt enable bit IE[EX1]. To enable INT1, first set IE[EX1] to “1” and then configure the corresponding enable bit. The interrupt edge is configured by TCON[IT1] bit, and the priority level by IP0[PX1] bit. See section 7.5.7 P1_IE (0xD1) ~ section 7.5.10 P4_IF (0xD4) for INT1 interrupt flags and enable registers.

7.4 Interrupt Summary

Table 7-1 Interrupt Summary

Interrupt Source	Priority Order	Interrupt Vector	Interrupt Flag	Cleared by SW?	Enable Bit	Priority Control
Reset	Highest	0x0000	None	N	Always enabled	Highest
LVW Interrupt	0	0x0003	LVSR[0]	Y	CCFG1[6]	IP0[1:0]
INT0	1	0x000B	TCON[2]	Y	IE[0]	IP0[3:2]
INT1	2	0x0013	P1IF[7:0]P2IF[7:0]	Y	IE[2]	IP0[5:4]
FG Interrupt DRV Interrupt	3	0x001B	DRV_SR[5:4]	Y	DRV_SR[2:0]	IP0[7:6]
TIM2 Interrupt	4	0x0023	TIM2_CR1[7:5]	Y	TIM2_CR1[4:3] TIM2_CR0[3]	IP1[1:0]
TIM1 Interrupt	5	0x002B	TIM1_SR[4:0]	Y	TIM_IER[4:0]	IP1[3:2]
ADC Interrupt	6	0x0033	ADC_CR[0]	Y	ADC_CR[1]	IP1[5:4]
CMP0/1/2 Interrupt	7	0x003B	CMP_SR[7:4]	Y	CMP_CR0[7:0]	IP1[7:6]
RTC	8	0x0043	RTC_STA[6]	Y	IE[6]	IP2[1:0]
TIM3 Interrupt	9	0x004B	TIM3_CR1[7:5]	Y	TIM3_CR1[4:3] TIM3_CR0[3]	IP2[3:2]
TIM4 Interrupt Systick Interrupt	10	0x0053	TIM4_CR1[7:5] DRV_SR[7]	Y	TIM4_CR1[4:3] TIM4_CR0[3] DRV_SR[6]	IP2[5:4]
TSD Interrupt	11	0x005B	TCON[5]	Y	IE[1]	IP2[7:6]
UART Interrupt	12	0x0063	UT_CR[1:0]	Y	IE[4]	IP3[1:0]
SPI Interrupt	13	0x0073	SPI_CR1[7]	Y	SPI_CR1[0]	IP3[5:4]
DMA Interrupt	14	0x007B	DMA0_CR0[7] DMA1_CR0[7]	Y	DMA0_CR0[2]	IP3[7:6]

As shown above, the chip includes an interrupt system with a total of 15 interrupt sources. Each interrupt source can be individually programmed in IP0 ~ IP3 registers with one of four priority levels. A low priority interrupt can be interrupted by a high priority interrupt. If two interrupt sources have the same priority level, they are processed in an order as listed in the above table, where the lower the mark the higher the priority level. An interrupt will not be preempted by another of the same priority level.

IE[EA] is the global interrupt enable bit. The MCU does not respond to any interrupt request when IE[EA] = 0.

7.5 Interrupt Registers

7.5.1 IE (0xA8)

Bit	7	6	5	4	3	2	1	0
Name	EA	RTCIE	RSV	ES0	SPIIE	EX1	TSDIE	EX0
Type	R/W	R/W	-	R/W	R/W	R/W	R/W	R/W
Reset	0	0	-	0	0	0	0	0
Bit Name Description								
[7]	EA	Enable All Interrupts 0: Disable 1: Enable						
[6]	RTCIE	RTC Interrupt Enable 0: Disable 1: Enable						
[5]	RSV	Reserved						
[4]	ES0	UART Interrupt Enable 0: Disable 1: Enable						
[3]	SPIIE	SPI Interrupt Enable 0: Disable 1: Enable						
[2]	EX1	External Interrupt 1 (INT1) Enable 0: Disable 1: Enable						
[1]	TSDIE	TSD Interrupt Enable 0: Disable 1: Enable						
[0]	EX0	External Interrupt 0 (INT0) Enable 0: Disable 1: Enable						

7.5.2 IP0 (0xB8)

Bit	7	6	5	4	3	2	1	0
Name	PDRV		PX1		PX0		PLVW	
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit Name Description								
[7:6]	PDRV	Driver Interrupt Priority Setting						
[5:4]	PX1	External Interrupt 1 (INT1) Priority Setting						
[3:2]	PX0	External Interrupt 0 (INT0) Priority Setting						
[1:0]	PLVW	LVW Interrupt Priority Setting						

Note: Priority level assigned ascends from 0 to 3, totaling 4 levels.

7.5.3 IP1 (0xC0)

Bit	7	6	5	4	3	2	1	0
Name	PCMP		PADC		PTIM1		PTIM2	
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:6]	PCMP	CMP0/1/2 Interrupt Priority Setting						
[5:4]	PADC	ADC Interrupt Priority Setting						
[3:2]	PTIM1	Timer1 Interrupt Priority Setting						
[1:0]	PTIM2	Timer2 Interrupt Priority Setting						

Note: Priority level assigned ascends from 0 to 3, totaling 4 levels.

7.5.4 IP2 (0xC8)

Bit	7	6	5	4	3	2	1	0
Name	PTSD		PTIM4		PTIM3		PRTC	
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:6]	PTSD	TSD Interrupt Priority Setting						
[5:4]	PTIM4	Timer4 and Systick Interrupt Priority Setting						
[3:2]	PTIM3	Timer3 Interrupt Priority Setting						
[1:0]	PRTC	RTC Interrupt Priority Setting						

Note: Priority level assigned ascends from 0 to 3, totaling 4 levels.

7.5.5 IP3 (0xD8)

Bit	7	6	5	4	3	2	1	0
Name	PDMA		PSPI		RSV		PUART	
Type	R/W	R/W	R/W	R/W	-	-	R/W	R/W
Reset	0	0	0	0	-	-	0	0
Bit	Name	Description						
[7:6]	PDMA	DMA Interrupt Priority Setting						
[5:4]	PSPI	SPI Interrupt Priority Setting						
[3:2]	RSV	Reserved						
[1:0]	PUART	UART Interrupt Priority Setting						

Note: Priority level assigned ascends from 0 to 3, totaling 4 levels.

7.5.6 TCON (0x88)

Bit	7	6	5	4	3	2	1	0
Name	RSV		TSDIF	IT1		IF0	IT0	
Type	-	-	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	-	0	0	0	0	0	0
Bit	Name	Description						
[7:6]	RSV	Reserved						
[5]	TSDIF	TSD Interrupt Flag This bit is set to “1” by hardware when the chip exceeds the set temperature. Read: 0: No Interrupt Pending 1: Interrupt Pending						

		Write: 0: This bit is cleared to “0” 1: No effect
[4:3]	IT1[1:0]	External Interrupt 1 (INT1) Edge Select 00: Interrupt on rising edge 01: Interrupt on falling edge 1X: Interrupt on edge changes (rise or fall)
[2]	IF0	External Interrupt 0 (INT0) Interrupt Flag Read: 0: No Interrupt Pending 1: Interrupt Pending Write: 0: This bit is cleared to “0” 1: No effect
[1:0]	IT0[1:0]	External Interrupt 0 (INT0) Edge Select 00: Interrupt on rising edge 01: Interrupt on falling edge 1X: Interrupt on edge changes (rise or fall)

7.5.7 P1_IE (0xD1)

Bit	7	6	5	4	3	2	1	0
Name	P17_IE	P16_IE	P15_IE	P14_IE	P13_IE	P12_IE	P11_IE	P10_IE
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	P17_IE	P1.7 INT1 Enable 0: Disable 1: Enable						
[6]	P16_IE	P1.6 INT1 Enable 0: Disable 1: Enable						
[5]	P15_IE	P1.5 INT1 Enable 0: Disable 1: Enable						
[4]	P14_IE	P1.4 INT1 Enable 0: Disable 1: Enable						
[3]	P13_IE	P1.3 INT1 Enable 0: Disable 1: Enable						
[2]	P12_IE	P1.2 INT1 Enable 0: Disable 1: Enable						
[1]	P11_IE	P1.1 INT1 Enable 0: Disable 1: Enable						
[0]	P10_IE	P1.0 INT1 Enable 0: Disable 1: Enable						

7.5.8 P1_IF (0xD2)

Bit	7	6	5	4	3	2	1	0
Name	P17_IF	P16_IF	P15_IF	P14_IF	P13_IF	P12_IF	P11_IF	P10_IF
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
<hr/>								
Bit	Name	Description						
[7]	P17_IF	P1.7 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[6]	P16_IF	P1.6 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[5]	P15_IF	P1.5 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[4]	P14_IF	P1.4 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[3]	P13_IF	P1.3 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[2]	P12_IF	P1.2 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[1]	P11_IF	P1.1 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[0]	P10_IF	P1.0 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						

7.5.9 P4_IE (0xD3)

Bit	7	6	5	4	3	2	1	0
Name	P04_IE	P46_IE	P45_IE	P44_IE	P36_IE	P42_IE	P41_IE	P07_IE
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
<hr/>								
Bit	Name	Description						
[7]	P04_IE	P0.4 INT1 Enable 0: Disable 1: Enable						
[6]	P46_IE	P4.6 INT1 Enable 0: Disable 1: Enable						
[5]	P45_IE	P4.5 INT1 Enable 0: Disable 1: Enable						
[4]	P44_IE	P4.4 INT1 Enable 0: Disable 1: Enable						
[3]	P36_IE	P3.6 INT1 Enable 0: Disable 1: Enable						

[2]	P42_IE	P4.2 INT1 Enable 0: Disable 1: Enable
[1]	P41_IE	P4.1 INT1 Enable 0: Disable 1: Enable
[0]	P07_IE	P0.7 INT1 Enable 0: Disable 1: Enable

7.5.10 P4_IF (0xD4)

Bit	7	6	5	4	3	2	1	0
Name	P04_IF	P46_IF	P45_IF	P44_IF	P36_IF	P42_IF	P41_IF	P07_IF
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	P04_IF	P0.4 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[6]	P46_IF	P4.6 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[5]	P45_IF	P4.5 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[4]	P44_IF	P4.4 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[3]	P36_IF	P3.6 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[2]	P42_IF	P4.2 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[1]	P41_IF	P4.1 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						
[0]	P07_IF	P0.7 INT1 Interrupt Flag 0: No Interrupt Pending 1: Interrupt Pending						

8 SPI

8.1 SPI Introduction

SPI provides access to a high-speed, full-duplex synchronous serial bus, with its block diagram shown in Figure 8-1. SPI can operate as a master or slave device in 3-wire or 4-wire mode, and supports multiple masters and slaves on a single SPI bus.




Figure 8-1 SPI Block Diagram

8.2 SPI Operations

8.2.1 Signal Descriptions

The four signals for SPI are MOSI, MISO, SCLK and NSS.

8.2.1.1 Master Output, Slave Input (MOSI)

The master-out, slave-in (MOSI) signal is an output from a master device and an input to slave devices. It is used to serially transfer data from the master to the slave. Data is transferred with most-significant bit (MSB) first, namely, the master begins its transmission by driving the MSB of the shift register on its MOSI pin.

8.2.1.2 Master Input, Slave Output (MISO)

The MISO signal is an output from a slave device and an input to the master device. The MISO pin is placed in a high-impedance state when the SPI module is disabled or when the SPI operates in 4-wire mode as a slave that is not selected. When the SPI acts as a slave in 3-wire mode that is selected, MISO is used to serially transfer data from the slave to the master. Data is transferred with most-significant bit (MSB) first, namely, the master begins its transmission by driving the MSB of the shift register on its MOSI pin.

8.2.1.3 Serial Clock (SCLK)

The serial clock (SCLK) signal is an output from the master device and an input to slave devices. It is used to synchronize serial data transmission between the master and slave. SCLK signal is generated by SPI operating as a master.

8.2.1.4 Slave Select (NSS)

The slave-select (NSS) is dependent on the setting of SPI_CR1[NSSMOD] bit. SPI may operate in 3-Wire Mode or 4-Wire Single Master Mode. When SPI operates in 4-Wire Single Master Mode, the master NSS is configured as chip select output. When SPI operates in 3-Wire Mode, NSS is disabled. When SPI operates as a master, multiple addressed slave devices can be selected using general-purpose I/O pins.

When SPI_CR1[NSSMOD] = 00, SPI operates in 3-Wire Mode. NSS port is not necessary in this mode and there is only one master and one slave on the SPI bus. The connection diagram is shown in Figure 8-2.




Figure 8-2 Connection Diagram of 3-Wire Single Master/Slave Mode

When SPI_CR1[NSSMOD] = 01, SPI operates in 4-Wire Mode. In this mode, NSS pins on the SPI bus are configured as inputs, waiting to be addressed by the master. When SPI_CR0[SPIMS] = 0, SPI operates in 4-Wire Slave Mode. In this case, data is transferred via SPI after the slave NSS is pulled down by two system cycles. When SPI_CR0[SPIMS] = 1, SPI operates in Multi-Master Mode. In this case, when NSS pin of a master on the SPI bus is pulled low, SPI_CR1[MODF] is set to “1” to disable the SPI and the master acts as a slave. The connection diagram is shown in Figure 8-3.




Figure 8-3 Connection Diagram of 4-Wire Multi-Master Mode

When SPI_CR1[NSSMOD] = 1X, SPI operates in 4-Wire Mode that is valid in master mode only. In this case, SPI_CR1[NSSMOD0] setting decides the output level of NSS pin. When SPI_CR1[NSSMOD0] = 1, NSS pin outputs high level, and when SPI_CR1[NSSMOD0] = 0, the pin outputs low level. The connection diagram is shown in Figure 8-4.




Figure 8-4 Connection Diagram of 4-Wire Master/Single Mode

8.2.2 SPI Master Mode

When SPI_CR0[SPIMS] = 1, SPI operates in master mode, which provides SCLK signal for the bus. When the data is written to SPI_DR, it is firstly written to the transmit buffer and SPI_CR1[TXBMT] is cleared to “0”. If the shift register is empty, then the data in the transmit buffer will be transferred to the shift register for the transmission. The master SPI begins its transmission by driving the MSB of shift register on its MOSI pin. After the transmission is completed, SPI_CR1[SPIIF] and SPI_CR1[TXBMT] are set to “1”. While the SPI master transfers data to a slave on the MOSI line, the addressed SPI slave simultaneously transfers data in the shift register to the SPI master on the MISO line in a full-duplex operation. Therefore, SPI_CR1[SPIIF] flag serves as both a transmit-complete flag and a receive-data-ready flag, and the data in the shift register is that received by MISO, which is transferred to the receive buffer. The data from SPI_DR is that of the receive buffer. If the data is written to SPI_DR when SPI_CR1[TXBMT] is “0”, the write conflict flag bit SPI_CR1[WCOL] will be set to “1” and the data in the transmit buffer keeps unchanged.

8.2.2.1 Master Mode Configurations

1. Configure SPI_CR1[NSSMOD] to set the SPI operating mode;
2. Configure SPI_CR0[CPOL] to set the clock polarity;
3. Configure SPI_CR0[CPHA] to set the clock phase;
4. Set SPI_CR0[SPIMS] to “1” to select master mode;
5. Configure SPI_CLK to set the SCK rate;
6. Set SPI_CR1[SPIEN] to “1” to enable SPI;
7. Write the data to SPI_DR. SPI transmits data for each write;
8. After SPI_CR1[SPIIF] is set to “1”, SPI_DR is read to receive the data.

8.2.3 SPI Slave Mode

When SPI_CR0[SPIMS] = 0, SPI operates in slave mode. In this mode, SCLK signal is sent by the

master SPI. The data is shifted from MOSI pin and shifted out from MISO pin. If no SCLK signal is input, shift register of the slave is in the stop state. If the signal of SCLK is input, the shift register of slave starts to receive and transmit data through MOSI and MISO pins. The slave device cannot initiate transfers. The data sent to the master device is pre-loaded into the shift register by writing to SPI_DR. If the shift register is empty, the data in the transit buffer is transferred into the shift register. After the transmission is completed, SPI_CR1[SPIIF] and SPI_CR1[TXBMT] are set to “1”. The received data that is transferred into receive buffer and receive buffer empty flag bit SPI_CR0[RXBMT] is cleared, indicating the new data has not been read. If SPI_CR0[RXBMT] is 0 and there is new data ready to be sent to the receive buffer, SPI_CR1[RXOVRN] is set to “1” and the data in the receive buffer remains unaffected. When data is written to SPI_DR, SPI_CR1[TXBMT] is cleared. If data is written in this case, the write conflict flag bit SPI_CR1[WCOL] is set to “1” and the data in the transmit buffer keeps unchanged.

8.2.3.1 Slave Mode Configurations

1. Configure SPI_CR1[NSSMOD] to set the SPI operating mode;
2. Configure SPI_CR0[CPOL] to set the clock polarity;
3. Configure SPI_CR0[CPHA] to set the clock phase;
4. Set SPI_CR0[SPIMS] to 0 to select slave mode;
5. Set SPI_CR1[SPIEN] to 1 to enable SPI;
6. Write data to SPI_DR and wait for the master to transmit the clock signal.

8.2.4 SPI Interrupt Sources

After SPI interrupt is enabled (IE[SPIIE] = 1), an interrupt is generated when any of the three following flag bits are set to “1”.

Note: These flag bits can be cleared to “0” by software only.

1. SPI interrupt flag SPI_CR1[SPIIF] is set to “1” each time after the byte is transferred. It applies to all SPI modes.
2. If SPI_DR is written when the data in transmit buffer has not been transferred to the shift register, the write conflict flag SPI_CR1[WCOL] is set to “1” and the write operation will not be implemented. It applies to all SPI modes.
3. The receive overflow flag SPI_CR1[RXOVRN] is set to “1” when SPI operates in slave mode and a transmission is completed while the receive buffer still holds unread data from a previous transfer. And the received data will not be transferred to the receive buffer.

8.2.5 Serial Clock Timing

Four combinations of serial clock phase and idle polarity can be selected using the CPHA and CPOL bits in the SPI_CR0 Register. SPI_CR0[CPHA] selects the clock phase (the edge of the SCLK signal used to

latch the data in shift register). SPI_CR0[CPOL] selects the polarity. Both master and slave devices must be configured with the same clock phase and polarity. When the clock phase and polarity is configured, SPI shall be disabled (SPI_CR1[SPIEN] = 0).

Note: The timing relationship between SCL and SDA in master mode is shown in Figure 8-5, and that in slave mode is shown in Figure 8-6 and Figure 8-7.




Figure 8-5 SDA/SCL Line Timing Diagram in Master Mode




Figure 8-6 SDA/SCL Line Timing Diagram in Slave Mode (SPI_CR0[CPHA] = 0)




Figure 8-7 SDA/SCL Line Timing Diagram in Slave Mode (SPI_CR0[CPHA] = 1)

8.3 SPI Registers

8.3.1 SPI_CR0 (0x4030)

Bit	7	6	5	4	3	2	1	0
Name	SPIBSY	SPIMS	CPHA	CPOL	SLVSEL	NSSIN	SRMT	RXBMT
Type	R	R/W	R/W	R/W	R	R	R	R
Reset	0	0	0	0	1	0	1	1
Bit	Name	Description						
[7]	SPIBSY	This bit is set to “1” when data is being transferred via SPI.						
[6]	SPIMS	Master/Slave Mode Selection 0: Slave 1: Master						
[5]	CPHA	SPI Clock Phase 0: Collect data at the first edge of SCK 1: Collect data at the second edge of SCK						
[4]	CPOL	SPI Clock Idle Polarity 0: Low level in idle state. 1: High level in idle state.						
[3]	SLVSEL	This bit is set to “1” when the filtered signal of NSS pin is low, indicating that SPI device is selected as slave. When the filtered signal of NSS pin is high, this bit is cleared to “0”, indicating that SPI device is not selected as slave. This bit does not indicate instant value of the NSS pin, but the de-noising signal input by the pin.						
[2]	NSSIN	Real-time signal of NSS pin, unfiltered.						
[1]	SRMT	Shift Register Empty Flag (valid only in Slave Mode) This bit is set to “0” after data has been shifted out of the Transit Buffer into the shift register or SCLK changes, and is set to “0” when there is no data in the shift register or transmit and receive buffer. Note: SPI_CR0[SRMT] = 1 in Master Mode.						
[0]	RXBMT	Receive Buffer Empty Flag (valid only in Slave Mode) This bit is set to “0” when new data in the receive buffer has not been read, and is set to “1” when data has been read and there is no new data in the receive buffer. Note: SPI_CR0[RXBMT] = 1 in Master Mode.						

Note: Clock phase and idle polarity modes SPI_CR0[CPHA:CPOL]:

- 00: Receive data on rising edge, and send data on falling edge. Idle level is low.
- 01: Send data on rising edge, and receive data on falling edge. Idle level is high.
- 10: Send data on rising edge, and receive data on falling edge. Idle level is low.
- 11: Receive data on rising edge, and send data on falling edge. Idle level is high.

8.3.2 SPI_CR1 (0x4031)

Bit	7	6	5	4	3	2	1	0	
Name	SPIIF	WCOL	MODF	RXOVR	NSSMOD		TXBMT	SPIEN	
Type	R/W0	R/W0	R/W0	R/W0	R/W	R/W	R	R/W	
Reset	0	0	0	0	0	0	1	0	
Bit	Name	Description							
[7]	SPIIF	SPI Interrupt Flag This bit is set to “1” by hardware each time after a data frame (8-bit) is transferred. It can be cleared to “0” by software only.							
[6]	WCOL	Write Conflict Interrupt Flag When SPI_CR1[TXBMT] is “0”, a write to SPI_DR sets this bit to “1”. This bit can be cleared to “0” by software only.							
[5]	MODF	Master Mode Fault Interrupt Flag This bit is set to “1” when a master mode conflict is detected (SPI_CR0[NSSIN] = 0, SPI_CR1[SPIMS] = 1 and SPI_CR1[NSSMOD] = 01). This bit can be cleared to “0” by software only.							
[4]	RXOVR	Receive Overflow Interrupt Flag (Slave Mode only) This bit is set to “1” by hardware (and generates a SPI interrupt) when the Receive Buffer still holds unread data from a previous transfer and the last bit of the current transfer has been shifted into the SPI shift register. This bit cannot be clear to “0” automatically by hardware, and can be cleared to “0” by software only.							
[3:2]	NSSMOD	SPI Mode Selection 00: 3-Wire Slave or 3-wire Master Mode. NSS signal is not routed to a port pin. 01: 4-Wire Slave. NSS pin is configured as an input. 1X: 4-Wire Single-Master Mode. NSS pin is configured as output and outputs SPI CR1[2] value.							
[1]	TXBMT	Transmit Buffer Empty Flag This bit is cleared to “0” when new data is written to the Transit Buffer. It is set to “1” when the data in the Transit Buffer is transferred to the SPI shift register, indicating that it is safe to write a new byte to the transmit buffer. 0: A new data is written to the transmit buffer. 1: Data in the transmit buffer has been transferred to the shift register.							
[0]	SPIEN	SPI Enable 0: Disable 1: Enable							

8.3.3 SPI_CLK (0x4032)

Bit	7	6	5	4	3	2	1	0	
Name	SPI_CLK								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit	Name	Description							
[7:0]	SPI_CLK	SPI Baud Rate Setting This bit is valid in master mode only, and can be written only when SPI_CR1[SPIEN] = 0. Baud rate = SYSCLK/2/(SPI_CLK + 1) Example: If baud rate = 2400kHz, then SPI_CLK = (24M/2/2400k) - 1 = 4, i.e. 0x04. Note: When MDU PI/PID and slave SPI are active at the same time (using DMA transfer), the master SPI Baud Rate shall be less than 600kHz to prevent data transmitted from the slave SPI.							

8.3.4 SPI_DR (0x4033)

Bit	7	6	5	4	3	2	1	0
Name	SPI_DR							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	SPI_DR	SPI Data Register SPI_DR Register is used to transmit and receive SPI data. In master mode, when the date is written to SPI_DR, it's transferred to Transit Buffer for the transmission. When SPI_DR is read, the data held in Receive Buffer is obtained.						

9 UART

9.1 UART Introduction

UART is a full-duplex or half-duplex serial data exchange interface as shown in Figure 9-1. The baud rate is configurable and supports DMA transmission. Figure 9-2 depicts the UART timing.




Figure 9-1 UART Block Diagram




Figure 9-2 UART Timing Diagram

9.2 UART Operations

The corresponding registers shall be enabled before using UART feature. See 22.3.12 PH_SEL (0x404C) (bits [6] and [5]) for details.

9.2.1 UART Mode0

UART1 mode0, or shifting mode, is mainly used to expand the IO ports. In this mode, TXD pin is configured as clock output, and RXD data bus. The clock frequency is set at SYS_CLK/12, and the data is sent starting from the least significant bit. UT_CR[REN] decides the data is received or sent. When UT_CR[REN] = 0, the data is sent, and when UT_CR[REN] = 1, the data is received.

Sending Data: Write the data to UT_DR and resent UT_CR[TI]. TXD pin outputs shift pulse, and RXD pin sends the data held by UT_DR. The output clock frequency is SYS_CLK/12. UT_CR[TI] is set to “1” after the transmission is completed.

Receiving Data: Set UT_CR[REN] to “1” to receive the data and clear UT_CR[RI]. TXD pin outputs shift pulse, and RXD pin receives the data. The shift pulse frequency is SYS_CLK/12. After the data is received, UT_CR[RI] is set to “1” and UT_DR is read to obtain the data.

9.2.2 UART Mode1

UART1 mode1 works in full/half duplex mode. TXD pin is configured as an output (Transmit Data Bus), and RXD as an input (Receive Data Bus). It uses a total of 10 bits (1-bit start, 8-bit data, 1-bit stop) to receive or transmit data. The baud rate is configured by UT_BAUD[BAUD].

Sending Data: Write the data to UT_DR and clear UT_CR[TI]. TXD pin outputs 10-bit data. UT_CR[TI] is set to "1" after the transmission is completed.

Receiving Data: Set UT_CR[REN] to "1" to receive the data and clear UT_CR[RI]. The data is received via RXD pin. After the data is received, UT_CR[RB8] and UT_CR[RI] are set to "1" and UT_DR is read to obtain the data.

9.2.3 UART Mode2

UART1 mode2 works in full/half duplex mode. TXD pin is configured as an output (Transmit Data Bus), and RXD pin as an input (Receive Data Bus). It uses a total of 11 bits, namely 1-bit start, 9-bit data (UT_DR + UT_CR[RB8]/ UT_CR[TB8]) and 1-bit stop, to receive or transmit data. The baud rate is configured by UT_BAUD[UT_BAUD].

Sending Data: Write the data to UT_DR, set UT_CR[TB8] and reset UT_CR[TI]. TXD outputs 11-bit data. UT_CR[TI] is set to "1" after the transmission is completed.

Receiving Data: Set UT_CR[REN] to "1" to receive the data and clear UT_CR[RI]. The data is received via RXD pin. After the data is received, UT_CR[RI] is set to "1". UT_CR[RB8] stores the 9th bit of the data, and UT_DR stores the first 8 bits.

9.2.4 UART Mode3

The operations are the same as those for UART mode 2, and the baud rate is different from that for UART mode1.

9.2.5 UART Interrupt Sources

After UART interrupt is enabled (IE[ES0] = 1), an interrupt is generated when any of the two following flag bits are set to "1".

Note: These flag bits can be cleared to "0" by software only.

- After UART sends the data (8-bit data for UART mode0 and mode1 and 9-bit data for UART mode2 and mode3), UT_CR[TI] is set to "1" by hardware.
- After UART receives the data and STOP, UT_CR[RI] is set to "1" by hardware.

9.3 UART Registers

9.3.1 UT_CR (0x98)

Bit	7	6	5	4	3	2	1	0
Name	MOD		SM2	REN	TB8	RB8	TI	RI
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:6]	MOD	Mode Selection 00: UART Mode0——Shift Register Baud rate: SYS_CLK/12 01: UART Mode1——8-bit UART Baud rate: SYS_CLK / (16 / (1 + UT_BAUD[BAUD_SEL])) / (UT_BAUD + 1) 10: UART Mode2——9-bit UART Baud rate: SYS_CLK/(32 – 16*UT_BAUD[BAUD_SEL]) 11: UART Mode3——9-bit UART Baud rate: SYS_CLK/(16 / (1 + UT_BAUD[BAUD_SEL])) / (UT_BAUD + 1)						
[5]	SM2	0: Single-device Communication 1: Multi-device Communication						
[4]	REN	UART Receive Enable 0: Disable 1: Enable. This bit can be cleared to “0” by software only.						
[3]	TB8	Bit9 of the sent data in UART Mode2 and UART Mode3. This bit can be cleared by hardware as required.						
[2]	RB8	Bit9 of the received data in UART Mode2 and UART Mode3. If the bit SM2 is set as “0”, it serves as the STOP bit. It does not work in UART Mode0.						
[1]	TI	Data Sending Completed Interrupt Flag. This bit is set to “1” after the data is sent, and can be cleared to “0” by software only.						
[0]	RI	Data Receiving Completed Interrupt Flag. This bit is set to “1” after the data is received, and can be cleared to “0” by software only.						

9.3.2 UT_DR (0x99)

Bit	7	6	5	4	3	2	1	0
Name	UT_DR							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	UT_DR	Send/Receive Data						

9.3.3 UT_BAUD (0x9A,0x9B)

UT_BAUDH(0x9B)								
Bit	15	14	13	12	11	10	9	8
Name	BAUD_SEL	RSV			UT_BAUDH[11:8]			
Type	R/W	-	-	-	R/W	R/W	R/W	R/W
Reset	0	-	-	-	0	0	0	0
UT_BAUDL(0x9A)								
Bit	7	6	5	4	3	2	1	0
Name	UT_BAUDL[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	1	0	0	1	1	0	1	1

Bit	Name	Description
[15]	BAUD_SEL	Frequency Multiplier Enable
[14:12]	RSV	Reserved
[11:0]	UT_BAUD	Baud rate setting in UART Mode1 and UART Mode3

10 MDU

Multiply and Division Unit (MDU) is a built-in multiply and division co-processor for 16bit×16bit multiplication and 32bit/16bit division. It supports both unsigned and signed multiplication and unsigned division. MDU mode is determined by register MD_CR.

Multiply Mode: $MD_MC3 \sim 0 = \{MD_MAH \text{ and } MD_MAL\} * \{MD_MBH \text{ and } MD_MBL\}$

Note: Since $MD_MC3 \sim 2$ multiplexes MD_MAH and MD_MAL , and $MD_MC1 \sim 0$ multiplexes MD_MBH and MD_MBL , multiplicand and multiplier are written to MD_MAH and MD_MAL , and MD_MBH and MD_MBL respectively, and the result is accessed by reading the register.

Division Mode: $MD_DC3 \sim 0, MD_DD1 \sim 0 = MD_DA3 \sim 0 / MD_DB1 \sim 0$

The quotient is saved in $MD_DC3 \sim 0$ and the remainder is saved in $MD_DD1 \sim 0$.

Note: Since $MD_DC3 \sim 0$ multiplexes $MD_DA3 \sim 0$ and $MD_DD1 \sim 0$ multiplexes $MD_DB1 \sim 0$, dividend and divisor are written to $MD_DA3 \sim 0$ and $MD_DB1 \sim 0$ respectively, and the quotient and the remainder are accessed by reading the corresponding registers.

One multiplication process takes about one clock cycle, and the result can be shifted to the right according to MDU_CR[ALIGN]. One division process takes about 16 clock cycles. MDU_CR[DIVSTA] shall be configured to start the division. The software determines whether the division is completed by MDU_CR[DIVDONE].

10.1 Multiplication Configurations

1. Set MD_CR[MDSN] according to the multiplication type. It is set to 0 for unsigned multiplication, and 1 for signed multiplication. The right-shift bit of the result is set by MD_CR[ALIGN];
2. Write multiplicand to MD_MA, and multiplier to MD_MB;
3. Read MD_MA to obtain 16 high-order bits of the product, and MD_MB to obtain 16 low-order bits of the product
4. Start from step 2 if multiplication type and right-shift bit are the same.

10.2 Division Configurations

1. Write dividend to MD_DA, and divisor to MD_DB;
2. Write “1” to MDU_CR[DIVSTA] to start 32-bit/16-bit division;
3. The division is completed after about 16 clock cycles. MDU_CR[DIVDONE] = 1 means the division process has been completed, otherwise, you have to wait for the result;
4. Read MD_DA to obtain the quotient, and MD_DB to obtain the remainder.

10.3 Important Matters

- If “0” is written to MD_DB as the divisor, MDU produces MDU_CR[DIVERR] flag bit and keeps it stays at “1” until a non-zero divisor is written;

- The quotient and the remainder are uncertain or incorrect when the divider of MDU module is working (MDU_CR[DIVDONE] = 0). They are stable and correct only when division process is completed, that is the divider is idle.
- When the divider of MDU module is working (MDU_CR[DIVDONE] = 0), changing the value of divisor or division will not affect the final result, unless MD_CR[DIVSTA] is configured to “1” again to restart a new division process.
- Because data input register of the multiplier or divider in MDU module is only one level deep, interrupts can change the result. For example, an interrupt is generated after the multiplicand is written to MD_MA but before the multiplier is written to MD_MB. The interrupt requires the multiplier in the service routine. In this case, after the interrupt is implemented, MD_MA is changed and the multiplication result is wrong. Therefore, software developers shall take proper measures to avoid such situation.

10.4 MDU Registers

10.4.1 MDU_CR (0xC1)

Bit	7	6	5	4	3	2	1	0
Name	DIVDON E	DIVERR	RSV		ALIGN		MDSN	DIVSTA
Type	R	R	-	-	R/W	R/W	R/W	R/W
Reset	1	0	-	-	0	0	0	0

Bit	Name	Description
[7]	DIVDONE	0: The division is in progress. 1: The division is completed.
[6]	DIVERR	0: Last division is correct (a non-zero divisor is written). 1: Last division is wrong (“0” is written as the divisor).
[5:4]	RSV	Reserved
[3:2]	ALIGN	Right-shift Bit for the Result of Multiplication 00: Right shift is not supported. 01: The result is right shifted by 8 bits. 10: The result is right shifted by 12 bits. 11: The result is right shifted by 15 bits.
[1]	MDSN	Multiplication Type Selection 0: Unsigned Multiplication 1: Signed Multiplication
[0]	DIVSTA	Division Start Bit. This bit is valid only for division and is set to “1” by software during division. It is automatically cleared to “0” by hardware after the division is completed. 0: The divider does not start. 1: 32-bit division starts.

10.4.2 MD_MBL (0xCA)

Bit	7	6	5	4	3	2	1	0
Name	MD_MBL							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_MBL	Multiplier bit [7:0] (write only) or product bit [7:0] (read only)

10.4.3 MD_MBH (0xCB)

Bit	7	6	5	4	3	2	1	0
Name	MD_MBH							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_MBH	Multiplier bit [15: 8] (write only) or product bit [15: 8] (read only)

10.4.4 MD_MAL (0xC2)

Bit	7	6	5	4	3	2	1	0
Name	MD_MAL							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_MAL	Multiplicand bit [7:0] (write only) or product bit [23:16] (read only)

10.4.5 MD_MAH (0xC3)

Bit	7	6	5	4	3	2	1	0
Name	MD_MAH							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_MAH	Multiplicand bit [15:8] (write only) or product bit [31:24] (read only)

10.4.6 MD_DA0 (0xC4)

Bit	7	6	5	4	3	2	1	0
Name	MD_DA0							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_DA0	Dividend bit [7:0] (write only) or quotient bit [7:0] (read only)

10.4.7 MD_DA1 (0xC5)

Bit	7	6	5	4	3	2	1	0
Name	MD_DA1							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_DA1	Dividend bit [15:8] (write only) or quotient bit [15:8] (read only)

10.4.8 MD_DA2 (0xC6)

Bit	7	6	5	4	3	2	1	0
Name	MD_DA2							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_DA2	Dividend bit [23:16] (write only) or quotient bit [23:16] (read only)

10.4.9 MD_DA3 (0xC7)

Bit	7	6	5	4	3	2	1	0
Name	MD_DA3							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_DA3	Dividend bit [31:24] (write only) or quotient bit [31:24] (read only)

10.4.10 MD_DB0 (0xCC)

Bit	7	6	5	4	3	2	1	0
Name	MD_DB0							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	MD_DB0	Divisor bit [7:0] (write only) or remainder bit [7:0] (read only)

10.4.11 MD_DB1 (0xCD)

Bit	7	6	5	4	3	2	1	0
Name	MD_DB1							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	MD_DB1	Divisor bit [15:8] (write only) or remainder bit [15:8] (read only)						

11 PI

11.1 PI Introduction

PI regulator is a linear controller, where the output is generated by linear combination of error proportional, integral and differential actions, and then implemented by an actuator. In motor control system, it is used to for speed and position control.

PI algorithm:

$$U_k = U_{k-1} + K_p \times (E_k - E_{k-1}) + K_i \times E_k$$

Where,

U_k : Output for round k of calculation

U_{k-1} : Output for round k-1 of calculation

E_k : Deviation for round k of input

E_{k-1} and E_{k-2} : Deviations for round k-1 and round k-2 of calculation

K_p and K_i : Proportional (P) and integral (I) coefficients of regulator

The maximum U_k is represented as PIx_UKMAX (x=0 ~ 3) and the minimum value as PIx_UKMIN

($U_{k_min} < U(k) < U_{k_max}$)

11.2 PI Operations

1. Configuring PI_LPF_CR[PISTA] = 1 to enable PI. After four clock cycles, the calculation is completed and PI_UK is updated.
2. Q12 (default) or Q15 can be selected for PI parameters. It means data format of PI_KP and PI_KI is Q12 and that of other registers are Q15.
3. U_{k-1} and E_{k-1} default to the previous U_k and E_k . You can write the data to PI_EK register and start PI to change E_{k-1} , or write the data to PI_UK register to change U_{k-1} .

When PI regulator is invoked repeatedly, relevant parameters shall be saved after each PI operation, and initialized before the next PI operation. Initialization codes are shown as below:

```

PI_EK = X;                      //Initialize E(k-1)
SetBit(PI_LPF_CR , PISTA);      //Start PI
_nop_();
_nop_();
_nop_();
_nop_();                         //Wait for PI regulator to complete operations
PI_UK = X;                      //Initialize U(k-1)

```

11.3 PI Registers

11.3.1 PI_LPF_CR (0xF9)

Bit	7	6	5	4	3	2	1	0
Name	T2SS	RSV				PIRANGE	PISTA	LPFSTA
Type	R/W	-	-	-	-	R/W	R/W	R/W
Reset	0	-	-	-	-	0	0	0
<hr/>								
Bit	Name	Description						
[7]	T2SS	Input Mode Selection of TIM2 Step Motor 0: Direction + Pulse Input Mode. P1.0 for direction input, and P0.7 for pulse input 1: Bidirectional Pulse Input Mode. P1.0 for backward pulse input, and P0.7 for forward pulse input						
[6:3]	RSV	Reserved						
[2]	PIRANGE	Data Format of PI Parameters 0: Q12. The value range of KP and KI (-32768,32767) corresponds to range (-8,8). 1: Q15. The value range of KP and KI (-32768,32767) corresponds to range (-1,1).						
[1]	PISTA	PI Regulator Enable Bit. It is set to "1" by software, and can be automatically cleared to "0" by hardware. 0: Disable 1: Enable						
[0]	LPFSTA	LPF Enable Bit. It is set to "1" by software, and can be automatically cleared to "0" by hardware. 0: Disable 1: Enable						

11.3.2 PI_EK (0xEA, 0xEB)

PI_EKH(0xEB)								
Bit	15	14	13	12	11	10	9	8
Name	PI_EK[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI_EKL(0xEA)								
Bit	7	6	5	4	3	2	1	0
Name	PI_EK[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
<hr/>								
Bit	Name	Description						
[15:0]	PI_EK	Input Deviation; Range (-32768, 32767)						

11.3.3 PI_UK (0xEC, 0xED)

PI_UKH(0xED)								
Bit	15	14	13	12	11	10	9	8
Name	PI_UK[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI_UKL(0xEC)								
Bit	7	6	5	4	3	2	1	0
Name	PI_UK[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI_UK	Calculation result of PI regulator Range (-32768, 32767)

11.3.4 PI_KP (0xEE, 0xEF)

PI_KPH(0xEF)								
Bit	15	14	13	12	11	10	9	8
Name	PI_KP[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI_KPL(0xEE)								
Bit	7	6	5	4	3	2	1	0
Name	PI_KP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI_KP	KP Coefficient Range (-32768, 32767)						

11.3.5 PI_KI (0xF2, 0xF3)

PI_KIH(0xF3)								
Bit	15	14	13	12	11	10	9	8
Name	PI_KI[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI_KIL(0xF2)								
Bit	7	6	5	4	3	2	1	0
Name	PI_KI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI_KI	KI Coefficient Range (-32768, 32767)						

11.3.6 PI_UKMAX (0xF4, 0xF5)

PI_UKMAXH(0xF5)								
Bit	15	14	13	12	11	10	9	8
Name	PI_UKMAX[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI_UKMAXL(0xF4)								
Bit	7	6	5	4	3	2	1	0
Name	PI_UKMAX[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI_UKMAX	UK Maximum Value; Range (-32768,32767)						

11.3.7 PI_UKMIN (0xF6, 0xF7)

PI_UKMINH(0xF7)								
Bit	15	14	13	12	11	10	9	8
Name	PI_UKMIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI_UKMINL(0xF6)								
Bit	7	6	5	4	3	2	1	0
Name	PI_UKMIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI_UKMIN	UK Minimum Value Range (-32768,32767)						

12 LPF

A low-pass filter (LPF) is a filter circuit that passes low-frequency signals while attenuates high-frequency signals.

The calculation formula of LPF:

$$Y_k = Y_{k-1} + K \times (X_k - Y_{k-1})$$

Where,

Y_k : Filtered value

Y_{k-1} : Previous filtered output

K : Filter coefficient

X_k : Value to be filtered

12.1 LPF Operations

1. Configuring PI_LPF_CR[LPFSTA] = 1 to enable LPF. After four clock cycles, LPF_Y is updated.
2. Y_{k-1} default to the previous Y_k . You can write the data to LPF_Y register to change Y_{k-1} .

12.2 LPF Registers

12.2.1 PI_LPF_CR (0xF9)

Bit	7	6	5	4	3	2	1	0
Name	T2SS	RSV				PIRANGE	PISTA	LPFSTA
Type	R/W	-	-	-	-	R/W	R/W	R/W
Reset	0	-	-	-	-	0	0	0
Bit								
Bit		Description						
[7:1]		See PI_LPF_CR (0xF9) for details.						
[0]	LPFSTA	LPF Enable Bit. It is set to “1” by software, and can be automatically cleared to “0” by hardware. 0: Disable 1: Enable						

12.2.2 LPF_K (0xDD)

Bit	7	6	5	4	3	2	1	0
Name	LPF_K							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit								
Bit		Description						
[7:0]		LPF Coefficient The value range (-128,127) corresponds to range (-1,1).						

12.2.3 LPF_X (0xDE, 0xDF)

LPF_XH(0xDF)								
Bit	7	6	5	4	3	2	1	0
Name	LPF_X[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

LPF_XL(0xDE)								
Bit	7	6	5	4	3	2	1	0
Name	LPF_X[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	LPF_X	Input Value Range (-32768, 32767)						

12.2.4 LPF_Y (0xE6, 0xE7)

LPF_YH(0xE7)								
Bit	7	6	5	4	3	2	1	0
Name	LPF_Y[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF_YL(0xE6)								
Bit	7	6	5	4	3	2	1	0
Name	LPF_Y[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	LPF_Y	Output Value Range (-32768, 32767)						

13 SMDU

SMDU is a built-in computing co-processor that assists the CPU in processing complex operations efficiently. It supports multiplication, division, trigonometric operation, LPF operation and PI operation. SMDU module can be invoked in different interrupt services and master programs, and the results are independent from each other.

13.1 SMDU Features

The SMDU module has the following features:

- Support invocation with nested interrupt
- Hardware acceleration to reduce CPU load
- Support the following modes:
 - 16-bit signed multiplication
 - 16-bit signed multiplication (result shifted left by one-bit)
 - 16-bit unsigned multiplication
 - 32-bit/16-bit unsigned division
 - SMDU LPF
 - Coordinate transformation (SIN/COS)
 - Arctangent (ATAN)
 - PI

13.2 SMDU Instructions

13.2.1 SMDU Operations

SMDU is operated as follows.

1. Set TIM234_CTRL[MDU_EN_N] to “1” to enable SMDU module. After that, MDU, LPF and PI modules are disabled;
2. Select an operation mode by MDU_CR[MDUMOD];
3. Write the data to the associated computing units, select computing unit of the SMDU module by MDU_CR[MDUSTA], and start SMDU computing;
4. Wait for MDU_CR[MDUBUSY] to be cleared to “0” by hardware.

Note: When using SMDU, ensure that the computing mode and other data have been written before configuring MDU_CR[MDUSTA].

13.2.2 16-bit Signed Multiplication with the Result Shifted Left by One-bit

When MDU_CR[MDUMOD] = 000, SMDU module works in the 16-bit signed multiplication mode with the result shifted left by one-bit. As shown in Table 13-1, after 16-bit signed data is written to

MULx_MA and MULx_MB as multiplicand and multiplier respectively, 32-bit signed data is obtained by the product shifting left by one bit. The result is accessed by reading MULx_MC register.

Table 13-1 Register Definitions in 16-bit Signed Multiplication Mode with the Result Shifted Left by One-bit

Data Register	Input	Output
MULx_MA	Multiplicand	-
MULx_MB	Multiplier	-
MULx_MC	-	Product

13.2.3 16-bit Signed Multiplication

When MDU_CR[MDUMOD] = 001, SMDU module works in the 16-bit signed multiplication mode. As shown in Table 13-2, 32-bit signed data is obtained after 16-bit signed data is written to MULx_MA and MULx_MB as multiplicand and multiplier respectively. The result is accessed by reading MULx_MC register.

Table 13-2 Register Definitions in 16-bit Signed Multiplication Mode

Data Register	Input	Output
MULx_MA	Multiplicand	-
MULx_MB	Multiplier	-
MULx_MC	-	Product

13.2.4 16-bit Unsigned Multiplication

When MDU_CR[MDUMOD] = 010, SMDU module works in the 16-bit unsigned multiplication mode. As shown in Table 13-3, 32-bit unsigned data is obtained after 16-bit unsigned data is written to MULx_MA and MULx_MB as multiplicand and multiplier respectively. The result is accessed by reading MULx_MC register.

Table 13-3 Register Definitions in 16-bit Unsigned Multiplication Mode

Data Register	Input	Output
MULx_MA	Multiplicand	-
MULx_MB	Multiplier	-
MULx_MC	-	Product

13.2.5 32-bit/16-bit Unsigned Division

When MDU_CR[MDUMOD] = 011, SMDU module works in the 32-bit/16-bit unsigned division mode. As shown in Table 13-4, 32-bit unsigned quotient and 16-bit unsigned remainder is obtained after 32-bit unsigned dividend and a 16-bit unsigned divisor are written to DIVx_DA and DIVx_DB registers respectively. The quotient and remainder are accessed by reading DIVx_DQ and DIVx_DR registers respectively.

Table 13-4 Register Definitions in the Unsigned Division Mode

Data Register	Input	Output
DIVx_DA	Dividend	-
DIVx_DB	Divisor	-

Data Register	Input	Output
DIVx_DQ	-	Quotient
DIVx_DR	-	Remainder

13.2.6 SMDU LPF

When MDU_CR[MDUMOD] = 110, SMDU module works in LPF mode.

SMDU LPF has the same function as LPF. LPF writes or reads data in SFR sector, while SMDU LPF in XSFR sector.

As shown in Table 13-5, K is 16-bit signed data. Y_k is obtained after Y_{k-1} is written to LPFx_Y, K to LPFx_K and X_k to LPFx_X, and is accessed by reading LPFx_Y.

Table 13-5 Register Definitions in LPF Mode

Data Register	Input	Output
LPFx_X	X_k	-
LPFx_K	K	-
LPFx_Y	Y_{k-1}	Y_k

13.2.7 Coordinate Transformation (SIN/COS)

When MDU_CR[MDUMOD] = 100, SMDU module works in Coordinate Transformation mode. As shown in Figure 13-1, the coordinate transformation converts the components \cos_i and \sin_i of vector A under the x-y axis to the components \cos_o and \sin_o under the x'-y' axis, with the x'-y' axis lagging the x-y axis by θ .

The formula for coordinate transformation is:

$$\cos_o = \cos_i \times \cos \theta - \sin_i \times \sin \theta$$

$$\sin_o = \cos_i \times \sin \theta + \sin_i \times \cos \theta$$

In particular, when $\sin_i = 0$, the coordinate transformation is a sine and cosine calculation with \cos_i as the amplitude, calculated as:

$$\cos_o = \cos_i \times \cos \theta$$

$$\sin_o = \cos_i \times \sin \theta$$




Figure 13-1 Coordinate Transformation

As shown in Table 13-6, \cos_i , \sin_i , θ , \cos_o and \sin_o are all 16-bit signed data. \cos_i is written to SCATx_COS, \sin_i to SCATx_SIN and θ to SCATx_THE to calculate \cos_o and \sin_o . The results \cos_o and \sin_o are accessed by reading SCATx_RES1 and SCATx_RES2 respectively.

Table 13-6 Register Definitions in the Coordinate Transformation Mode

Data Register	Input	Output
SCATx_COS	\cos_i	-
SCATx_SIN	\sin_i	-
SCATx_THE	θ	-
SCATx_RES1	-	\cos_o
SCATx_RES2	-	\sin_o

13.2.8 Arctangent

When MDU_CR[MDUMOD] = 101, SMDU module works in arctangent (ATAN) mode.

ATAN calculates the amplitude and angle of a vector based on sine and cosine inputs. The calculation formula is:

$$U = \sqrt{(U \sin \theta)^2 + (U \cos \theta)^2}$$

$$\theta = \tan^{-1} \left(\frac{U \sin \theta}{U \cos \theta} \right)$$

Where,

$U \sin \theta$: Sin component of the vector

$U \cos \theta$: Cosine component of the vector

θ : Calculated vector angle

U : Calculated vector amplitude

As shown in Table 13-7, $U \cos \theta$ and $U \sin \theta$, U and θ are 16-bit signed data. $U \cos \theta$ is written to SCATx_COS and $U \sin \theta$ to SCATx_SIN to calculate U and θ . U and θ are accessed by reading SCATx_RES1 and SCATx_RES2 respectively.

Table 13-7 Register Definitions in ATAN Mode

Data Register	Input	Output
SCATx_COS	$U \cos \theta$	-
SCATx_SIN	$U \sin \theta$	-
SCATx_RES1	-	U
SCATx_RES2	-	θ

13.2.9 PI

13.2.9.1 PI Introduction

PI regulator is a linear controller, where the output is generated by linear combination of error proportional, integral and differential actions, and then implemented by an actuator. In motor control system, it is used to for speed and position control.

PI algorithm:

$$U_k = U_{k-1} + K_p \times (E_k - E_{k-1}) + K_i \times E_k$$

Where,

U_k : Output for round k of calculation

U_{k-1} : Output for round k-1 of calculation

E_k : Deviation for round k of input

E_{k-1} and E_{k-2} : Deviations for round k-1 and round k-2 of calculation

K_p and K_i : Proportional (P) and integral (I) coefficients of regulator

The maximum U_k is represented as PIx_UKMAX (x=0 ~ 3) and the minimum value as PIx_UKMIN.

13.2.9.2 PI Features

- Parameter range is configurable
- Support multiple invocations but not with nested interrupt
- Produce a 32-bit result PIx_UK
- Results are read after Busy Flag is reset to “0”.

13.2.9.3 PI Operations

1. Initialize SMDU before operations, and configure K_p , K_i and the maximum and minimum values of U_k ;
2. Set MDU_CR[MDUMOD] to 111, and then configure MDU_CR[MDUSTA] bit to select the desired computing unit and start PI computing. At this time, busy flag MDU_CR[MDUBUSY] is automatically set to “1”;
3. Read MDU_CR[MDUBUSY] bit by software. When this bit is 0, it indicates that the calculation is completed, and calculation result PIx_UK is updated.
4. Read PIx_UK to obtain the output.

Notes:

- The data format of PI_KP is Q12 and that of other registers are Q15.
- PIx_UK and PIx_EK1 values default to the previous calculated U_k and E_k . The related values change after PIx_EK1 and PIx_UK are written.

- When PI controller is invoked repeatedly, relevant parameters shall be saved after each PI operation, and initialized before the next PI operation. Initialization codes are shown as below:

```
PIx_KP = KP;           //Initialize Kp  
PIx_KI = KI;           //Initialize Ki  
PIx_UKMAX = UKMAX;    //Initialize maximum output  
PIx_UKMIN = UKMIN;    //Initialize minimum output  
PIx_EK1 = X;           //Initialize Ek-1  
PIx_UKH = Y1;           //Initialize 16 high-order bits of Uk-1  
PIx_UKL = Y2;           //Initialize 16 low-order bits of Uk-1
```

13.3 SMDU Registers

13.3.1 MDU_CR (0xC1)

MDU_CR(0xC1)								
Bit	7	6	5	4	3	2	1	0
Name	MDUB SY	MDUST A3	MDUST A2	MDUST A1	MDUST A0	MDUMO D2	MDUMO D1	MDUMO D0
Type	R	R/W						
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7]	MDUBSY	After SMDU module is enabled, this bit is used to indicate operating status of the module. 0: Idle 1: Busy
[6]	MDUSTA3	After SMDU module is enabled, this bit is used to enable or disable computing unit 3. 0: Disable 1: Enable
[5]	MDUSTA2	After SMDU module is enabled, this bit is used to enable or disable computing unit 2. 0: Disable 1: Enable
[4]	MDUSTA1	After SMDU module is enabled, this bit is used to enable or disable computing unit 1. 0: Disable 1: Enable
[3]	MDUSTA0	After SMDU module is enabled, this bit is used to enable or disable computing unit 0. 0: Disable 1: Enable
[2:0]	MDUMOD [2:0]	After SMDU module is enabled, this bit is used to select operating mode of the module. 000: Signed Multiplication (the result shifted left by one-bit) 001: Signed Multiplication 010: Unsigned Multiplication 011: 32-bit/16-bit Unsigned Division 100: Coordinate Transformation (SIN/COS) 101: ATAN 110: LPF 111: PI

Note: Configuring TIM234_CTRL[6] enables or disables SMDU module.

13.3.2 TIM234_CTRL(0x40f1)

TIM234_CTRL(0x40f1)								
Bit	7	6	5	4	3	2	1	0
Name	RSV	MDU_E N_N	TIM2_F AST_DI R	TIM2_D R_SEL	TIM4_R CTRL	TIM3_R CTRL	TIM2_R CTRL	TIM3_48 M
Type	-	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	0	0	0	0	0	0	0

Bit	Name	Description
[7]	RSV	Reserved

[6]	MDU_EN_N	When this bit is set to “1”, SMDU module is enabled and MDU module is disabled. 0: SMDU module is disabled. 1: SMDU module is enabled.
[5]	TIM2_FAST_DIR	After this bit is enabled in TIM2 QEP mode, SMDU module can quickly identify the direction. 0: Disable 1: Enable
[4]	TIM2_DR_SEL	After this bit is enabled in TIM2 QEP mode, the timer is reset to 0 or TIM2_DR when it reaches to TIM2_DR or 0. 0: Disable 1: Enable
[3]	TIM4_RCTRL	After this bit is enabled, DR = 0/0xffff when TIM4_CNTR overflows. 0: Disable 1: Enable
[2]	TIM3_RCTRL	After this bit is enabled, DR = 0/0xffff when TIM3_ARR overflows. 0: Disable 1: Enable
[1]	TIM2_RCTRL	After this bit is enabled, DR = 0/0xffff when TIM2_ARR overflows. 0: Disable 1: Enable
[0]	TIM3_48M	TIM3_48M Input Capture Enable 0: Disable 1: Enable

13.3.3 MUL0_MA (0x03C8, 0x03C9)

MUL0_MAH(0x03C8)							
Bit	15	14	13	12	11	10	9
Name	MUL0_MA[15:8]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
MUL0_MAL(0x03C9)							
Bit	7	6	5	4	3	2	1
Name	MUL0_MA[7:0]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
Bit	Name		Description				
[15:0]	MUL0_MA		Data register A of MUL0; Multiplicand of the multiplication				

13.3.4 MUL0_MB (0x03CA, 0x03CB)

MUL0_MBH(0x03CA)							
Bit	15	14	13	12	11	10	9
Name	MUL0_B[15:8]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
MUL0_MBL(0x03CB)							
Bit	7	6	5	4	3	2	1
Name	MUL0_B[7:0]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
Bit	Name		Description				
[15:0]	MUL0_MB		Data register B of MUL0; Multiplier of the multiplication				

13.3.5 MUL0_MC (0x03CC, 0x03CD, 0x03CE, 0x03CF)

MUL0_MCHH(0x03CC)								
Bit	31	30	29	28	27	26	25	24
Name	MUL0_MC[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL0_MCHL(0x03CD)								
Bit	23	22	21	20	19	18	17	16
Name	MUL0_MC[13:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL0_MCLH(0x03CE)								
Bit	15	14	13	12	11	10	9	8
Name	MUL0_MC[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL0_MCLL(0x03CF)								
Bit	7	6	5	4	3	2	1	0
Name	MUL0_MC[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[31:0]	MUL0_MC		Product of MUL0. The 16 high-order bits of the data are held by MUL0_MCH and the 16 low-order bits by MUL0_MCL.					

13.3.6 MUL1_MA (0x03C0, 0x03C1)

MUL1_MAH(0x03C0)								
Bit	15	14	13	12	11	10	9	8
Name	MUL1_MA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL1_MAL(0x03C1)								
Bit	7	6	5	4	3	2	1	0
Name	MUL1_MA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	MUL1_MA		Data register A of MUL1; Multiplicand of the multiplication					

13.3.7 MUL1_MB (0x03C2, 0x03C3)

MUL1_MBH(0x03C2)								
Bit	15	14	13	12	11	10	9	8
Name	MUL1_MB[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL1_MBL(0x03C3)								
Bit	7	6	5	4	3	2	1	0
Name	MUL1_MB[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	MUL1_MB		Data register B of MUL1; Multiplier of the multiplication					

13.3.8 MUL1_MC (0x03C4, 0x03C5, 0x03C6, 0x03C7)

MUL1_MCHH(0x03C4)								
Bit	31	30	29	28	27	26	25	24
Name	MUL1_MC[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL1_MCHL(0x03C5)								
Bit	23	22	21	20	19	18	17	16
Name	MUL1_MC[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL1_MCLH(0x03C6)								
Bit	15	14	13	12	11	10	9	8
Name	MUL1_MC[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL1_MCLL(0x03C7)								
Bit	7	6	5	4	3	2	1	0
Name	MUL1_MC[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[31:0]	MUL1_MC		Product of MUL1. The 16 high-order bits of the data are held by MUL1_MCH and the 16 low-order bits by MUL1_MCL.					

13.3.9 MUL2_MA (0x0370, 0x0371)

MUL2_MAH(0x0370)								
Bit	15	14	13	12	11	10	9	8
Name	MUL2_MA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL2_MAL(0x0371)								
Bit	7	6	5	4	3	2	1	0
Name	MUL2_MA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	MUL2_MA		Data register A of MUL2; Multiplicand of the multiplication					

13.3.10 MUL2_MB (0x0372, 0x0373)

MUL2_MBH(0x0372)								
Bit	15	14	13	12	11	10	9	8
Name	MUL2_MB[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL2_MBL(0x0373)								
Bit	7	6	5	4	3	2	1	0
Name	MUL2_MB[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	MUL2_MB		Data register B of MUL2; Multiplier of the multiplication					

13.3.11 MUL2_MC (0x0374, 0x0375, 0x0376, 0x0377)

MUL2_MCHH(0x0374)								
Bit	31	30	29	28	27	26	25	24
Name	MUL2_MC[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL2_MCHL(0x0375)								
Bit	23	22	21	20	19	18	17	16
Name	MUL2_MC[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL2_MCLH(0x0376)								
Bit	15	14	13	12	11	10	9	8
Name	MUL2_MC[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL2_MCLL(0x0377)								
Bit	7	6	5	4	3	2	1	0
Name	MUL2_MC[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[31:0]	MUL2_MC	Product of Register MUL2. The 16 high-order bits of the data are held by MUL2_MCH and the 16 low-order bits by MUL2_MCL.						

13.3.12 MUL3_MA (0x0368, 0x0369)

MUL3_MAH(0x0368)								
Bit	15	14	13	12	11	10	9	8
Name	MUL3_MA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL3_MAL(0x0369)								
Bit	7	6	5	4	3	2	1	0
Name	MUL3_MA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	MUL3_MA	Data register A of MUL3; Multiplicand of the multiplication						

13.3.13 MUL3_MB (0x036A, 0x036B)

MUL3_MBH(0x036A)								
Bit	15	14	13	12	11	10	9	8
Name	MUL3_MB[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL3_MBL(0x036B)								
Bit	7	6	5	4	3	2	1	0
Name	MUL3_MB[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	MUL3_MB	Data register B of MUL3; Multiplier of the multiplication						

13.3.14 MUL3_MC (0x036C, 0x036D, 0x036E, 0x036F)

MUL3_MCHH(0x036C)								
Bit	31	30	29	28	27	26	25	24
Name	MUL3_MC[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL3_MCHL(0x036D)								
Bit	23	22	21	20	19	18	17	16
Name	MUL3_MC[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL3_MCLH(0x036E)								
Bit	15	14	13	12	11	10	9	8
Name	MUL3_MC[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
MUL3_MCLL(0x036F)								
Bit	7	6	5	4	3	2	1	0
Name	MUL3_MC[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[31:0]	MUL3_MC		Product of MUL3. The 16 high-order bits of the data are held by MUL3_MCH and the 16 low-order bits by MUL3_MCL.					

13.3.15 DIV0_DA (0x03B4, 0x03B5, 0x03B6, 0x03B7)

DIV0_DAHH(0x03B4)								
Bit	31	30	29	28	27	26	25	24
Name	DIV0_DA[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DAHL(0x03B5)								
Bit	23	22	21	20	19	18	17	16
Name	DIV0_DA[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DALH(0x03B6)								
Bit	15	14	13	12	11	10	9	8
Name	DIV0_DA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DALL(0x03B7)								
Bit	7	6	5	4	3	2	1	0
Name	DIV0_DA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[31:0]	DIV0_DA		Dividend of DIV0. The 16 high-order bits of the data are held by DIV0_DAH and the 16 low-order bits by DIV0 DAL.					

13.3.16 DIV0_DB (0x03B8, 0x03B9)

DIV0_DBH(0x03B8)								
Bit	15	14	13	12	11	10	9	8
Name	DIV0_DB[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DBL(0x03B9)								
Bit	7	6	5	4	3	2	1	0
Name	DIV0_DB[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DIV0_DB	Data register B of DIV0; Divisor of the division						

13.3.17 DIV0_DQ (0x03BA, 0x03BB, 0x03BC, 0x03BD)

DIV0_DQHH(0x03BA)								
Bit	31	30	29	28	27	26	25	24
Name	DIV0_DQ[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DQHL(0x03BB)								
Bit	23	22	21	20	19	18	17	16
Name	DIV0_DQ[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DQLH(0x03BC)								
Bit	15	14	13	12	11	10	9	8
Name	DIV0_DQ[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DQLL(0x03BD)								
Bit	7	6	5	4	3	2	1	0
Name	DIV0_DQ[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[31:0]	DIV0_DQ[31:0]	Quotient of DIV0. The 16 high-order bits of the data are held by DIV0_DQH and the 16 low-order bits by DIV0_DQL.						

13.3.18 DIV0_DR (0x03BE, 0x03BF)

DIV0_DRH(0x03BE)								
Bit	15	14	13	12	11	10	9	8
Name	DIV0_DR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV0_DRL(0x03BF)								
Name	DIV0_DR[7:0]							
Bit	7	6	5	4	3	2	1	0
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DIV0_DR	Remainder of DIV0						

13.3.19 DIV1_DA (0x03A8, 0x03A9, 0x03AA, 0x03AB)

DIV1 DAHH(0x03A8)								
Bit	31	30	29	28	27	26	25	24
Name	DIV1_DA[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV1 DAHL(0x03A9)								
Bit	23	22	21	20	19	18	17	16
Name	DIV1_DA[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV1 DALH(0x03AA)								
Bit	15	14	13	12	11	10	9	8
Name	DIV1_DA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV1 DALL(0x03AB)								
Bit	7	6	5	4	3	2	1	0
Name	DIV1_DA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[31:0]	DIV1_DA	Dividend of DIV1. The 16 high-order bits of the data are held by DIV1_DA and the 16 low-order bits by DIV1_DA.						

13.3.20 DIV1_DB (0x03AC, 0x03AD)

DIV1_DBH(0x03AC)								
Bit	15	14	13	12	11	10	9	8
Name	DIV1_DB[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV1_DBL(0x03AD)								
Bit	7	6	5	4	3	2	1	0
Name	DIV1_DB[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DIV1_DB	Data register B of DIV1; Divisor of the division						

13.3.21 DIV1_DQ (0x03AE, 0x03AF, 0x03B0, 0x03B1)

DIV1_DQHH(0x03AE)								
Bit	31	30	29	28	27	26	25	24
Name	DIV1_DQ[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV1_DQHL(0x03AF)								
Bit	23	22	21	20	19	18	17	16
Name	DIV1_DQ[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

DIV1_DQLH(0x03B0)								
Bit	15	14	13	12	11	10	9	8
Name	DIV1_DQ[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV1_DQLL(0x03B1)								
Bit	7	6	5	4	3	2	1	0
Name	DIV1_DQ[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[31:0]	DIV1_DQ	Quotient of DIV1. The 16 high-order bits of the data are held by DIV1_DQH and the 16 low-order bits by DIV1_DQL.						

13.3.22 DIV1_DR (0x03B2, 0x03B3)

DIV1_DRH(0x03B2)								
Bit	15	14	13	12	11	10	9	8
Name	DIV1_DR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV1_DRL(0x03B3)								
Bit	7	6	5	4	3	2	1	0
Name	DIV1_DR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DIV1_DR	Remainder of DIV1						

13.3.23 DIV2_DA (0x035C, 0x035D, 0x035E, 0x035F)

DIV2_DAHH(0x035C)								
Bit	31	30	29	28	27	26	25	24
Name	DIV2_DA[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2_DAHL(0x035D)								
Bit	23	22	21	20	19	18	17	16
Name	DIV2_DA[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2 DALH(0x035E)								
Bit	15	14	13	12	11	10	9	8
Name	DIV2_DA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2_DALL(0x035F)								
Bit	7	6	5	4	3	2	1	0
Name	DIV2_DA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[31:0]	DIV2_DA	Dividend of DIV2. The 16 high-order bits of the data are held by DIV2_DA and the 16 low-order bits by DIV2_DA.						

13.3.24 DIV2_DB (0x0360, 0x0361)

DIV2_DBH(0x0360)								
Bit	15	14	13	12	11	10	9	8
Name	DIV2_DB[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2_DBL(0x0361)								
Bit	7	6	5	4	3	2	1	0
Name	DIV2_DB[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DIV2_DB	Data register B of DIV2; Divisor of the division						

13.3.25 DIV2_DQ (0x0362, 0x0363, 0x0364, 0x0365)

DIV2_DQHH(0x0362)								
Bit	31	30	29	28	27	26	25	24
Name	DIV2_DQ[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2_DQHL(0x0363)								
Bit	23	22	21	20	19	18	17	16
Name	DIV2_DQ[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2_DQLH(0x0364)								
Bit	15	14	13	12	11	10	9	8
Name	DIV2_DQ[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2_DQLL(0x0365)								
Bit	7	6	5	4	3	2	1	0
Name	DIV2_DQ[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[31:0]	DIV2_DQ	Quotient of DIV2. The 16 high-order bits of the data are held by DIV2_DQH and the 16 low-order bits by DIV2_DQL.						

13.3.26 DIV2_DR (0x0366, 0x0367)

DIV2_DRH(0x0366)								
Bit	15	14	13	12	11	10	9	8
Name	DIV2_DR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV2_DRL(0x0367)								
Bit	7	6	5	4	3	2	1	0
Name	DIV2_DR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DIV2_DR	Remainder of DIV2						

13.3.27 DIV3_DA (0x0350, 0x0351, 0x0352, 0x0353)

DIV3_DAHH(0x0350)								
Bit	31	30	29	28	27	26	25	24
Name	DIV3_DA[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV3_DAHL(0x0351)								
Bit	23	22	21	20	19	18	17	16
Name	DIV3_DA[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV3_DALH(0x0352)								
Bit	15	14	13	12	11	10	9	8
Name	DIV3_DA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV3_DALL(0x0353)								
Bit	7	6	5	4	3	2	1	0
Name	DIV3_DA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[31:0]	DIV3_DA	Dividend of DIV3. The 16 high-order bits of the data are held by DIV3_DAH and the 16 low-order bits by DIV3 DAL.						

13.3.28 DIV3_DB (0x0354, 0x0355)

DIV3_DBH(0x0354)								
Bit	15	14	13	12	11	10	9	8
Name	DIV3_DB[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV3_DBL(0x0355)								
Bit	7	6	5	4	3	2	1	0
Name	DIV3_DB[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DIV3_DB	Data register B of DIV3; Divisor of the division						

13.3.29 DIV3_DQ (0x0356, 0x0357, 0x0358, 0x0359)

DIV3_DQHH(0x0356)								
Bit	31	30	29	28	27	26	25	24
Name	DIV3_DQ[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DIV3_DQHL(0x0357)								
Bit	23	22	21	20	19	18	17	16
Name	DIV3_DQ[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

DIV3_DQLH(0x0358)									
Bit	15	14	13	12	11	10	9	8	
Name	DIV3_DQ[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
DIV3_DQLL(0x0359)									
Bit	7	6	5	4	3	2	1	0	
Name	DIV3_DRQ[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit Name Description									
[31:0]	DIV3_DQ	Quotient of DIV3. The 16 high-order bits of the data are held by DIV3_DQH and the 16 low-order bits by DIV3_DQL.							

13.3.30 DIV3_DR (0x035A, 0x035B)

DIV3_DRH(0x035A)									
Bit	15	14	13	12	11	10	9	8	
Name	DIV3_DR[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
DIV3_DRL(0x035B)									
Bit	7	6	5	4	3	2	1	0	
Name	DIV3_DR[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit Name Description									
[15:0]	DIV3_DR	Remainder of DIV3							

13.3.31 SCAT0_COS (0x0346, 0x0347)

SCAT0_COSH(0x0346)									
Bit	15	14	13	12	11	10	9	8	
Name	SCAT0_COS[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
SCAT0_COSL(0x0347)									
Bit	7	6	5	4	3	2	1	0	
Name	SCAT0_COS[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit Name Description									
[15:0]	SCAT0_COS	COS input in SIN/COS or ATAN mode of computing unit SCAT0							

13.3.32 SCAT0_SIN (0x0348, 0x0349)

SCAT0 SINH(0x0348)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT0 SIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT0 SINL(0x0349)								
Bit	7	6	5	4	3	2	1	0

Name	SCAT0_SIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit								
[15:0]	SCAT0_SIN	Description						

13.3.33 SCAT0_THE (0x034A, 0x034B)

SCAT0 THEH(0x034A)								
Bit	15	14	13	12	11	10	9	8
Name								
SCAT0_THE[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT0 THEL(0x034B)								
Bit	7	6	5	4	3	2	1	0
Name								
SCAT0_THE[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit								
[15:0]	SCAT0_THE	Description						

13.3.34 SCAT0_RES1 (0x034C, 0x034D)

SCAT0 RES1H(0x034C)								
Bit	15	14	13	12	11	10	9	8
Name								
SCAT0_RES1[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT0 RES1L(0x034D)								
Bit	7	6	5	4	3	2	1	0
Name								
SCAT0_RES1[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit								
[15:0]	SCAT0_RES1	Description						

13.3.35 SCAT0_RES2 (0x034E, 0x034F)

SCAT0 RES2H(0x034E)								
Bit	15	14	13	12	11	10	9	8
Name								
SCAT0_RES2[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT0 RES2L(0x034F)								
Bit	7	6	5	4	3	2	1	0
Name								
SCAT0_RES2[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit								
[15:0]	SCAT0_RES2	Description						

13.3.36 SCAT1_COS (0x033C, 0x033D)

SCAT1_COSH(0x033C)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT1_COS[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1_COSL(0x033D)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT1_COS[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	SCAT1_COS		COS input in SIN/COS or ATAN mode of computing unit SCAT1					

13.3.37 SCAT1_SIN (0x033E, 0x033F)

SCAT1_SINH(0x033E)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT1_SIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1_SINL(0x033F)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT1_SIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	SCAT1_SIN		SIN input in SIN/COS or ATAN mode of computing unit SCAT1					

13.3.38 SCAT1_THE (0x0340, 0x0341)

SCAT1_THEH(0x0340)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT1_THE[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1_THEL(0x0341)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT1_THE[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	SCAT1_THE		THE input in SIN/COS mode of computing unit SCAT1					

13.3.39 SCAT1_RES1 (0x0342, 0x0343)

SCAT1_RES1H(0x0342)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT1_RES1[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

SCAT1 RES1L(0x0343)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT1_RES1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1 RES2H(0x0344)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT1_RES2[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1 RES2L(0x0345)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT1_RES2[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1 RES2[7:0]								
Bit	7	6	5	4	3	2	1	0
[15:0]	SCAT1_RES2	SIN output in SIN/COS mode of computing unit SCAT1; θ output of ATAN mode						

13.3.40 SCAT1_RES2 (0x0344, 0x0345)

SCAT1 RES2H(0x0344)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT1_RES2[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1 RES2L(0x0345)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT1_RES2[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT1 RES2[7:0]								
Bit	7	6	5	4	3	2	1	0
[15:0]	SCAT1_RES2	SIN output in SIN/COS mode of computing unit SCAT1; θ output of ATAN mode						

13.3.41 SCAT2_COS (0x0332, 0x0333)

SCAT2 COSH(0x0332)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT2_COS[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT2 COSL(0x0333)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT2_COS[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT2_COS[7:0]								
Bit	7	6	5	4	3	2	1	0
[15:0]	SCAT2_COS	COS input in SIN/COS or ATAN mode of computing unit SCAT2						

13.3.42 SCAT2_SIN (0x0334, 0x0335)

SCAT2 SINH(0x0334)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT2_SIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT2 SINL(0x0335)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT2_SIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT2_SIN[7:0]								
Bit	7	6	5	4	3	2	1	0
[15:0]	SCAT2_SIN	SIN input in SIN/COS or ATAN mode of computing unit SCAT2						

13.3.43 SCAT2_THE (0x0336, 0x0337)

SCAT2 THEH(0x0336)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT2_THE[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT2 THEL(0x0337)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT2_THE[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	SCAT2_THE		THE input in SIN/COS mode of computing unit SCAT2					

13.3.44 SCAT2_RES1 (0x0338, 0x0339)

SCAT2 RES1H(0x0338)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT2_RES1[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT2 RES1L(0x0339)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT2_RES1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	SCAT2_RES1		COS output in SIN/COS mode of computing unit SCAT2; U output in ATAN mode					

13.3.45 SCAT2_RES2 (0x033A, 0x033B)

SCAT2 RES2H(0x033A)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT2_RES[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT2 RES2L(0x033B)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT2_RES[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	SCAT2_RES2		SIN output in SIN/COS mode of computing unit SCAT2; θ output in ATAN mode					

13.3.46 SCAT3_COS (0x0328, 0x0329)

SCAT3 COSH(0x0328)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT3_COS[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	7	6	5	4	3	2	1	0
Name	SCAT3_COSL(0x0329)							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	SCAT3_COS	COS input in SIN/COS or ATAN mode of computing unit SCAT3

13.3.47 SCAT3_SIN (0x032A, 0x032B)

SCAT3 SINH(0x032A)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT3_SIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT3 SINL(0x032B)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT3_SIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	SCAT3_SIN	SIN input in SIN/COS or ATAN mode of computing unit SCAT3						

13.3.48 SCAT3_THE (0x032C, 0x032D)

SCAT3 THEH(0x032C)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT3_THE[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT3 THEL(0x032D)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT3_THE[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	SCAT3_THE	THE input in SIN/COS mode of computing unit SCAT3						

13.3.49 SCAT3_RES1 (0x032E, 0x032F)

SCAT3 RES1H(0x032E)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT3_RES1[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT3 RES1L(0x032F)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT3_RES1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	SCAT3_RES1	COS output in SIN/COS mode of computing unit SCAT3; U output in ATAN mode						

13.3.50 SCAT3_RES2 (0x0330, 0x0331)

SCAT3 RES2H(0x0330)								
Bit	15	14	13	12	11	10	9	8
Name	SCAT3_RES[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
SCAT3 RES2L(0x0331)								
Bit	7	6	5	4	3	2	1	0
Name	SCAT3_RES[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	SCAT3_RES2		SIN output in SIN/COS mode of computing unit SCAT3; θ output in ATAN mode					

13.3.51 LPF0_K (0x03F8, 0x03F9)

LPF0 KH(0x03F8)								
Bit	15	14	13	12	11	10	9	8
Name	LPF0_K[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF0 KL(0x03F9)								
Bit	7	6	5	4	3	2	1	0
Name	LPF0_K[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	LPF0_K[15:0]		K input of LPF0					

13.3.52 LPF0_X (0x03FA 0x03FB)

LPF0_XH(0x03FA)								
Bit	15	14	13	12	11	10	9	8
Name	LPF0_X[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF0_XL(0x03FB)								
Bit	7	6	5	4	3	2	1	0
Name	LPF0_X[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	LPF0_X[15:0]		X input of LPF0					

13.3.53 LPF0_Y (0x03FC, 0x03FD, 0x03FE, 0x03FF)

LPF0_YHH(0x03FC)								
Bit	31	30	29	28	27	26	25	24
Name	LPF0_Y[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF0_YHL(0x03FD)								
Bit	23	22	21	20	19	18	17	16
Name	LPF0_Y[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

LPF0_YLH(0x03FE)								
Bit	15	14	13	12	11	10	9	8
Name	LPF0_Y[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF0_YLL(0x03FF)								
Bit	7	6	5	4	3	2	1	0
Name	LPF0_Y[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Description								
[31:0]	LPF0_Y[31:0]	Input and output of the register in LPF0 Input: LPF0_Y _{k-1} Output: LPF0_Y _k						

13.3.54 LPF1_K (0x03F0, 0x03F1)

LPF1_KH(0x03F0)								
Bit	15	14	13	12	11	10	9	8
Name	LPF1_K[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF1_KL(0x03F1)								
Bit	7	6	5	4	3	2	1	0
Name	LPF1_K[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	LPF1_K[15:0]	K input of LPF1						

13.3.55 LPF1_X (0x03F2, 0x03F3)

LPF1_XH(0x03F2)								
Bit	15	14	13	12	11	10	9	8
Name	LPF1_X[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF1_XL(0x03F3)								
Bit	7	6	5	4	3	2	1	0
Name	LPF1_X[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	LPF1_X[15:0]	X input of LPF1						

13.3.56 LPF1_Y (0x03F4, 0x03F5, 0x03F6, 0x03F7)

LPF1_YHH(0x03F4)								
Bit	31	30	29	28	27	26	25	24
Name	LPF1_Y[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

LPF1_YHL(0x03F5)							
Bit	23	22	21	20	19	18	17
Name	LPF1_Y[23:16]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
LPF1_YLH(0x03F6)							
Bit	15	14	13	12	11	10	9
Name	LPF1_Y[15:8]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
LPF1_YLL(0x03F7)							
Bit	7	6	5	4	3	2	1
Name	LPF1_Y[7:0]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
Bit	Name		Description				
[31:0]	LPF1_Y[31:0]		Input and output of the register in LPF1 Input: LPF1_Y _{k-1} Output: LPF1_Y _k				

13.3.57 LPF2_K (0x03A0, 0x03A1)

LPF2_KH(0x03A0)							
Bit	15	14	13	12	11	10	9
Name	LPF2_K[15:8]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
LPF2_KL(0x03A1)							
Bit	7	6	5	4	3	2	1
Name	LPF2_K[7:0]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
Bit	Name		Description				
[15:0]	LPF2_K[15:0]		K input of LPF2				

13.3.58 LPF2_X (0x03A2, 0x03A3)

LPF2_XH(0x03A2)							
Bit	15	14	13	12	11	10	9
Name	LPF2_X[15:8]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
LPF2_XL(0x03A3)							
Bit	7	6	5	4	3	2	1
Name	LPF2_X[7:0]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
Bit	Name		Description				
[15:0]	LPF2_X[15:0]		X input of LPF2				

13.3.59 LPF2_Y (0x03A4, 0x03A5, 0x03A6, 0x03A7)

LPF2_YHH(0x03A4)								
Bit	31	30	29	28	27	26	25	24
Name	LPF2_Y[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF2_YHL(0x03A5)								
Bit	23	22	21	20	19	18	17	16
Name	LPF2_Y[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF2_YLH(0x03A6)								
Bit	15	14	13	12	11	10	9	8
Name	LPF2_Y[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF2_YLL(0x03A7)								
Bit	7	6	5	4	3	2	1	0
Name	LPF2_Y[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[31:0]	LPF2_Y[31:0]		Input and output of the register in LPF2 Input: LPF2_Y _{k-1} Output: LPF2_Y _k					

13.3.60 LPF3_K (0x0398, 0x0399)

LPF3_KH(0x0398)								
Bit	15	14	13	12	11	10	9	8
Name	LPF3_K[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF3_KL(0x0399)								
Bit	7	6	5	4	3	2	1	0
Name	LPF3_K[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	LPF3_K[15:0]		K input of LPF3					

13.3.61 LPF3_X (0x039A, 0x039B)

LPF3_XH(0x039A)								
Bit	15	14	13	12	11	10	9	8
Name	LPF3_X[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF3_XL(0x039B)								
Bit	7	6	5	4	3	2	1	0
Name	LPF3_X[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	LPF3_X[15:0]		X input of LPF3					

13.3.62 LPF3_Y (0x039C, 0x039D, 0x039E, 0x039F)

LPF3_YHH(0x039C)								
Bit	31	30	29	28	27	26	25	24
Name	LPF3_Y[31:24]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF3_YHL(0x039D)								
Bit	23	22	21	20	19	18	17	16
Name	LPF3_Y[23:16]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF3_YLH(0x039E)								
Bit	15	14	13	12	11	10	9	8
Name	LPF3_Y[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
LPF3_YLL(0x039F)								
Bit	7	6	5	4	3	2	1	0
Name	LPF3_Y[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[31:0]	LPF3_Y[31:0]		Input and output of the register in LPF3 Input: LPF3_Y _{k-1} Output: LPF3_Y _k					

13.3.63 PIO_KP (0x03E0, 0x03E1)

PIO_KPH(0x03E0)								
Bit	15	14	13	12	11	10	9	8
Name	PIO_KP[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PIO_KPL(0x03E1)								
Bit	7	6	5	4	3	2	1	0
Name	PIO_KP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	PIO_KP		Proportional coefficient of PIO					

13.3.64 PIO_EK1 (0x03E2, 0x03E3)

PIO_EK1H(0x03E2)								
Bit	15	14	13	12	11	10	9	8
Name	PIO_EK1[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PIO_EK1L(0x03E3)								
Bit	7	6	5	4	3	2	1	0
Name	PIO_EK1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	PIO_EK1		Previous input deviation of PIO					

13.3.65 PIO_EK (0x03E4, 0x03E5)

PIO_EKH(0x03E4)								
Bit	15	14	13	12	11	10	9	8
Name	PIO_EK[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PIO_EKL(0x03E5)								
Bit	7	6	5	4	3	2	1	0
Name	PIO_EK[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PIO_EK	Present input deviation of PIO						

13.3.66 PIO_KI (0x03E6, 0x03E7)

PIO_KIH(0x03E6)								
Bit	15	14	13	12	11	10	9	8
Name	PIO_KI[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PIO_KIL(0x03E7)								
Bit	7	6	5	4	3	2	1	0
Name	PIO_KI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PIO_KI	Integral coefficient of PIO						

13.3.67 PIO_UKH (0x03E8, 0x03E9)

PIO_UKHH(0x03E8)								
Bit	15	14	13	12	11	10	9	8
Name	PIO_UKH[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PIO_UKHL(0x03E9)								
Bit	7	6	5	4	3	2	1	0
Name	PIO_UKH[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PIO_UKH	16 high-order bits of PIO output						

13.3.68 PIO_UKL (0x03EA, 0x03EB)

PIO_UKLH(0x03EA)								
Bit	15	14	13	12	11	10	9	8
Name	PIO_UKL[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI0_UKLL(0x03EB)								
Bit	7	6	5	4	3	2	1	0
Name	PI0_UKL[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI0_UKL	16 low-order bits of PI0 output

13.3.69 PI0_UKMAX (0x03EC, 0x03ED)

PI0_UKMAXH(0x03EC)								
Bit	15	14	13	12	11	10	9	8
Name	PI0_UKMAX[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI0_UKMAXL(0x03ED)								
Bit	7	6	5	4	3	2	1	0
Name	PI0_UKMAX[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI0_UKMAX	Maximum output of PI0

13.3.70 PI0_UKMIN (0x03EE, 0x03EF)

PI0_UKMINH(0x03EE)								
Bit	15	14	13	12	11	10	9	8
Name	PI0_UKMIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI0_UKMINL(0x03EF)								
Bit	7	6	5	4	3	2	1	0
Name	PI0_UKMIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI0_UKMIN	Minimum output of PI0

13.3.71 PI1_KP (0x03D0, 0x03D1)

PI1_KPH(0x03D0)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_KP[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI1_KPL(0x03D1)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_KP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI1_KP	Proportional coefficient of PI1

13.3.72 PI1_EK1 (0x03D2, 0x03D3)

PI1_EK1H(0x03D2)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_EK1[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI1_EKL(0x03D3)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_EK1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	PI1_EK1	Previous input deviation of PI1						

13.3.73 PI1_EK (0x03D4, 0x03D5)

PI1_EKH(0x03D4)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_EK[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI1_EKL(0x03D5)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_EK[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	PI1_EK	Present input deviation of PI1						

13.3.74 PI1_KI(0x03D6, 0x03D7)

PI1_KIH(0x03D6)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_KI[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI1_KIL(0x03D7)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_KI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	PI1_KI	Integral coefficient of PI1						

13.3.75 PI1_UKH (0x03D8, 0x03D9)

PI1_UKHH(0x03D8)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_UKH[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI1_UKHL(0x03D9)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_UKH[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI1_UKH	16 high-order bits of PI1 output

13.3.76 PI1_UKL (0x03DA, 0x03DB)

PI1_UKLLH(0x03DA)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_UKL[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI1_UKLL(0x03DB)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_UKL[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI1_UKL	16 low-order bits of PI1 output

13.3.77 PI1_UKMAX (0x03DC, 0x03DD)

PI1_UKMAXH(0x03DC)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_UKMAX[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI1_UKMAXL(0x03DD)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_UKMAX[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI1_UKMAX	Maximum output of PI1

13.3.78 PI1_UKMIN (0x03DE, 0x03DF)

PI1_UKMINH(0x03DE)								
Bit	15	14	13	12	11	10	9	8
Name	PI1_UKMIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI1_UKMINL(0x03DF)								
Bit	7	6	5	4	3	2	1	0
Name	PI1_UKMIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI1_UKMIN	Minimum output of PI1

13.3.79 PI2_KP (0x0388, 0x0389)

PI2_KPH(0x0388)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_KP[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI2_KPL(0x0389)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_KP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI2_KP	Proportional coefficient of PI2						

13.3.80 PI2_EK1 (0x038A, 0x038B)

PI2_EK1H(0x038A)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_EK1[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI2_EK1L(0x038B)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_EK1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI2_EK1	Previous input deviation of PI2						

13.3.81 PI2_EK (0x038C, 0x038D)

PI2_EKH(0x038C)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_EK[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI2_EKL(0x038D)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_EK[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI2_EK	Present input deviation of PI2						

13.3.82 PI2_KI (0x038E, 0x038F)

PI2_KIH(0x038E)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_KI[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI2_KIL(0x038F)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_KI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI2_KI	Integral coefficient of PI2

13.3.83 PI2_UKH (0x0390, 0x0391)

PI2_UKHH(0x0390)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_UKH[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI2_UKHL(0x0391)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_UKH[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI2_UKH	16 high-order bits of PI2 output

13.3.84 PI2_UKL (0x0392, 0x0393)

PI2_UKLLH(0x0392)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_UKL[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI2_UKLL(0x0393)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_UKL[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI2_UKL	16 low-order bits of PI2 output

13.3.85 PI2_MAX (0x0394, 0x0395)

PI2_MAXH(0x0394)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_MAX[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI2_MAXL(0x0395)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_MAX[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	PI2_MAX	Maximum output of PI2

13.3.86 PI2_MIN (0x0396, 0x0397)

PI2_MINH(0x0396)								
Bit	15	14	13	12	11	10	9	8
Name	PI2_MIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI2_MINL(0x0397)								
Bit	7	6	5	4	3	2	1	0
Name	PI2_MIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI2_MIN	Minimum output of PI2						

13.3.87 PI3_KP (0x0378, 0x0379)

PI3_KPH(0x0378)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_KP[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI3_KPL(0x0379)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_KP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_KP	Proportional coefficient of PI3						

13.3.88 PI3_EK1 (0x037A, 0x037B)

PI3_EK1H(0x037A)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_EK1[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI3_EK1L(0x037B)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_EK1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_EK1	Previous input deviation of PI3						

13.3.89 PI3_EK (0x037C, 0x037D)

PI3_EKH(0x037C)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_EK[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

PI3_EKL(0x037D)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_EK[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_EK	Present input deviation of PI3						

13.3.90 PI3_KI (0x037E, 0x037F)

PI3_KIH(0x037E)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_KI[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI3_KIL(0x037F)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_KI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_KI	Integral coefficient of PI3						

13.3.91 PI3_UKH (0x0380, 0x0381)

PI3_UKHH(0x0380)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_UKH[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI3_UKHL(0x0381)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_UKH[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_UKH	16 high-order bits of PI3 output						

13.3.92 PI3_UKL (0x0382, 0x0383)

PI3_UKLL(0x0382)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_UKL[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI3_UKLL(0x0383)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_UKL[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_UKL	16 low-order bits of PI3 output						

13.3.93 PI3_UKMAX (0x0384, 0x0385)

PI3_UKMAXH(0x0384)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_UKMAX[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI3_UKMAXL(0x0385)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_UKMAX[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_UKMAX	Maximum output of PI3						

13.3.94 PI3_UKMIN (0x0386, 0x0387)

PI3_UKMINH(0x0386)								
Bit	15	14	13	12	11	10	9	8
Name	PI3_UKMIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
PI3_UKMINL(0x0387)								
Bit	7	6	5	4	3	2	1	0
Name	PI3_UKMIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	PI3_UKMIN	Minimum output of PI3						

14 FOC

14.1 FOC Overview

14.1.1 FOC Introduction

FOC/SVPWM module is used in sensorless and sensed FOC motor drive applications and SVPWM-based motor control applications. Since SVPWM is a subset of FOC module, the following FOC/SVPWM module is referred to as FOC module for short. When DRV_CR[FOC_EN] = 0, FOC module is inactivated, and FOC clock stops. The relevant FOC registers are forced into the reset state and cannot be written.

FOC module consists of angle estimator, PI controller, coordinate transform module and PWM output module. The internal angle estimator can be used to implement sensorless FOC-based control. MCU can also process Hall signals to implement sensed FOC-based control. Moreover, FOC module contains a closed current loop, which outputs six channel PWM signals to drive the motor based on user-defined ID and IQ. Meanwhile, ADC automatically samples current signals to fulfill closed loop current control.

- Sensorless FOC: Angle for coordinate transformation is obtained by angle estimator, the motor speed is estimated for speed closed-loop control and BEMF is sensed for startup detection.
- Sensor-based FOC (Single/Dual/Triple Hall Sensors): FOC module provides the angle input interface. MCU samples Hall signals and calculates electrical angle of the motor. Software sends the result to FOC module for coordinate transformation.




Figure 14-1 FOC Block Diagram

14.1.2 Reference Voltage (VREF) Input

The current loop of FOC module uses the d-axis current reference value FOC_IDREF and the q-axis current reference value FOC_IQREF as the reference. FOC module outputs real-time estimated motor speed FOC_EOME. MCU or PI module can use FOC_EOME as the feedback to implement the speed-current dual closed loop control.

14.1.3 PI Controller

FOC module uses 4 PI controllers, which are respectively applied to:

1. Rotor flux control: PI controller of axis D, reference current FOC_IDREF minus feedback current FOC_ID as deviation input, proportional coefficient FOC_DKP and integral coefficient FOC_DKI to adjust the performance of PI controller, FOC_DMAX and FOC_DMIN to limit the output, and finally output D axis voltage FOC_UD.
2. Torque control: PI controller of q-axis current, with current reference FOC_IQREF minus feedback current FOC_IQ as the error input, proportional coefficient FOC_DQKP and the integral coefficient FOC_DQKI for adjustment of PI performance, and FOC_QMAX and FOC_QMIN for limiting of the output amplitude. The output is voltage reference of q-axis FOC_UQ.
3. Angle estimation: PI controller of the estimator, proportional coefficient FOC_EKP and integral coefficient FOC_EKI adjust the performance of PI controller, and finally output estimated angle FOC_ETHETA.
4. PLL estimation: PI controller of PLL estimator, proportional coefficient FOC_PLLKP and integral coefficient FOC_PLLKI adjust the performance of PI controller, and finally output estimated BEMF FOC_EALP and FOC_EBET.

14.1.4 Coordinate Transformation

14.1.4.1 Inverse Park Transformation




Figure 14-2 Park Transformation

Inverse Park transformation is used to transform two voltage vectors obtained by PI controller, FOC_UD and FOC_UQ, from dq-axis coordinate to $\alpha\beta$ -axis coordinate.

14.1.4.2 Inverse Clarke Transformation




Figure 14-3 Inverse Clarke Transformation

Inverse Clarke transformation is used to transform voltage vector from $\alpha\beta$ -axis coordinate to 3-phase stationary coordinate.

14.1.4.3 Clarke Transformation




Figure 14-4 Clarke Transform

Clarke transformation is used to transform the sampled current from 3-phase stationary coordinate to $\alpha\beta$ -axis coordinate.

14.1.4.4 Park Transformation




Figure 14-5 Park Transform

Park transformation is used to transform the current vectors, obtained after Clarke transformation, from $\alpha\beta$ -axis coordinate to dq-axis coordinate to get the sampled dq-axis current.

14.1.5 SVPWM

SVPWM algorithm is an important part of FOC. The main idea is to obtain quasi-circular rotating magnetic field by switching the inverter space voltage vectors. This method decreases harmonic components of the phase current, harmonic losses of the motor and torque ripple, and achieves high voltage utilization.

SVPWM generates pulse-width modulation signals for the three-phase motor voltage control, whose process can be reduced to a few simple equations. Since high side and low side of the three-phase inverter cannot be turned on simultaneously, there are two states for a phase, i.e., phase connected to bus voltage (+) or phase connected to ground (-). Therefore, voltage vector output of the inverter has a total of $2^3 = 8$ possible states. When all three phases are connected to bus voltage (+) or ground (-), no voltage drop exists between two phases and the two states are called inactive state or zero voltage vector. The other six states which have voltage output are active voltage vectors with an adjacent state rotation offset of 60 degrees.




Figure 14-6 SVPWM Voltage Vector

SVPWM uses the sum of two adjacent vectors to generate any voltage vector located in the voltage vector space. As shown in Figure 14-7, U_{OUT} is the desired vector and it is in the sector between U_{60} and U_0 . In defined PWM cycle (T), the effect, U_0 applied $2T_1/T$ time and U_{60} applied $2T_2/T$ time, is equivalent to the U_{OUT} . The rest of time (T_0) is applied by zero voltage vector.




Figure 14-7 SVPWM Voltage Vector Synthesis

Table 14-1 States of SVPWM Inverter

Phase C	Phase B	Phase A	V_{ab}	V_{bc}	V_{ca}	V_{ds}	V_{qs}	Vector
0	0	0	0	0	0	0	0	$U(000)$
0	0	1	V_{DC}	0	$-V_{DC}$	$2/3V_{DC}$	0	$U0$
0	1	1	0	V_{DC}	$-V_{DC}$	$1/3V_{DC}$	$1/3V_{DC}$	$U60$
0	1	0	$-V_{DC}$	V_{DC}	0	$-1/3V_{DC}$	$1/3V_{DC}$	$U120$
1	1	0	$-V_{DC}$	0	V_{DC}	$-2/3V_{DC}$	0	$U180$
1	0	0	0	$-V_{DC}$	V_{DC}	$-1/3V_{DC}$	$-1/3V_{DC}$	$U240$
1	0	1	V_{DC}	$-V_{DC}$	0	$1/3V_{DC}$	$-1/3V_{DC}$	$U300$
1	1	1	0	0	0	0	0	$U(111)$

14.1.5.1 Continuous SVPWM

In single-shunt current sampling mode, continuous SVPWM is always used. In dual-shunt current sampling mode, FOC_CR2[F5SEG] is set to “0” to select continuous SVPWM as the output mode.




Figure 14-8 Output Level of Continuous SVPWM

14.1.5.2 Discontinuous SVPWM

Discontinuous SVPWM is available in dual-shunt current sampling mode. FOC_CR2[F5SEG] is set to “1” to activate this mode.




Figure 14-9 Output Level of Discontinuous SVPWM

14.1.6 Overmodulation

Overmodulation is available in single/dual/triple-shunt current sampling mode. FOC_CR1[OVMDL] is set to “1” to enable overmodulation feature. The voltage output, FOC_UD, FOC_UQ and related limit amplitudes (MAX/MIN) are be multiplied by 1.15 in this mode.

14.1.7 Deadtime Compensation

Deadtime compensation is available in dual/triple-shunt current sampling mode. The compensation value of deadtime is configured by FOC_TSMIN. This mode improves sinusoidal waveform of the current.

14.1.8 Current and Voltage Sampling

In FOC mode, bus voltage and phase current are sampled by hardware automatically. Before FOC module operates, ADC and operational amplifier shall be enabled and the corresponding control registers be configured. No configuration is required for ADC channel and scan mode. Single/dual/triple-shunt current sampling mode is selected by setting FOC_CR1[CSM]. In single-shunt current sampling mode, ADC channel 4 is the default sampling channel of the bus current (itrip). In dual-shunt current sampling mode, ADC channel 0 and channel 1 are the default sampling channels of A-phase current (ia) and B-phase current (ib) respectively. In triple-shunt current sampling mode, ADC channel 0, channel 1 and channel 4 are the default sampling channels of ia, ib and C-phase current (ic) respectively. Channel 2 can be selected for bus voltage sampling.

14.1.8.1 Single-shunt Current Sampling Mode

FOC_CR1[CSM] is set to “0” to select the single-shunt current sampling mode. In this mode, FOC module samples itrip (channel 4) twice during the timer counting-up operation, and samples bus voltage during the timer counting-down operation and after FOC module completes the calculation.

Since deadtime affects the accuracy of current sampling, FOC module samples within T1' and T2', which is the applied time of active voltage vector with deadtime removed. FOC_TRGDLY is the register which advances or delays the current sampling time, and this register shall be configured reasonably to ensure sampling is completed within T1' and T2'. For example, when MCU clock rate = 24MHz(41.67ns) and

`FOC_TRGDLY = 5`, the sampling time is delayed by $41.67 \times 5 = 208\text{ns}$; and when `FOC_TRGDLY = 0xFB(-5)`, the sampling time is advanced by 208ns.

The time of single-shunt current sampling window may be not enough to sample the current in low modulation index and sector switching area. PWM waveform shall be adjusted to ensure the minimum sampling window required in the case. `FOC_TSMIN` (`FOC_TSMIN` = minimum sampling window + deadtime) is used to configure the compensation value of deadtime, and FOC module adjusts the PWM waveform automatically.

14.1.8.2 Dual/Triple-shunt Current Sampling Mode




Figure 14-10 Dual/Triple-shunt Sequential Current Sampling Mode

`FOC_CR1[CSM]` is set to “10/11” and `FOC_CR2[DSS]` to “0” to select dual/triple-shunt sequential current sampling mode. `FOC_TRGDLY` is used to configure the sampling time of a phase current (`ia(ib/ic` is determined according to the sector), and other phases are sampled at the end of previous sampling. The bus voltage is sampled during the timer counting-down operation and after FOC module completes the calculation. `FOC_TRGDLY` shall be configured reasonably to ensure current sampling time is within zero voltage vector (i.e. `pwm_a1,pwm_b1, pwm_c1=111`). For example, when MCU clock rate = 24MHz(41.67ns), `FOC_TRGDLY = 0xB2` and FOC timer counts down, `ia(ib/ic` is sampled at $41.67 \times 50 = 2.08\mu\text{s}$ before an underflow event, and then the other phases of `ia(ib/ic` are sampled.




Figure 14-11 Dual/Triple-shunt Alternate Current Sampling Mode

FOC_CR1[CSM] is set to “10/11” and FOC_CR2[DSS] to “1” to select dual/triple-shunt alternating current sampling mode. In this mode, FOC module performs calculation in every PWM cycle. However, only one phase current is sampled at each PWM cycle (ia(ib/ic is determined according to the sector). The first carrier cycle samples one phase of the ia(ib/ic, and the second carrier cycle samples the current of the other phase, so as to alternately sample the current of two phases in three phases. FOC_TRGDLY is used to configure the sampling time of ia (channel 0), ib (channel 1) and ic (channel 4). FOC_TRGDLY shall be configured reasonably to ensure sampling time for the ia(ib/ic current is within zero voltage vector (i.e. pwm_al,pwm_bl,pwm_cl = 111). For example, when MCU clock rate = 24MHz(41.67ns), FOC_TRGDLY = 0xB2 and FOC timer counts-down, phase current is sampled at $41.67 \times 50 = 2.08\mu s$ before an underflow event.

14.1.8.3 Current Sampling Offset

The current sampling offset voltage shall be added to sample full range of current due to the existence of the positive and negative phase current. When phase current is 0, ADC result is the offset value. ADC result minus this value, 0x4000 default, is the sampling current. Since ADC reference voltage and hardware are nonideal, there is a deviation between the default value and the real value. Therefore, it is necessary to calibrate the offset. The calibration procedure is as follows. When FOC module does not work and there is no current in three phases, MCU starts to sample the corresponding channel several times, averages all the sampled value, and writes the averaged value to FOC_CS0. Providing ADC sampling range is 0 ~ 5V and the offset is 2.5V, $FOC_CS0 = 2.5V/5V \times 32768 = 16384$ (0x4000).

- When FOC_CR2[CSOC] = 00/11, FOC_CS0 is written to modify the offset of itrip and ic.
- When FOC_CR2[CSOC] = 01, FOC_CS0 is written to modify the offset of ia.
- When FOC_CR2[CSOC] = 10, FOC_CS0 is written to modify the offset of ib.

14.1.9 Angle Mode

Angle module includes angle estimation module, ramping module and estimated angle smooth switching module. The sources of angle are as follows:

- Forced ramping angle
- Forced pulling angle
- Estimated angle of estimator
- Forced angle of estimator

Table 14-2 Sources of Angle

RFAE	ANGM	EFAE	Source
1	x	x	Forced ramping angle
0	0	x	Forced pulling angle
0	1	0	Estimated angle of estimator
0	1	1	omega > FOC_EFREQMIN: Estimated angle of estimator omega < FOC_EFREQMIN: Forced angle of estimator

14.1.9.1 Forced Ramping Angle

Forced ramping angle is controlled by angle FOC__THETA, speed FOC__RTHESTEP, acceleration FOC_RTHeACC and ramping counter FOC_RTHeCNT. The formula is:

$\text{FOC_RTHESTEP (32-bit)} = \text{FOC_RTHESTEP (32-bit)} + \text{FOC_RTHeACC (32-bit, 16 high-order bits are always 0 and 16 low-order bits are configurable)}$

$$\text{THETA_OL (16-bit)} = \text{FOC_THETA_OL (16-bit)} + \text{FOC_RTHESTEP (16 high-order bits)}$$

Forced ramping angle has the highest priority. Configuring FOC_CR1[RFAE] to “1” enables the ramping feature. Ramping module makes a ramping operation in every PWM cycle and the counter is added by 1. When the value of the counter reaches the set value by FOC_RTHeCNT, FOC_CR1[RFAE] is cleared by hardware, and then the ramping is completed. Thereafter, according to the value of FOC_CR1[ANGM], the angle comes from estimator (FOC_CR1[ANGM] = 1) or forced pulling angle (FOC_CR1[ANGM] = 0).

14.1.9.2 Forced Pulling Angle

Forced pulling angle is controlled by angle FOC__THETA and speed FOC__RTHESTEP.

The formula is: $\text{THETA_OL (16-bit)} = \text{THETA_OL (16-bit)} + \text{FOC_RTHESTEP (16 high-order bits)}$

There are two scenarios for forced pulling angle.

- When FOC_CR1[RFAE] is set to “1” and FOC_CR1[ANGM] to “0”, MCU switches to forced pulling angle mode after forced ramping angle mode. The speed is the cumulative result after ramp force angle mode. This mode implements a forced uniform speed control.
- When FOC_CR1[RFAE] is set to “0” and FOC_CR1[ANGM] to “0”, the angle is the forced pulling angle and the speed FOC__RTHESTEP is the initial speed written by software. Configuring FOC__RTHESTEP = 0 enables the pre-position feature. Configuring FOC__RTHESTEP != 0

implements Hall-based FOC (Principle of Hall-based FOC: MCU calculates the angle and speed based on the received Hall signals, and writes them to FOC__THETA and FOC__RTHESTEP for calibration).

14.1.9.3 Estimator Output Angle




Figure 14-12 Schematic Block Diagram of Estimator

The estimator collects the motor current and voltage and outputs the angle, speed and BEMF based on user-defined motor parameters and other control parameters.

14.1.9.3.1 Estimated Angle of Estimator

The estimator builds the motor model based on the motor parameters and control parameters, and outputs the estimated angle based on the sampled current and voltage. The estimator works in PLL mode or SMO mode by configuring the FOC_CR2[ESEL].

14.1.9.3.2 Forced Angle of Estimator




Figure 14-13 Schematic Diagram of Forced Angle of Estimator

This feature is similar to the ramping feature. Due to the low speed at motor starting process, there may be a deviation in angle and speed estimation with the small effective signal, resulting in startup failure. In this case, the estimator outputs the forced angle to ensure the motor start normally. When $\text{FOC_CR1[EFAE]} = 1$, if $\omega < \text{FOC_EFREQMIN}$, the forced speed is selected as $E\text{OME}$. The forced speed starts with 0 and increases by FOC_EFREQACC in each PWM cycle, with the maximum value FOC_EFREQHOLD . When $\omega \geq \text{FOC_EFREQMIN}$, ω is selected as $E\text{OME}$.

14.1.9.3.3 Angle Smooth Switching




Figure 14-14 Angle Smooth Switching Curve

hen FOC_CR1[RFAE] is set to “1” and FOC_CR1[ANGM] to “1”, the motor starts with ramping feature, and it switches to estimator angle mode after the ramping. However, there is usually a deviation between the estimated angle (FOC_ETHETA) and the forced ramping angle (THETA_OL). If the angle is switched from forced ramping angle to estimated angle directly, motor jitter may occur due to such a sudden change. To deal with this problem, a smooth switching is preferred.

After ramping, if the deviation between FOC_ETHETA and THETA_OL is less than or equal to FOC_THECOR , FOC_ETHETA is selected as the output angle. But if the deviation is larger than FOC_THECOR , THETA_OL is modified smoothly with the step of FOC_THECOR at every PWM cycle

until it is close to FOC__ETHETA. After the deviation is less than FOC_THECOR, FOC__ETHETA is selected as the output angle.

14.1.9.3.4 Angle Compensation

Angle compensation value FOC_THECOMP is used to compensate for the estimated angle FOC__ETHETA. If FOC_THECOMP is negative (MSB is 1), the lag angle is compensated; if it is positive (MSB is 0), the lead angle is compensated.

14.1.10 Motor Real-time Parameters

MCU monitors the state of motor using the following real time variables provided by FOC module:

- Used angle FOC__THETA
- Estimated angle FOC__ETHETA, Estimated speed FOC__EOME
- d-axis voltage FOC__UD, q-axis voltage FOC__UQ
- d-axis current FOC__ID, q-axis current FOC__IQ
- α -axis voltage FOC__VALP, β -axis voltage FOC__VBET
- Bus voltage FOC__UDCFLT
- Phase current FOC__IA, FOC__IB, FOC__IC and maximum phase current FOC__IAMAX, FOC__IBMAX, FOC__ICMAX
- α -axis current (equal to FOC__IA), β -axis current FOC__IBET
- α -axis BEMF FOC__EALP, β -axis BEMF FOC__EBET
- Square of BEMF FOC__ESQU
- Magnitude of BEMF FOC__EMF
- Motor power FOC__POW

14.1.10.1 Tailwind/headwind Detection

FOC module provides tailwind/headwind detection feature. FOC module starts to operate when FOC_CR3[ESCMS] is set to “1”, FOC_IDREF to “0” and FOC_IQREF to “0”. Motor’s rotor state is detected by FOC__ETHETA and FOC__EOME. If FOC__ETHETA decreases or FOC__EOME is a negative value, the motor rotates in the headwind state and it is necessary to brake first and then start the motor with ramping forced angle mode. If FOC__ETHETA increases or FOC__EOME is a positive value, the motor rotates in the tailwind state and can be started using estimated angle directly.

14.1.10.2 BEMF Detection

Estimator estimates α -axis BEMF FOC__EALP and β -axis BEMF FOC__EBET with the motor parameters, and calculates FOC__ESQU ($e\alpha^2 + e\beta^2$), which implements protection features, such as motor lock protection, phase loss protection, etc.

14.1.10.3 Motor Power

FOC module calculates motor power based on the sampling current, modulation index of SVPWM and bus voltage.

14.2 FOC Registers

14.2.1 FOC_CR1 (0x40A0)

Bit	7	6	5	4	3	2	1	0
Name	OVMXL	EFAE	RFAE	ANGM	CSM		RSV	SVPWMEN
Type	R/W	R/W	R/W	R/W	R/W	R/W	-	R/W
Reset	0	0	0	0	0	0	-	0
Bit	Name	Description						
[7]	OVMXL	Overmodulation Enable 0: Disable 1: Enable						
[6]	EFAE	Forced Angle of Estimator Enable When this feature is enabled, angle mode is determined by the estimator, and it switches to estimated angle mode automatically. 0: Disable 1: Enable						
[5]	RFAE	Forced Ramping Angle Enable When this feature is enabled, angle mode is determined by the ramping module. After ramping, it switches to estimated mode or forced pulling mode according to FOC_CR1[ANGM]. FOC_CR1[RFAE] is cleared to "0" by hardware as well. 0: Disable 1: Enable						
[4]	ANGM	Angle Mode When FOC_CR1[RFAE] = 0, angle mode is determined by this bit. When FOC_CR1[RFAE] = 1, angle mode is determined by this bit after ramping. 0: Forced Pulling Angle Mode 1: Estimated Angle of Estimator Mode						
[3:2]	CSM	Current Sampling Mode x0: Single-shunt Current Sampling 01: Dual-shunt Current Sampling 11: Triple-shunt Current Sampling						
[1]	RSV	Reserved						
[0]	SVPWMEN	SVPWM Module Enable 0: Disable 1: Enable						

14.2.2 FOC_CR2 (0x40A1)

Bit	7	6	5	4	3	2	1	0
Name	ESEL	RSV	F5SEG	DSS	CSOC		UQD	UDD
Type	R/W	-	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	-	0	0	0	0	0	0
Bit	Name	Description						
[7]	ESEL	Angle Estimator Mode Selection 0: SMO 1: PLL (phase-locked loop). FOC_KSILDE register is FOC_PLLKP of PI controller, and FOC_KLPFMIN register is FOC_PLLKI of PI controller.						
[6]	RSV	Reserved						

[5]	F5SEG	SVPWM Mode Selection in Dual/Triple-shunt Current Sampling Mode 0: Continuous SVPWM 1: Discontinuous SVPWM (cannot be selected in single-shunt current sampling mode)
[4]	DSS	Dual/Triple-shunt Current Sampling Mode 0: Sequential Sampling Mode, where the current of two phases are sampled in each carrier period. 1: Alternate Sampling Mode, where FOC module completes the calculation in every PWM cycle, and the current of two phases are sampled alternately in two adjacent PWM cycles.
[3:2]	CSOC	Current Sampling Offset Calibration This bit is written to select the offset of FOC_CS0. In single-shunt sampling, “00” or “11” is written to calibrate itrip offset. In dual-shunt sampling, “01” is written to calibrate ia offset and “10” to calibrate ib offset. In triple-shunt sampling, “01” is written to calibrate ia offset, “10” to calibrate ib offset and “00” or “11” to calibrate ic offset. 00: itrip & ic 01: ia 10: ib 11: itrip & ic
[1]	UQD	q-axis PI controller disabled, where FOC_UQ value is no longer updated by the PI controller. 0: Not forbid 1: Forbid
[0]	UDD	d-axis PI controller disabled, where the FOC_UD value is no longer updated by the PI controller. 0: Not forbid 1: Forbid

14.2.3 FOC_TSMIN (0x40A2)

Bit	7	6	5	4	3	2	1	0
Name FOC_TSMIN								
Type R/W R/W R/W R/W R/W R/W R/W R/W								
Reset 0 0 0 0 0 0 0 0								
Bit	Name	Description						
[7:0]	FOC_TSMIN	Single-shunt Sampling Mode: minimum window for sampling Dual/triple-shunt Sampling Mode: deadtime compensation Range (0,255)						
TSMIN = sampling window $T_{window} + \text{deadtime } T_{DT}$ Example: Assuming that $T_{window} = 1\mu s$, $T_{DT} = 1\mu s$, $TSMIN = 2\mu s$ and carrier period = $62.5\mu s$, then $FOC_TSMIN = (1 + 1)/62.5 * 4096 = 131$.								

14.2.4 FOC_TGLI (0x40A3)

Bit	7	6	5	4	3	2	1	0
Name FOC_TGLI								
Type R/W R/W R/W R/W R/W R/W R/W R/W								
Reset 0 0 0 0 0 0 0 0								
Bit	Name	Description						
[7:0]	FOC_TGLI	Narrow Pulse Elimination for High Side of the Bridge This feature is designed for high-voltage applications. The high side of bridge must be longer than a certain time. After this bit is configured, high side of the bridge is not turned on when the conducting time is less than this value. Range (0,255)						
Example: Assuming that it is required to remove narrow pulses with less than $1\mu s$ width, deadtime $T_{DT} = 1\mu s$, and carrier period = $62.5\mu s$, then $FOC_TGLI = (1 + 1)/62.5 * 4096 = 131$.								

14.2.5 FOC_TBLO (0x40A4)

Bit	7	6	5	4	3	2	1	0
Name	FOC_TBLO							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	FOC_TBLO	Sampling Masking Time in Triple-shunt Current Sampling Mode If low side of the bridge is turned on for less than FOC_TBLO, the current of this phase is not sampled and obtained through special process. Range (0,255)						
Example: Assuming that the phase current is not sampled if the low side is turned on for less than 1μs, then FOC_TBLO = 1000ns/41.67ns = 24.								

14.2.6 FOC_TRGDLY (0x40A5)

Bit	7	6	5	4	3	2	1	0
Name	FOC_TRGDLY							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	FOC_TRGDLY	Single-shunt Current Sampling Mode: Trigger Delay for ADC Current Sampling Range (-128,127) Dual/Triple-shunt Current Sampling Mode: Time for Current Sampling TRGDLY[7] decides the sampling occurs in falling or rising interval of the timer: TRGDLY[7] = 0: rising interval; TRGDLY[7] = 1: falling interval Range (0, DRV_ARR[6:0]) Single-shunt Current Sampling Mode: If FOC_TRGDLY = 5, it delays by 5*T = 208ns to sample the current, and if FOC_TRGDLY = 0xFB (complement) or FOC_TRGDLY = -5, it advances by 5*T=208ns. Dual-shunt/Triple-shunt Current Sampling Mode: If FOC_TRGDLY = 0x85 (the highest bit, and the remaining 7 bits are absolute values) and Driver timer counts down, it samples the current at 5*T = 208ns before an overflow event occurs. If OC_TRGDLY = 5 and Driver timer counts up, it samples the current at 5*T = 208ns after an overflow event occurs.						

14.2.7 FOC_CS0 (0x40A6, 0x40A7)

FOC_CSOH(0x40A6)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_CSO [15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	1	0	0	0	0	0	0
FOC_CSOL(0x40A7)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_CSO[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_CSO	Current Sampling Offset FOC_CR2[CSOC] is configured to select the current, and FOC_CSO is written to calibrate current sampling offset of itrip in single-shunt current sampling mode, ia, ib in dual-shunt current sampling mode and ia, ib and ic in triple-shunt current						

		sampling mode. Range (0,32767), the MSB is always 0
Example: Assuming that the ADC voltage falls within 0V ~ 5V with a reference value of 2.5V, then FOC_CS0 = 2.5V/5V*32768 = 16384(0x4000)		

14.2.8 FOC_RTHESTEP (0x40A8, 0x40A9)

FOC_RTHESTEPH(0x40A8)																
Bit	15	14	13	12	11	10	9	8								
Name	FOC_RTHESTEP[15:8]															
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W								
Reset	0	0	0	0	0	0	0	0								
FOC_RTHESTEPL(0x40A9)																
Bit	7	6	5	4	3	2	1	0								
Name	FOC_RTHESTEP[7:0]															
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W								
Reset	0	0	0	0	0	0	0	0								
Bit	Name		Description													
[15:0]	FOC_RTHESTEP		Speed of Ramping Module; The format is the same as that of FOC_THETA Write: Initial speed Read: Current speed Range (-32768,32767) Note: FOC_RTHESTEP is an internal 32-bit variable. MSB is sign bit. High-order 16 bits are written by software.													
FOC_RTHESTEP (32 bits) = FOC_RTHESTEP (32 bits) + FOC_RTHeACC (32 bits, 16 high-order bits are always 0 and 16 low-order bits are configurable)																
THETA (16 bits) = THETA (16 bits) + FOC_RTHESTEP (16 high-order bits)																

14.2.9 FOC_RTHeACC (0x40AA, 0x40AB)

FOC_RTHeACCH(0x40AA)																
Bit	15	14	13	12	11	10	9	8								
Name	FOC_RTHeACC[15:8]															
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W								
Reset	0	0	0	0	0	0	0	0								
FOC_RTHeACCL(0x40AB)																
Bit	7	6	5	4	3	2	1	0								
Name	FOC_RTHeACC[7:0]															
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W								
Reset	0	0	0	0	0	0	0	0								
Bit	Name		Description													
[15:0]	FOC_RTHeACC		Ramping Acceleration; The format is the same as that of FOC_THETA Range (-32768,32767) FOC_RTHeACC is an internal 32-bit variable. MSB is sign bit. Low-order 15 bits are written by software.													
FOC_RTHESTEP (32 bits) = FOC_RTHESTEP (32 bits) + FOC_RTHeACC (32 bits, 16 high-order bits are always 0 and 15 low-order bits are configurable)																
THETA (16 bits) = THETA_OL + FOC_RTHESTEP (16 high-order bits)																

14.2.10 FOC_RTHERCNT (0x40AC)

Bit	7	6	5	4	3	2	1	0
Name	FOC_RTHERCNT							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[7:0]	FOC_RTHERCNT		Max. ramping counts = FOC_RTHERCNT*256 When ramping feature is enabled (FOC_CR1[RFAE] = 1), the ramping angle increases in each PWM cycle. After FOC_RTHERCNT*256 times, ramping feature is disabled. Range (0,255)					

14.2.11 FOC_THECOR (0x40AD) (Shared with BLDC Motors)

Bit	7	6	5	4	3	2	1	0
Name	FOC_THECOR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R
Reset	0	0	0	0	0	0	0	1
Bit	Name		Description					
[7:0]	FOC_THECOR		Angle smooth switching correction: The step value of angle smooth switching after ramping. The format is the same as FOC__THETA. Range (0, 255)					

14.2.12 FOC_THECOMP (0x40AE, 0x40AF)

FOC_THECOMPH(0x40AE)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_THECOMP[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_THECOMPL(0x40AF)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_THECOMP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_THECOMP		Angle Compensation Value The output angle FOC__THETA is derived from the estimator estimated angle + compensation value; the format is same with that of FOC__THETA. Range (-32768,32767)					

14.2.13 FOC_DMAX (0x40B0, 0x40B1)

FOC_DMAXH(0x40B0)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_DMAX[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_DMAXL(0x40B1)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_DMAX[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description							
[15:0]	FOC_DMAX	Max. output UD of d-axis PI controller Range (-32768,32767)							

14.2.14 FOC_DMIN (0x40B2, 0x40B3)

FOC_DMINH(0x40B2)									
Bit	15	14	13	12	11	10	9	8	
Name	FOC_DMIN [15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
FOC_DMINL(0x40B3)									
Bit	7	6	5	4	3	2	1	0	
Name	FOC_DMIN[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit	Name	Description							
[15:0]	FOC_DMIN	Min. output UD of d-axis PI controller Range (-32768,32767)							

14.2.15 FOC_QMAX (0x40B4, 0x40B5)

FOC_QMAXH(0x40B4)									
Bit	15	14	13	12	11	10	9	8	
Name	FOC_QMAX[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
FOC_QMAXL(0x40B5)									
Bit	7	6	5	4	3	2	1	0	
Name	FOC_QMAX[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit	Name	Description							
[15:0]	FOC_QMAX	Max. output UQ of q-axis PI controller Range (-32768,32767)							

14.2.16 FOC_QMIN (0x40B6, 0x40B7)

FOC_QMINH(0x40B6)									
Bit	15	14	13	12	11	10	9	8	
Name	FOC_QMIN[15:8]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
FOC_QMINL(0x40B7)									
Bit	7	6	5	4	3	2	1	0	
Name	FOC_QMIN[7:0]								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit	Name	Description							
[15:0]	FOC_QMIN	Min. output UQ of q-axis PI controller; Range (-32768,32767)							

14.2.17 FOC_UD (0x40B8, 0x40B9)

FOC_UDH(0x40B8)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_UD[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_UDL(0x40B9)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_UD[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_UD	d-axis voltage calculated by d-axis PI controller Range (-32768,32767)						

14.2.18 FOC_UQ (0x40BA, 0x40BB)

FOC_UQH(0x40BA)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_UQ[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_UQL(0x40BB)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_UQ[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_UQ	q-axis voltage calculated by q-axis PI controller Range (-32768,32767)						

14.2.19 FOC_ID (0x40BC, 0x40BD)

FOC_IDH(0x40BC)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_ID[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_IDL(0x40BD)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_ID[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_ID	ID by Park Transformation Range (-32768,32767)						

14.2.20 FOC_IQ (0x40BE, 0x40BF)

FOC_IQH(0x40BE)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_IQ[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_IQL(0x40BF)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_IQ[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_IQ	IQ by Park Transformation Range (-32768,32767)						

14.2.21 FOC_IBET (0x40C0, 0x40C1)

FOC_IBETH(0x40C0)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_IBET[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_IBETL(0x40C1)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_IBET[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_IBET	Current IBETA Range (-32768,32767)						

14.2.22 FOC_VBET (0x40C2, 0x40C3)

FOC_VBETH(0x40C2)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_VBET[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_VBETL(0x40C3)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_VBET[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_VBET	VBETA by Inverse Park Transformation Range (-32768,32767)						

14.2.23 FOC__VALP (0x40C4, 0x40C5)

FOC__VALPH(0x40C4)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__VALP[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__VALPL(0x40C5)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__VALP[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC__VALP		VALPHA by Inverse Park Transformation Range (-32768,32767)					

14.2.24 FOC__IC (0x40C6, 0x40C7)

FOC__ICH(0x40C6)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__IC[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__ICL(0x40C7)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__IC[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC__IC		Sampled Phase-C Current Range (-32768,32767)					

14.2.25 FOC__IB (0x40C8, 0x40C9)

FOC__IBH(0x40C8)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__IB[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__IBL(0x40C9)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__IB[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC__IB		Sampled Phase-B Current Range (-32768,32767)					

14.2.26 FOC_IA (0x40CA, 0x40CB)

FOC_IAH(0x40CA)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_IA[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_IAL(0x40CB)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_IA[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_IA	Sampled Phase-A Current; Range (-32768,32767)						

14.2.27 FOC_THETA (0x40CC, 0x40CD)

FOC_THETAH(0x40CC)															
Bit	15	14	13	12	11	10	9	8							
Name	FOC_THETA[15:8]														
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W							
Reset	0	0	0	0	0	0	0	0							
FOC_THETAL(0x40CD)															
Bit	7	6	5	4	3	2	1	0							
Name	FOC_THETA[7:0]														
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W							
Reset	0	0	0	0	0	0	0	0							
Bit	Name	Description													
[15:0]	FOC_THETA	Output Angle Write: Forced Pulling Angle Read: Current Angle by FOC Module Range (-32768,32767)													
The bit value -32768 ~ 32767 corresponds to angle range -180°~ 180°.															
Example: Assuming that FOC_THETA = 8192, the output angle is $8192/32768 * 180^\circ = 45^\circ$.															

14.2.28 FOC_ETHETA (0x40CE, 0x40CF)

FOC_ETHETAH(0x40CE)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_ETHETA[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_ETHETAL(0x40CF)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_ETHETA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_ETHETA	Read: Output Angle of Estimator (angle before FOC_THECOMP is applied); the format is same as that of FOC_THETA.						

14.2.29 FOC_EALP (0x40D0, 0x40D1)

FOC_EALPH(0x40D0)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EALP[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_EALPL(0x40D1)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EALP[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_EBETL(0x40D3)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EBET[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_EOMEH(0x40D4)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EOME[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EOMEL(0x40D5)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EOME[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EOME (0x40D4, 0x40D5)								
Bit	Name		Description					
[15:0]	FOC_EOME		Output Speed OMEGA of Estimator Range (-32768,32767)					

14.2.31 FOC_EOME (0x40D4, 0x40D5)

FOC_EOMEH(0x40D4)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EOME[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EOMEL(0x40D5)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EOME[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EOME (0x40D4, 0x40D5)								
Bit	Name		Description					
[15:0]	FOC_EOME		Output Speed OMEGA of Estimator Range (-32768,32767)					

14.2.32 FOC_ESQU (0x40D6, 0x40D7)

FOC_ESQUH(0x40D6)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_ESQU[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_ESQL(0x40D7)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_ESQU[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	FOC_ESQU	Square of EBETA + square of EALPHA. The result is obtained from 16 high-order bits, with MSB being always 0. Range (0,32767)						

14.2.33 FOC_POW (0x40D8, 0x40D9)

FOC_POWH(0x40D8)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_POW[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_POWL(0x40D9)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_POW[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	FOC_POW	Motor Power Range (-32768,32767); An error occurs if this value is negative.						

14.2.34 FOC_EKP (0x4074, 0x4075) (Shared with BLDC Motors)

FOC_EKPH(0x4074)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EKP[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EKPL(0x4075)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EKP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Description								
[15:0]	FOC_EKP	KP of PI controller used by the estimator. Range (0,32767). MSB is always 0. Q12 format.						

14.2.35 FOC_EKI (0x4076, 0x4077) (Shared with BLDC Motors)

FOC_EKIH(0x4076)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EKI[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EKIL(0x4077)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EKI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_EKI	KI of PI controller used by the estimator Range (0,32767); MSB is always 0; Q15 format.						

14.2.36 FOC_EBMFK (0x407C, 0x407D) (Shared with BLDC Motors)

FOC_EBMFKH(0x407C)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EBMFK[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EBMFKL(0x407D)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EBMFK[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_EBMFK	Coefficient used to calculate BEMF low-pass filter coefficient EKLPF Range (0,32767); Q15 format.						
EKLPF = EBMFK * OMEGA EBMFK = $2 * \pi * f_{base} * \Delta T$								

14.2.37 FOC_KSLIDE (0x4078, 0x4079) (Shared with BLDC Motors)

FOC_KSLIDEH(0x4078)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_KSLIDE / FOC_PLLKP[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_KSLIDEL(0x4079)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_KSLIDE / FOC_PLLKP [7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_KSLIDE /FOC_PLLKP	FOC_CR2[ESEL] = 0: KSLIDE coefficient; Q15 format FOC_CR2[ESEL] = 1: KP of PI controller on PLL; Q12 format Range (0,32767); MSB is always 0.						

14.2.38 FOC_EKLPFMIN (0x407A, 0x407B) (Shared with BLDC Motors)

FOC_EKLPFMINH(0x407A)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EKLPFMIN / FOC_PLLKPI[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EKLPFMINL(0x407B)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EKLPFMIN / FOC_PLLKPI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_EKLPFMIN / FOC_PLLKI		FOC_CR2[ESEL] = 0: The minimum value of BEMF low pass filter factor. EKLPF is forced to be this value when it is lower than this value. Q15 format. FOC_CR2[ESEL] = 1: PI controller KI coefficient on PLL. Q15 format. Range (0,32767); MSB is always 0.					

14.2.39 FOC_OMEKLPF (0x407E, 0x407F)

FOC_OMEKLPFH(0x407E)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_OMEKLPF[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_OMEKLPFL(0x407F)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_OMEKLPF[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_OMEKLPF		LPF factor of estimated speed of the estimator. Range (0,32767); MSB is always 0. Q15 format.					

14.2.40 FOC_FBASE (0x4080, 0x4081)

FOC_FBASEH(0x4080)																
Bit	15	14	13	12	11	10	9	8								
Name	FOC_FBASE[15:8]															
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W								
Reset	0	0	0	0	0	0	0	0								
FOC_FBASEL(0x4081)																
Bit	7	6	5	4	3	2	1	0								
Name	FOC_FBASE[7:0]															
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W								
Reset	0	0	0	0	0	0	0	0								
Bit	Name		Description													
[15:0]	FOC_FBASE		Coefficient of angular increment DELTA THETA that is calculated based on OMEGA													
FBASE = fbase * $\Delta T * 32768$																
Assuming that fbase = 200Hz and $\Delta T = 62.5\mu s$, then FBASE = 409																

14.2.41 FOC_EFREQACC (0x4082, 0x4083) (Shared with BLDC Motors)

FOC_EFREQACCH(0x4082)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EFREQACC[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EFREQACCL(0x4083)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EFREQACC[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_EFREQACC		Speed Increment of the Forced Angle Mode Range (0,65535) FOC_EFREQACC is an internal 24-bit variable and MSB is sign bit. Low-order 16 bits are written by software.					
Example: Assuming that fbase = 200Hz and pp (Pole_Pairs) = 4, then speed_base = 60*fbase/pp = 3000rpm. If speed increment = 3rpm, then FOC_EFREQACC = 3rpm/speed_base*32768*256 = 8388(0x20C4).								

14.2.42 FOC_EFREQMIN (0x4084 0x4085) (Shared with BLDC Motors)

FOC_EFREQMINH(0x4084)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EFREQMIN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EFREQMINL(0x4085)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EFREQMIN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_EFREQMIN		Minimum value of Omega: With Forced Angle of Estimator Mode enabled, FOC module outputs forced angle when the estimated angle is smaller than the bit value. Range (-32768,32767) Note: FOC_EFREQMIN is an internal 24-bit variable, and MSB is sign bit. High-order 16 bits are written by software.					
Example: Assuming that fbase = 200Hz and pp (Pole_Pairs) = 4, then speed_base = 60*fbase/pp = 3000rpm. Assuming that the minimum Omega = 30rpm, then FOC_EFREQMIN = 30rpm/speed_base*32768 = 327(0x147).								

14.2.43 FOC_EFREQHOLD (0x4086, 0x4087) (Shared with BLDC Motors)

FOC_EFREQHOLDH(0x4086)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EFREQHOLD[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

FOC_EFREQHOLDL(0x4087)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EFREQHOLD[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	FOC_EFREQHOLD	Hold value of Omega: When Omega rises to this value, it is kept unchanged. Range (-32768,32768) FOC_EFREQHOLD is an internal 24-bit variable, and MSB is sign bit. High-order 16 bits are written by the software.

Example: Assuming that fbase = 200Hz and pp (Pole_Pairs) = 4, then speed_base = 60*fbase/pp = 3000rpm. If hold value of Omega = 60rpm, then FOC_EFREQHOLD = 60rpm/speed_base*32768 = 655(0x028F).

14.2.44 FOC_EK3 (0x4088, 0x4089)

FOC_EK3H(0x4088)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EK3[15:8]							
Type	R	R/W						
Reset	0	0	0	0	0	0	0	0
FOC_EK3L(0x4089)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EK3[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	FOC_EK3	The 3 rd coefficient of the current model in estimator; Range (0, 32767) and MSB is always 0. Q15 format

14.2.45 FOC_EK4 0x408A, 0x408B)

FOC_EK4H(0x408A)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EK4[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EK4L(0x408B)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EK4[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	FOC_EK4	The 4 th coefficient of the current model in estimator.

14.2.46 FOC_EK1 (0x408C, 0x408D)

FOC_EK1H(0x408C)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EK1[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EK1L(0x408D)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EK1[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_EK1	The 1 st coefficient of the current model in estimator; Range (0,32767) and MSB is always 0. Q15 format.						

14.2.47 FOC_EK2 (0x408E, 0x408F)

FOC_EK2H(0x408E)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_EK2[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_EK2L(0x408F)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_EK2[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_EK2	The 2 nd coefficient of the current model in estimator; Range (0,32767) and MSB is always 0. Q15 format.						

14.2.48 FOC_IDREF (0x4090, 0x4091) (Shared with BLDC Motors)

FOC_IDREFH(0x4090)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_IDREF[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_IDREFL(0x4091)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_IDREF[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_IDREF	User-defined Current ID Range (-32768,32767)						

14.2.49 FOC_IQREF (0x4092, 0x4093) (Shared with BLDC Motors)

FOC_IQREFH(0x4092)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_IQREF[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_IQREFL(0x4093)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_IQREF[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_IQREF		User-defined Current IQ Range (-32768,32767)					

14.2.50 FOC_DQKP (0x4094, 0x4095) (Shared with BLDC Motors)

FOC_DQKPH(0x4094)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_DQKP[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_DQKPL(0x4095)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_DQKP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_DQKP		KP of dq-axis PI Controller Range (0,32767); MSB is always 0. Q12 format.					

14.2.51 FOC_DQKI (0x4096, 0x4097) (Shared with BLDC Motors)

FOC_DQKIH(0x4096)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_DQKI[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_DQKIL(0x4097)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_DQKI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC_DQKI		KI of dq-axis PI Controller Range (0,32767); MSB is always 0. Q15 format.					

14.2.52 FOC__UDCFLT (0x4098, 0x4099)

FOC__UDCFLTH(0x4098)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__UDCFLT[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__UDCFLTL(0x4099)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__UDCFLT[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC__UDCFLT		Filtered Bus voltage FOC module samples the bus voltage and filters it for software use. The default channel is ADC channel 2. Range (0,32767)					
Example: The bus voltage is scaled down by 1/6 before feeding into the ADC module, ADC VREF = 5V (namely, the sampling range is [0V ~ 30V]) and FOC__UDCFLT = 19661(0x4CCD), then bus voltage = 19661/32768*5V*6 = 18V.								

14.2.53 FOC_CR3 (0x40ee)

FOC_CR3(0x40ee)								
Bit	7	6	5	4	3	2	1	0
Name	ICLR	RSV	MFP_EN	FOCUSSTA	FOCFEN	ESCMS	TSMINH9	TSMINH8
Type	R/W	-	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	-	0	0	0	0	0	0
Bit	Name		Description					
[7]	ICLR		Clear FOC__IA/B/CMAX to “0” A write of “1” clears FOC__IA/B/CMAX to “0”. The bit is automatically set to “0” after FOC__IA/B/CMAX are cleared to “0”. 0: Disable 1: Enable					
[6]	RSV		Reserved					
[5]	MFP_EN		Adaptive Observer Enable 0: Disable 1: Enable					
[4]	FOCUSSTA		Single-shunt Off Sampling Enable 0: Disable 1: Enable					
[3]	FOCFEN		FOC Force Enable Bit When DRV_CR[MESEL] is set to “1”, FOC module performs calculation even if DRV_CR[OCS] = 0. 0: Disable 1: Enable					
[2]	ESCMS		ATAN Estimation Enable 0: Disable 1: Enable					
[1:0]	TSMINH[9:8]		Scale up by two bits of FOC_TSMIN					

14.2.54 FOC_DKP (0x409c, 0x409d)

FOC_DKPH(0x409c)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_DKP[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_DKPL(0x409d)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_DKP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]It	FOC_DKP	KP of d-axis PI Controller Range (0,32767) MSB is always 0, Q12 format It is effective when FOC_DKP! = 0. Otherwise, the original FOC_DQKP/I is applied.						

14.2.55 FOC_DKI (0x409e, 0x409f)

FOC_DKIH(0x409e)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_DKI[15:8]							
Type	R	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_DKIL(0x409f)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_DKI[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_DKI	KI of d-axis PI Controller Range (0,32767) MSB is always 0. Q15 format						

14.2.56 FOC_IAMAX (0x40da, 0x40db)

FOC_IAMAXH(0x40DA)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_IAMAX[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC_IAMAXL(0x40DB)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_IAMAX[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	FOC__Iamax	<p>Max. Phase-A Current This value may be unreliable unless the motor rotates in a full electrical period. It is also incorrect if the phase current is collected improperly. This maximum value will not be cleared to “0” automatically unless FOC_CR3[ICLR] is set to “1”. Range (0,32767)</p>

14.2.57 FOC__IBMAX (0x40dc, 0x40dd)

FOC__IBMAXH(0x40DC)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__IBMAX[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__IBMAXL(0x40DD)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__IBMAX[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC__IBMAX	<p>Max. Phase-B Current This value may be unreliable unless the motor rotates in a full electrical period. It is also incorrect if the phase current is collected improperly. This maximum value will not be cleared to “0” automatically unless FOC_CR3[ICLR] is set to “1”. Range (0,32767)</p>						

14.2.58 FOC__ICMAX (0x40de, 0x40df)

FOC__ICMAXH(0x40DE)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__ICMAX[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__ICMAXL(0x40DF)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__ICMAX[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC__ICMAX	<p>Max. Phase-C Current This value may be unreliable unless the motor rotates in a full electrical period. It is also incorrect if the phase current is collected improperly. This maximum value will not be cleared to “0” automatically unless FOC_CR3[ICLR] is set to “1”. Range (0,32767)</p>						

14.2.59 FOC__EMF (0x40e0, 0x40e1)

FOC__EMFH(0x40E0)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__EMF [15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__EMFL(0x40E1)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__EMF[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC__EMF	Estimated BEMF of Estimator This value is the root of sum of square of FOC__EALP and square of FOC__ EBET Range (0,32767)						

14.2.60 FOC__UDCPS (0x40e2,0x40e3)

FOC__UDCPSH(0x40e2)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__UDCPS[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC__UDCPSL(0x40e3)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__UDCPS[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC__UDCPS	d-axis Voltage Compensation Value The result of d-axis PI controller (FOC__UD) added to FOC__UDCPS is transferred to the next module. Range (-32768,32767)						

14.2.61 FOC__UQCPS (0x40e4, 0x40e5)

FOC__UQCPSH(0x40e4)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__UQCPS [15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC__UQCPSL(0x40e5)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__UQCPS [7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						

[15:0]	FOC__UQCPS	q-axis Voltage Compensation Value The result of q-axis PI controller (FOC__UD) added to FOC_UQCPS is transferred to the next module. Range (-32768,32767)
--------	------------	---

14.2.62 FOC__UQEX (0x40e6, 0x40e7)

FOC__UQEXH(0x40e6)								
Bit	15	14	13	12	11	10	9	8
Name	FOC__UQEX [15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
FOC__UQEXL(0x40e7)								
Bit	7	6	5	4	3	2	1	0
Name	FOC__UQEX[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	FOC__UQEX		q-axis Overflow Value for Flux-weakening Control Equation: FOC_UQ - FOC_QMAX FOC__UQEX is positive when FOC_UQ > FOC_QMAX; FOC__UQEX is negative when FOC_UQ < FOC_QMAX; FOC__UQEX can be used to realize flux-weakening control. Range (-32768, 32768)					

14.2.63 FOC_ID_LPKF (0x40e8)

Bit	7	6	5	4	3	2	1	0
Name	FOC_ID_LPKF [7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	1	1	1	1	1	1	1	1
Bit	Name		Description					
[7:0]	FOC_ID_LPKF		LPF coefficient of FOC__ID Range 0 ~ 255					

14.2.64 FOC_IQ_LPKF (0x40e9)

Bit	7	6	5	4	3	2	1	0
Name	FOC_IQ_LPKF[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	1	1	1	1	1	1	1	1
Bit	Name		Description					
[7:0]	FOC_IQ_LPKF		LPF coefficient of FOC__IQ Range 0 ~ 255					

14.2.65 FOC_KFG (0x40ea, 0x40eb)

FOC_KFGH(0x40ea)								
Bit	15	14	13	12	11	10	9	8
Name	FOC_KFG [15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
FOC_KFGL(0x40eb)								
Bit	7	6	5	4	3	2	1	0
Name	FOC_KFG[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	FOC_KFG	Coefficient of FG Calculation FOC module performs the calculation based on FOC_EOMELPF and FOC_KFG in each PWM cycle. The result is updated to TIM4__ARR and half of the result (TIM4__ARR/2) to TIM4__DR by hardware. Note: When FOC_KFG = 0, this feature is disabled. Range (0,65535); The clock division factor TIM4_CR0[T4PSC] of Timer4 shall be adjusted if FOC_KFG overflows.						

15 Timer1

15.1 Timer1 Operations

Timer1 consists of an internal 16-bit up-counting Base Timer and an internal 16-bit up-counting Reload Timer. Timer1 can be used in the applications of square-wave controlled BLDC motor drive or Hall signals processing.

Timer1 features as follows.

- The 16-bit up-counting Base Timer is used to record the time between two position detected events or writing timings, that is, two phase commutations (60 degree time);
- The 16-bit up-counting Reload Timer is used to control the time between position detection and reload timer overflow, that is, masking time for diode freewheeling as well as the time from ZCP to phase commutation.
- The 3-bit programmable frequency prescaler divides the system clock. The divided clock is used as the clock source of the two timers.
- Input filtering and sampling
- Position detection module generates the position signal required according to the input signal
- The output status register is updated by the write timing module
- 7 groups state register control comparators and outputs
- 6 interrupt sources
 - Basic timer overflow interrupt
 - Reload timer overflow interrupt
 - Writing timing interrupt
 - Position detection interrupt
 - Shield freewheeling end interrupt
 - ADC detection interrupt

The internal structure of Timer1 is shown in Figure 15-1.




Figure 15-1 Timer1 Internal Structure

15.1.1 Timer1 Counter Module




Figure 15-2 Timebase Unit

Timer1 consists of a frequency prescaler, an 16-bit up-counting Base Timer and an 16-bit up-counting Reload Timer.

15.1.1.1 Prescaler

Prescaler divides the system clock frequency and generates the counter clock source for Base Timer and Reload Timer. It offers 8 division coefficients and can be selected through TIM1_CR3[T1PSC]. Since this register has no buffer, the clock rate is immediately updated after the division coefficient is written. Therefore, the division coefficient shall be configured when both the Basic Timer and Reload Timer are not working. Clock rate $\text{clk_psc} = \text{SYSCLK}/(2^{\text{TIM1_CR3}[T1PSC]})$. The rate corresponding to TIM1_CR3[T1PSC] is

shown in Table 15-1.

Table 15-1 Mapping between Clock Rate and TIM1_CR3[T1PSC]

PSC	Coefficient (Hexadecimal)	CLK(Hz)	PSC	Coefficient (Hexadecimal)	CLK(Hz)
000	0x1	24M	100	0x10	1.5M
001	0x2	12M	101	0x20	750K
010	0x4	6M	110	0x40	375K
011	0x8	3M	111	0x80	187.5K

15.1.1.2 Base Timer

The Base Timer is a 16-bit up timer with its count value held in TIM1__BCNTR. When count value of TIM1__BCNTR increases to TIM1__BARR, overflow interrupt flag TIM1_SR[T1BOIF] of the Basic Timer is set to “1” and TIM1__BCNTR continues (instead of being cleared to “0” to restart the counter cycle). TIM1__BCNTR value is loaded into TIM1__BCCR upon a Position Detected Interrupt or a Write Timing Interrupt (selected by TIM1_CR2[T1BRS]). Meanwhile, TIM1__BCNTR is cleared to “0” and restarts the counter cycle.




Figure 15-3 Waveform of Base Timer

TIM1_BARR register shall be updated when the basic timer stops working, so that its value is immediately applied to the timer. The overflow event occurs only when TIM1_BCNTR is equal to the value held by TIM1_BARR. When TIM1_BCNTR is larger than the value held by TIM1_BARR, TIM1_BCNTR restarts from 0 after it reaches 0xFFFF. In this case, TIM1_BCNTR cannot be greater than TIM1_BARR after the register is initialized.

15.1.1.3 Reload Timer

The Reload Timer is a 16-bit up timer with its count value held in TIM1__RCNTR. The timer overflows when TIM1__RCNTR increases to TIM1__RARR. In this case, TIM1_SR[T1ROIF] (overflow interrupt flag of the reload counter) is set to “1”, and TIM1__RCNTR and TIM1_CR0[T1RCEN] are cleared to “0”. The timer restarts after TIM1_CR0[T1RCEN] is set to “1”.




Figure 15-4 Waveform of Reload Timer

TIM1_CR0[T1RCEN] is set to “1” upon a position detection interrupt or write timing interrupt. After the Reload Timer overflows, TIM1_CR0[T1RCEN] is cleared to “0” by hardware and the timer stops counting. The Reload Timer is mainly used to realize diode freewheeling masking and delay commutation after ZCP for square-wave control over BLDC motors. It does not work in other situations.

15.1.2 Position Detection




Figure 15-5 Functional Block Diagram of Position Detection

The TIM1_CR3[T1TIS] bit selects the sources of Position Detection signal, including comparator or GPIO. CMP_CR1[HALLSEL] bit is used to configure GPIO sourced by P1.4/P1.6/P2.1. TIM1_CR3[T1INM] bit decides whether CMP/GPIO signal is filtered and CMP_CR3[SAMSEL] bit determines sampling delay feature is enabled or disabled.

15.1.2.1 Position Detection Event




Figure 15-6 Functional Block Diagram of Position Detection

The register bank TIM1_DBR1/2/3/4/5/6/7[T1CPE] is configured to select the active edge of position

detection signal. An position detection event is generated after an input active edge (TI2/TI1/TI0) is detected. TIM1_CR4[T1CST] bit selects TIM1_DBR1/2/3/4/5/6/7[T1CPE] timing.




Figure 15-7 Timing Diagram of CMP/GPIO Position Detection

The relation between active edge and TIM1_DBR1/2/3/4/5/6/7[T1CPE] is shown in Table 15-2.

Table 15-2 Mapping between Active Edge and TIM1_DBR1/2/3/4/5/6/7[T1CPE]

T1CPE	Description	T1CPE	Description
000	0	100	U-phase corresponding comparator is enabled when falling edge of U-phase is detected.
001	U-phase corresponding comparator is enabled when rising edge of U-phase is detected.	101	W-phase corresponding comparator is enabled when rising edge of W-phase is detected.
010	W-phase corresponding comparator is enabled when falling edge of W-phase is detected.	110	V-phase corresponding comparator is enabled when falling edge of V-phase is detected.
011	V-phase corresponding comparator is enabled when rising edge of V-phase is detected.	111	U+W+V-phase corresponding comparator is enabled when rising falling edge of U+W+V-phase is detected.

15.1.2.1.1 Sampling




Figure 15-8 PWM ON Sampling Mode




Figure 15-9 PWM OFF Sampling Mode

In the square wave control mode, the input of TI2/TI1/TI0 comes from the comparator. Due to MOS on-off from driving circuit, PWM signals create electromagnetic interference. Therefore, CMP_CR3[SAMSEL], CMP_SAMR[CSOFFD] and CMP_SAMR[CSOND] bits shall be set reasonably to adjust the sampling interval and obtain the valid position detection signal.

There is a delay from PWM output to the output of the comparator, which is mainly affected by the following factors: resistance value of drive resistor, MOS on-off speed, and input delay and hysteresis settings of the comparator. In this case, CMP_SAMR[CSOFFD] is set to delay comparator sampling by offdelay, in order to avoid the interference from comparators, where offdelay = CSOND-CSOFFD and means the sampling delay for CMP0, CMP1 and CMP2.

For example, the delay from PWM output to the output of the comparator is 2μs and the interference width is 1μs, then

$$CSOFFD > 1\mu s = 1000ns/41.67ns/8 = 3$$

$$CSOND > (2 + 1) \mu s = 3000ns/41.67ns/8 = 9$$

Method for measuring the delay of PWM output to comparator: Set CMP_CR3[SAMSEL] = 00 to

disable the comparator sampling delay feature. Set CMP_CR3[CMPSEL] to select the corresponding comparator output. Enable PWM output and comparator, manually rotate the motor to change the comparator value, and measure the delay between the PWM output and the comparator output.

Method for measuring interference width: The operations are the same as above.

15.1.2.1.2 Filtering




Figure 15-10 Timing Diagram of Filtering Module

According to TIM1_CR3[T1INM], the filtered pulse width of input noise can be selected as 8/32/64 system clock. After this feature is enabled, the signal is lagged behind about 8 ~ 9/32 ~ 33/64 ~ 65 system clock.

15.1.3 Write Timing Interrupt




Figure 15-11 Write Timing Block Diagram

The triggered source of write timing interrupt is selected by TIM1_CR0[T1OPS]. After a writing sequence interrupt is generated, writing sequence interrupt flag TIM1_SR[T1WTIF] is set to “1”. If TIM1_CR4[T1CST] ranges in 001 ~ 110, TIM1_CR4[T1CST] adds 1 automatically and the value held by TIM1_DBR1/2/3/4/5/6/7 is updated to DRV_CMU.

15.1.4 Timer1 Interrupt

Timer1 supports 6 interrupt sources:

- Base Timer overflow interrupt
- Reload Timer overflow interrupt
- Writing sequence interrupt
- Position Detected Interrupt
- Diode Freewheeling End Interrupt
- ADC Position Detected Interrupt

Configuring enable bit of TIM1_IER enables or disables the corresponding interrupt request.




Figure 15-12 Timer1 Interrupt Sources

15.2 Square-wave Control Based BLDC Motor

For BLDC motor square-wave control application, Timer1 works with comparators and Driver module to achieve the following features:

- Automatic record of 60 degree time, filtered as 60 degree reference time
- Automatic forced phase commutation when position signal is not detected
- Automatic diode freewheeling masking, i.e., stopping comparator sampling during diode freewheeling
- Automatic control of the time from position detected to phase commutation to achieve automatic commutation
- Take over CMP_CR2[CMP0SEL] to control CMP0 automatically
- Comparator signals can be sampled during PWM ON/OFF, and the signals can be filtered as well
- Take over DRV_CM register to control three-phase 6 PWM outputs automatically

Square-wave control is mainly used for sensorless applications of BLDC motors, where 30-degree commutation delay is implemented after BEMF zero-crossing points. The following example is based on this principle (TIM1_CR0[T1OPS] = 01).

15.2.1 Six-Step Phase Commutation of Square Wave Control




Figure 15-13 Diagram of Six-step Phase Commutation of Square Wave Control

TIM1_CR4[T1CST] is the commutation state machine. Among them, state 0 is used to output off state, and state 7 is customizable for braking, pre-charging, pre-positioning, startup, etc. States 1 ~ 6 are used for six-step automatic commutation, and the state machine TIM1_CR4[T1CST] automatically adds 1 after phase commutation.

The states 1 ~ 7 maps to the TIM1_DBRI ~ 7. When writing sequence interrupt occurs, TIM1_DBRx corresponding to the current state is automatically transferred to DRV_CMRI and CMP_CR2[CMP0SEL] for phase commutation and position detection.

15.2.2 Working Principle of BLDC Motor




Figure 15-14 Working Principle of BLDC Motor

15.2.2.1 60° Commutation Base Time

TIM1__BCCR captures the time of last 60 degree. TIM1_CR2[T1BRS] is set to "0" to capture the time between two writing sequence interrupts and TIM1_CR2[T1BRS] to "1" to capture the time between two position detected interrupts.

TIM1_BCOR is the filtered 60 degree time, i.e., 60 degree base time. TIM1_CR0[T1CFLT] can select the last 1/2/4/8 TIM1__BCCR averaged to obtain TIM1_BCOR.

The diode freewheeling masking time, the time from ZCP to phase commutation, and the time to forced commutation are determined by the 60 degree base time TIM1_BCOR.

15.2.2.2 Phase Commutation

TIM1_CR1[T1OPS] decides phase commutation mode or writing timing event. Configuring TIM1_CR1[T1OPS] = 00 enables sensorless control, TIM1_CR1[T1OPS] = 01 enables sensorless automatic

commutation, or TIM1_CR1[T1OPS] = 10 enables sensored commutation

After phase commutation, Timer1 automatically performs the following operations:

1. Store the data held by TIM1_BCNTR to TIM1_BCCR for filtering, and then sends it to TIM1_BCOR as the 60 degree base time;
2. TIM1_BCNTR starts counting from “0”;
3. Start freewheeling mask, write the mask angle into TIM1_RARR and set TIM1_CR0[T1RCEN] to “1”. TIM1_RCNTR begins to count;
4. If TIM1_CR4[TICST] is in the state 1 to 6, it automatically switches to the next state;
5. Write timing interrupt TIM1_SR[T1WTIF] and reload timer overflow interrupt TIM1_SR[T1ROIF] are generated.

15.2.2.3 Forced Commutation at 60°

When the motor rotates smoothly, ZCP is generally detected after 30 degrees of rotation after phase commutation. If ZCP is not detected in 60 degree after the phase commutation, a forced phase commutation is required. In this case, TIM1_CR0[T1FORC] is set to “1” to enable the forced commutation feature. If no ZCP is detected in 60 degree after commutation, TIM1_SR[T1BOIF] (overflow interrupt flag of the Basic Timer) is set to “1” for forced phase commutation (Note: If an ZCP is detected within 60 degrees after phase commutation, even when TIM1_BCNTR > TIM1_BARR, the forced commutation will not be triggered and TIM1_SR[T1BOIF] will not be set to “1”). When forced commutation feature is disabled (TIM1_CR0[T1FORC] = 0) and TIM1_BCNTR > TIM1_BARR, the interrupt flag TIM1_SR[T1BOIF] is set to “1” and TIM1_BCNTR continues. Phase commutation can be performed manually by Basic Timer overflow interrupt flag TIM1_SR[T1BOIF] and the position detected interrupt flag TIM1_SR[T1PDIF].

15.2.2.4 Diode Freewheeling Masking

After the commutation, inductance energy of the phase is released to the power supply or ground through the diode since the original active phase becomes a floating phase. By masking comparator signal during freewheeling time, wrong commutation caused by wrong signal generated by the freewheeling is avoided. After freewheeling masking, the freewheeling masking end interrupt flag TIM1_SR[T1BDIF] is generated.

Timer1 holds the last latched level value of the comparator during freewheeling masking, and samples the level value after freewheeling masking. If the time for freewheeling masking is shorter than that for freewheeling, a false zero-crossing trigger point is generated. Therefore, it is necessary to adjust freewheeling masking time according to motor characteristics and ensure it is longer than freewheeling time.

Freewheeling masking time is set by TIM1_CR1[BSEL] with the formula: Masking angle = TIM1_CR1[BSEL]/128*60°.

15.2.2.5 Angle of ZCP to Phase Commutation (Delayed Commutation)

A zero-crossing detection is performed after diode freewheeling masking. If no ZCP is detected, the detection continues until phase commutation. It is triggered by a position detected interrupt, and only the first position detected interrupt is the effective trigger source. If a ZCP is detected, zero-crossing detection is completed and other subsequent trigger sources become invalid. Therefore, parameters related to filtering and sampling must be properly configured to ensure the first trigger source is a correct zero-crossing point.

After commutation, a ZCP is detected (generating a position detected interrupt) and the hardware starts TIM1_RCNTR for counting according to the software-set time between ZCP and the commutation. After the counting ends, the hardware automatically implements phase commutation and generates the writing sequence interrupt flag TIM1_SR[T1WTIF].

The time between ZCP and phase commutation is set by TIM1_CR2[CSEL] with the formula:
Commutation angle = TIM1_CR2[CSEL]/128*60°.

15.2.2.6 Cycle-by-cycle Current Limiting

See section 29.1.1.2.

15.2.3 BLDC Motor Debugging

The chip supports the following debugging methods.

1. GP07 displays comparator signals in real time
2. GP01 displays the status of Timer1 in real time
3. SPI debugger displays Timer1 related registers on the oscilloscope

15.2.3.1 Comparator Debugging

Configure CMP_CR3[CMPSEL] to output CMP0/1/2_OUT via GP07. CMP0/1/2_OUT is the filtered comparator signal.

Configure CMP_CR3[DBGSEL] = 11 to output comparator signals via GP01. See section 15.1.2.1.1 for waveforms. Select sampling delay by CMP_CR3[SAMSEL], as shown in the below table.

Table 15-3 Relation between CMP_CR3[SAMSEL] and GP01 Output

SAMSEL	Sampling Delay	GP01 Output
00	Sampling at both PWM ON and OFF modes without time delay	Constant high level
01	Sampling at PWM OFF, with time delay according to CMP_SAMR	Sampling at PWM OFF
10	Sampling at PWM ON, with time delay according to CMP_SAMR	Sampling at PWM ON
11	Sampling at both PWM ON and OFF, with time delay according to CMP_SAMR	Sampling at both PWM ON and OFF

Display comparator sampling, one of the signals of CMP0/1/2_OUT and the corresponding phase signal of phase-U/V/W output on the oscilloscope, adjust CMP_SAMR register to fall the comparator sampling

waveform within the PWM waveform and then observe whether CMP0/1/2_OUT meets the requirements.




Figure 15-15 Comparator Debugging

15.2.3.2 Debugging on Diode Freewheeling Masking and Phase Commutation

The reload timer RCNTR is used for freewheeling masking and delayed commutation, so SPI debugger can be used to display its waveform on the oscilloscope.

After the real-time status of Timer1 is displayed via GP01, waveforms of the freewheeling masking, ZCP and delayed commutation are obtained through phase-U/V/W commutation points.




Figure 15-16 RCNTR/GP01 Waveform at 15° Freewheeling Masking and 30° Delayed Commutation

15.3 Phase Commutation Signals by ADC

Formula K^*A-B , where K refers to coefficient, A to sampled voltage of active phase and B to sampled voltage of floating phase. When the symbol of the formula changes, phase commutation signal is generated.

Table 15-4 Relation between TIM1_DBR112/3/4/5/6/7[T1CPE] and K/A/B

CPE	Description
000	No sampling
001	$A = W, B = U, K = \text{TIM1_KR}$
010	$A = U, B = W, K = \text{TIM1_KF}$
011	$A = U, B = V, K = \text{TIM1_KR}$
100	$A = V, B = U, K = \text{TIM1_KF}$

CPE	Description
101	A = V, B = W, K = TIM1_KR
110	A = W, B = V, K = TIM1_KF
111	Reserved

Similar to the comparator, ADC can also samples the voltage at PWM ON/OFF. To reduce interference, filtering counts for ADC sampled voltage can be set as 2 or 4 by TIM1_CR3[T1AFL].

ADC has basically the same configurations for phase commutation as the comparator. But ADC has more flexible calculation formula, including different coefficients K, symbol flip with different position points, etc. For example, K=TIM1_KR=TIM1_KF=0.5, the symbol flip point is zcp.

15.4 Timer1 Registers

15.4.1 TIM1_CR0 (0x4068)

Bit	7	6	5	4	3	2	1	0	
Name	T1RWEN	T1CFLT		T1FORC	T1OPS		T1BCEN	T1RCEN	
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit	Name	Description							
[7]	T1RWEN	When TIM1_CR0 is updated, TIM1_CR0[T1RWEN] must be set to “1” to enable TIM1_CR0[T1RCEN]. This bit can be read to “0” only.							
[6:5]	T1CFLT	60 Degree Base Time Filtering Selection The average of previous x times 60 degree is used as the base time 00: 1 times 60 degree 01: 2 times 60 degree 10: 4 times 60 degree 11: 8 times 60 degree							
[4]	T1FORC	Forced Phase Commutation at 60° Enable If no ZCP is detected after phase commutation, the hardware implements forced phase commutation. But if a ZCP is detected, forced phase commutation will not be implemented even if TIM1_BCNTR exceeds TIM1_BARR. Note: If TIM1_CR0[T1FORC] = 0, TIM1_BCNTR continues (does not restart from “0”) and forced phase commutation will not be implemented even if TIM1_BCNTR exceeds TIM1_BARR. 0: Disable 1: Enable							
[3:2]	T1OPS	Data Transfer Mode Selection The bit selects the trigger signal for TIM1_DBRx to transfer data to DRV_CM, i.e., write timing even or phase commutation. 00: The transfer is triggered upon a write of “1” to TIM1_IER[T1UPD] in software or on a write to TIM1_CR4[T1CST] (sensorless square-wave control) 01: The transfer is triggered upon an overflow interrupt of 16-bit reload timer during phase commutation (sensorless square-wave control) 10: The transfer is triggered upon a Position Detected Interrupt (sensored square-wave control) or ADC calculation result 11: The transfer is triggered upon an overflow interrupt of 16-bit reload timer during phase commutation or ADC calculation result							
[1]	T1BCEN	Base Timer Enable 0: Disable 1: Enable							
[0]	T1RCEN	Reload Timer Enable							

		When TIM1_CR0 is updated, TIM1_CR0[T1RWEN] must be set to “1” to enable TIM1_CR0[T1RCEN]. TIM1_CR0[T1RCEN] is automatically enabled upon a Position Detected Interrupt and a Write Timing Interrupt. TIM1_CR0[T1RCEN] is cleared to “0” by hardware upon a Reload Timer Overflow Interrupt. 0: Disable 1: Enable
--	--	--

15.4.2 TIM1_CR1 (0x4069)

Bit	7	6	5	4	3	2	1	0
Name	T1BAPE				BSEL			
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	T1BAPE	TIM1__BARR Register Auto-load Enable With this bit enabled, TIM1__BCOR is written to TIM1__BARR when Basic Timer is reset due to a Position Detected Interrupt or a Write Timing Interrupt. It is used for forced phase commutation at 60°when no ZCP is detected. Setting the device in Manual mode has no effect on TIM1__BARR Register auto-load feature. 0: Disable 1: Enable						
[6:0]	BSEL	Diode Freewheeling Masking Angle Selection The bit is used to configure the angle (time) of diode freewheeling masking after phase commutation. Position is not detected during diode freewheeling masking. Equation: Diode freewheeling masking angle = TIM1_CR1[BSEL]/128*60° Note: This bit is invalid in Manual mode.						

15.4.3 TIM1_CR2 (0x406A)

Bit	7	6	5	4	3	2	1	0
Name	T1BRS				CSEL			
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	T1BRS	Base Timer Reset Source Select This bit is invalid in Manual mode (TIM1_IER[T1MAME] = 1). TIM1__BCNTR can only be cleared by a BCNTR Overflow Interrupt. 0: Write Timing Reset 1: Position Detected Interrupt Reset						
[6:0]	CSEL	Phase Commutation Angle Select After a position detected event, phase commutation is implemented after the degree configured by TIM1_CR2[CSEL]. Equation: Commutation angle = TIM1_CR2[CSEL]/128*60° Note: TIM1_CR2[CSEL] shall be set as “1” if the phase commutation angle is required at 0.						

15.4.4 TIM1_CR3 (0x406B)

Bit	7	6	5	4	3	2	1	0		
Name	T1AFL	T1PSC			T1TIS		T1INM			
Type	R/W	R/W		R/W	R/W		R/W	R/W		
Reset	0	0		0	0		0	0		
Bit	Name	Description								
[7]	T1AFL	ADC Sampled Voltage Calculation Filtering Counts 0: 4 1: 2								
[6:4]	T1PSC	Timer Clock Source Frequency Selection These bits are configured to divide the system clock as the clock source for Base Timer and Reload Timer. The clock source frequency of the two timers: 000: 24MHz 001: 12MHz 010: 6MHz 011: 3MHz 100: 1.5MHz 101: 750kHz 110: 375kHz 111: 187.5kHz								
[3:2]	T1TIS	Position Detection Signal Selection Timer1 filters, samples and generates a position detection on the selected input source. This bit affects CMP0/1/2_OUT and CMP0/1/2_IF results of the comparator module CMP_SR. 00: GPIO as the input (select P1.4/P1.6/P2.1 according to CMP_CR1[7]). The results of CMP_SR is generated through the GPIO. 01: Output signal of CMP0/CMP1/CMP2 as the input. The results of CMP_SR is generated through the comparator. 1x: Reserved								
[1:0]	T1INM	Noise Pulse Width Selection for TI0/TI1/TI2 When pulse width of the noise is less than the set value, it is filtered as noise. Assuming that MCU clock runs at 24MHz(41.67ns): 00: Disable 01: 8 system clock cycles, 8 x 41.67ns 10: 32 system clock cycles, 32 x 41.67ns 11: 64 system clock cycles, 64 x 41.67ns								

15.4.5 TIM1_CR4 (0x406C)

Bit	7	6	5	4	3	2	1	0
Name	RSV			T1CST				
Type	-	-	-	-	-	R/W	R/W	R/W
Reset	-	-	-	-	-	0	0	0
Bit	Name	Description						
[7:3]	RSV	Reserved						
[2:0]	T1CST	Commutation State Machine The state machine corresponds to different TIM1_DBRx at different states. When TIM1_CR4[T1CST] reads 001~111, Timer1 automatically enables or disables CMP0/1/2 according to the TIM1_DBRx[T1CPE]. When TIM1_CR4[T1CST] reads 001~110, Timer1 automatically adds by “1” each cycle upon a Write Timing Interrupt. Table 15-5 Mapping between TIM1_CR4[T1CST] and TIM1_DBRx						
		T1CST	TIM1_DBRx	T1CST	TIM1_DBRx			
		000	0	100	TIM1_DBR4			
		001	TIM1_DBR1	101	TIM1_DBR5			
		010	TIM1_DBR2	110	TIM1_DBR6			
		011	TIM1_DBR3	111	TIM1_DBR7			

15.4.6 TIM1_IER (0x406D)

Bit	7	6	5	4	3	2	1	0
Name	T1UPD	T1MAME	T1ADIE	T1BOIE	T1ROIE	T1WTIE	T1PDIE	T1BDIE
Type	W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	T1UPD	When TIM1_CR0[T1OPS] = 00, a write of “1” to this bit enables data transfer. This bit is Write only, and automatically cleared to “0” by hardware after “1” is written.						
[6]	T1MAME	Manual Mode Enable With this bit enabled, Basic Timer and Reload Timer acts as separate counters. Details: TIM1__BCNTR of the Basic Timer is cleared by a Base Timer Overflow Interrupt instead of TIM1_CR2[T1BRS] TIM1_CR0[T1RCEN] of the Reload Timer cannot be cleared to “0” or set to “1” automatically, and is controlled by software only. TIM1__RCNTR of the Reload Timer can be cleared to “0” upon a Reload Timer Overflow Interrupt only. TIM1__RARR of the Reload Timer cannot be updated automatically, and is controlled by software only. 0: Disable 1: Enable						
[5]	T1ADIE	ADC Position Detected Interrupt Enable 0: Disable 1: Enable						
[4]	T1BOIE	Base Timer Overflow Interrupt Enable 0: Disable 1: Enable						
[3]	T1ROIE	Reload Timer Overflow Interrupt Enable 0: Disable 1: Enable						
[2]	T1WTIE	Write Timing Interrupt Enable 0: Disable 1: Enable						
[1]	T1PDIE	Position Detected Interrupt Enable 0: Disable 1: Enable						
[0]	T1BDIE	Diode Freewheeling Masking Interrupt Enable 0: Disable 1: Enable						

15.4.7 TIM1_SR (0x406E)

Bit	7	6	5	4	3	2	1	0
Name	RSV		T1ADIF	T1BOIF	T1ROIF	T1WTIF	T1PDIF	T1BDIF
Type	-	-	R/W0	R/W0	R/W0	R/W0	R/W0	R/W0
Reset	-	-	0	0	0	0	0	0
Bit	Name	Description						
[7:6]	RSV	Reserved						
[5]	T1ADIF	ADC Position Detected Interrupt Flag This bit is set to “1” by hardware when a Position Detected Interrupt is generated. It is cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending						
[4]	T1BOIF	Base Timer Overflow Interrupt Flag An overflow event occurs when Basic Timer counts up and TIM1__BCNTR matches with TIM1__BARR. If TIM1_CR0[T1FORC] = 1, TIM1__BCNTR is cleared to “0”, otherwise, TIM1__BCNTR continues. This bit is set to “1” by hardware, and cleared						

		<p>to “0” by software.</p> <p>Note: If TIM1__BCNTR is to be cleared during an interrupt, UPD or TIM1_CR4 is written when TIM1_CR2[T1BRS] = 0.</p> <p>0: No Interrupt Pending 1: Interrupt Pending</p>
[3]	T1ROIF	<p>Reload Timer Overflow Interrupt Flag</p> <p>An overflow event occurs and TIM1__RCNTR is cleared to “0” when TIM1__RCNTR matches TIM1__RARR. This bit is set to “1” by hardware, and cleared to “0” by software.</p> <p>0: No Interrupt Pending 1: Interrupt Pending</p>
[2]	T1WTIF	<p>Writing Sequence Interrupt Flag</p> <p>Writing Sequence Interrupt is generated when TIM1_DBRH/TIM1_DBRL is transferred to TIM1_DRH/TIM1_DRL. This bit is set to “1” by hardware, and cleared to “0” by software.</p> <p>Note: When OPS = 00, a write of “1” to this bit generates a writing sequence interrupt.</p> <p>0: No Interrupt Pending 1: Interrupt Pending</p>
[1]	T1PDIF	<p>Position Detected Interrupt Flag</p> <p>A position detected interrupt is generated when Position Detection matches TIM1_DBRx[T1CPE]. This bit is set to “1” by hardware, and cleared to “0” by software.</p> <p>0: No Interrupt Pending 1: Interrupt Pending</p>
[0]	T1BDIF	<p>Diode Freewheeling Masking End Interrupt Flag</p> <p>Diode freewheeling masking starts after phase commutation. This bit is set to “1” by hardware, and cleared to “0” by software.</p> <p>0: No Interrupt Pending 1: Interrupt Pending</p>

15.4.8 TIM1_BCOR (0x4070, 0x4071)

TIM1_BCORH(0x4070)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_BCOR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1_BCORL(0x4071)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_BCOR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	TIM1_BCOR	<p>The bit is configured to capture filtered count values held in the Base Timer. TIM1_BCCR holds the filtered count value, i.e. 60 Degree Base Time.</p> <p>Note: TIM1_BCCR and TIM1_BCOR shall be initialized when the 60 Degree Base Time is initialized. For TIM1_BCCR, the 60 Degree Base Time can be directly written. For TIM1_BCOR, please note the followings:</p> <p>T1CFLT=00, 60 Degree Base Time; T1CFLT=01, 60 Degree Base Time /2; T1CFLT=10, 60 Degree Base Time /4; T1CFLT=11, 60 Degree Base Time /8.</p>						

15.4.9 TIM1_DBRx (x=1 ~ 7)(0x4074+2*x, 0x4075+2*x)

TIM1_DBRx(x=1~7) corresponds to the data when CST=1/2/3/4/5/6, respectively. TIM1_DBR1 is taken as an example to introduce TIM1_DBRx registers.

TIM1_DBR1H(0x4074)								
Bit	15	14	13	12	11	10	9	8
Name	RSV	T1CPE			T1WHP	T1WLP	T1VHP	T1VLP
Type	-	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	0	0	0	0	0	0	0
TIM1_DBR1L(0x4075)								
Bit	7	6	5	4	3	2	1	0
Name	T1UHP	T1ULP	T1WHE	T1WLE	T1VHE	T1VLE	T1UHE	T1ULE
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15]	RSV	Reserved						
[14:12]	T1CPE	TI0/TI1/TI2 Input Edge Polarity and Comparator Enable Select This bit is used to define the edge of Position Detection Input and enable or disable the associated comparators. The detected edge in input signal, corresponding to the configuration, generates a position detected interrupt. See section 15.1.2.1 and Table 15-2.						
[11]	T1WHP	High-side Output Polarity of W-phase 0: Active High 1: Active Low						
[10]	T1WLP	Low-side Output Polarity of W-phase 0: Active High 1: Active Low						
[9]	T1VHP	High-side Output Polarity of V-phase 0: Active High 1: Active Low						
[8]	T1VLP	Low-side Output Polarity of V-phase 0: Active High 1: Active Low						
[7]	T1UHP	High-side Output Polarity of U-phase 0: Active High 1: Active Low						
[6]	T1ULP	Low-side Output Polarity of U-phase 0: Active High 1: Active Low						
[5]	T1WHE	High-side Output Enable of W-phase 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-W are complementary and deadtime is automatically added when WLE and WHE are set to “1”.						
[4]	T1WLE	Low-side Output Enable of W-phase 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-W are complementary and deadtime is automatically added when WLE and WHE are set to “1”.						
[3]	T1VHE	High-side Output Enable of V-phase 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-V are complementary and deadtime is automatically added when VLE and VHE are set to “1”.						

[2]	T1VLE	Low-side Output Enable of V-phase 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-V are complementary and deadtime is automatically added when VLE and VHE are set to “1”.
[1]	T1UHE	High-side Output Enable of U-phase 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-U are complementary and deadtime is automatically added when ULE and UHE are set to “1”.
[0]	T1ULE	Low-side Output Enable of U-phase 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-U are complementary and deadtime is automatically added when ULE and UHE are set to “1”.

15.4.10 TIM1__BCNTR (0x4082, 0x4083)

TIM1__BCNTRH(0x4082)							
Bit	15	14	13	12	11	10	9
Name	TIM1__BCNTRH[15:8]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
TIM1__BCNTRL(0x4083)[7:0]							
Bit	7	6	5	4	3	2	1
Name	TIM1__BCNTRL						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
TIM1__BCNTR							
Bit	Name		Description				
[15:0]	TIM1__BCNTR		This bit holds count values of the Base Timer and is used for clocking commutation at 60°. Note: TIM1__BCNTR selects the reset source according to TIM1_CR2[T1BRS], and TIM1__BCNTR does not restart when TIM1__BCNTR overflow interrupt is generated.				

15.4.11 TIM1__BCCR (0x4084, 0x4085)

TIM1__BCCRH(0x4084)							
Bit	15	14	13	12	11	10	9
Name	TIM1__BCCR[15:8]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
TIM1__BCCRL(0x4085)							
Bit	7	6	5	4	3	2	1
Name	TIM1__BCCR[7:0]						
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
TIM1__BCCR							
Bit	Name		Description				
[15:0]	TIM1__BCCR		The bit is configured to capture count values held in Base Timer. When the Base Timer is reset on a Position Detected Interrupt or a Write Timing Interrupt, the count values before the reset are stored into TIM1__BCCR.				

15.4.12 TIM1__BARR (0x4086, 0x4087)

TIM1__BARRH(0x4086)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1__BARR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1__BARRL(0x4087)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1__BARR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1__BARR		Auto-Reload Value in Base Timer When the count value of the Base Timer equals to TIM1__BARR value, an overflow interrupt is generated and the counter is cleared to “0”.					

15.4.13 TIM1__RARR (0x4088, 0x4089)

TIM1__RARRH(0x4088)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1__RARR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1__RARRL(0x4089)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1__RARR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1__RARR		Auto-Reload Value in Reload Timer When count of the Reload Timer is equal to TIM1__RARR, an overflow interrupt is generated and the value of timer is cleared to “0”.					

15.4.14 TIM1__RCNTR (0x408A, 0x408B)

TIM1__RCNTRH(0x408A)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1__RCNTR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1__RCNTRL(0x408B)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1__RCNTR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1__RCNTR		Count value of the Reload Timer for diode freewheeling masking and ZCP to phase commutation.					

15.4.15 TIM1_ITRIP (0x4098, 0x4099)

TIM1_ITRIPH(0x4098)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_ITRIP[15:8]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
TIM1_ITRIPL(0x4099)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_ITRIP[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1_ITRIP		Filtered Bus Current The hardware automatically samples the bus current and filters it for software application. The default channel is ADC channel 4. Range (0,32767)					

15.4.16 TIM1_UCOP (0x408C, 0x408D)

TIM1_UCOPH(0x408C)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_UCOPH[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1_UCOPL(0x408D)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_UCOP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1_UCOP		Active Phase Voltage					

15.4.17 TIM1_UFLP (0x408E, 0x408F)

TIM1_UFLPH(0x408E)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_UFLP[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1_UFLPL(0x408F)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_UFLP[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1_UFLP		Floating Phase Voltage					

15.4.18 TIM1_URES (0x4090, 0x4091)

TIM1_URESH(0x4090)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_URES[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1_URESL(0x4091)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_URES[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1_URES		Voltage Calculation Result					

15.4.19 TIM1_UIGN (0x4092, 0x4093)

TIM1_UIGNH(0x4092)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_UIGN[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1_UIGNL(0x4093)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_UIGN[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1_UIGN		Ignored Voltage of Active Phase When the voltage of active phase is lower than TIM1_UIGN, the voltage is ignored.					

15.4.20 TIM1_KF (0x4094, 0x4095)

TIM1_KFH(0x4094)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_KF[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1_KFL(0x4095)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_KF[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1_KF		Coefficient of the falling edge					

15.4.21 TIM1_KR (0x4096, 0x4097)

TIM1_KRH(0x4096)								
Bit	15	14	13	12	11	10	9	8
Name	TIM1_KR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM1_KRL(0x4097)								
Bit	7	6	5	4	3	2	1	0
Name	TIM1_KR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:0]	TIM1_KR		Coefficient of the rising edge					

15.4.22 EXT0 (0x40f0)

Bit	7	6	5	4	3	2	1	0
Name	RSV		FAEN	MOEMD2	T1COM_MD	CMPXO_P11	TIM4_CT	EXT0_P11
Type	-	-	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	-	0	0	0	0	0	0
Bit	Name		Description					
[7:6]	RSV		Reserved					
[5]	FAEN		After this feature is enabled, CMP_SAMR is scaled up by 4 times. 0: Disable 1: Enable					
[4]	MOEMD2		10μs of MOE Cycle-by-cycle Current Limiting Enable (MOEMD must be configured as 1X) 0: Disable 1: Enable					
[3]	T1COM_MD		Freewheeling Masking by ADC in Square-wave Control Mode 0: Disable. Freewheeling masking is not implemented by ADC. 1: Enable. Freewheeling masking is implemented by ADC (TIM1_CR1[BSEL] ≥ 1).					
[2]	CMPXO_P11		Comparator Output Switching 0: P0.7 1: P1.1					
[1]	TIM4_CT		DBG Function Switching 0: Reserved 1: P0.6					
[0]	EXT0_P11		P11 INT0 Enable 0: Disable 1: Enable					

16 Timer2

16.1 Timer2 Instructions

Timer2 has the following five working modes:

- Output mode: PWM generation
- Input capture mode: Detect the duration of high and low level of input PWM
- Input counter mode: Detect input time of the set PWM wave numbers
- QEP & RSD mode: Quadrature Encoder Pulse & Rotating State Detection (tailwind/headwind detection) mode
- Step Mode: Detect rotation direction, position and speed of step motor.

Timer2 features:

- 3-bit programmable prescaler divides the system clock
- 16-bit up-counting Base Timer; Counting clock source serves as the output of prescaler
- 16-bit up/down-counting special timer for Input Counter Mode, QEP&RSD Mode and Step Mode, with external input signal selected as clock source.
- Input filter module
- Edge detection module
- PWM generation module
- Interrupt event

16.1.1 Prescaler

Prescaler divides the system clock frequency and generates clock source for Base Timer. 8 frequency division coefficients of prescaler are available and can be selected by TIM2_CR0[T2PSC]. Since this register has no buffer, the clock source frequency is updated immediately after TIM2_CR0[T2PSC] is written. Therefore, the frequency division coefficients shall be configured when Basic Timer is not working.

Clock source frequency formula:

$$f_{CK_CNT} = f_{CK_PSC}/T2PSC$$

when MCU clock rate is at 24MHz(41.67ns).

Table 16-1 Mapping between Clock Rate and TIM2_CR0[T2PSC]

TIM2_CR0[T2PSC]	Coefficient (Hexadecimal)	CLK(Hz)
000	0x01	24M
001	0x02	12M
010	0x04	6M
011	0x08	3M
100	0x10	1.5M
101	0x20	750k
110	0x40	375k
111	0x80	187.5k

16.1.2 Reading, Writing and Counting of TIM2__CNTR

When $\text{TIM2_CR1[T2CEN]} = 1$, TIM2_CNTR starts to count. The write operation to TIM2_CNTR directly changes the value of the register, so Base Timer shall be disabled before the write operation. When reading TIM2_CNTR , software reads the high-order bits first, and the hardware synchronously caches the low-order bits. When reading the low-order bits, the software reads the cached data.

16.1.3 Output Mode

When $\text{TIM2_CR0[T2OCM]} = 01$, Timer2 works in output mode.




Figure 16-1 Output Mode Block Diagram

The output mode generates output signals according to TIM2_CR0[T2OCM] and the comparison results from the comparator. Meanwhile, corresponding interrupts events are generated.

16.1.3.1 Reading and Writing of TIM2__ARR/TIM2__DR

In output mode, $\text{TIM2_ARR}/\text{TIM2_DR}$ contains preload registers and shadow registers. When the software writes $\text{TIM2_ARR}/\text{TIM2_DR}$ register, the data is saved in the preload register. When the overflow event TIM2_CR1[T2IF] is generated or the Base Timer stops working ($\text{TIM2_CR1[T2CEN]} = 0$), the set value is transferred to the shadow register.

$\text{TIM2_ARR}/\text{TIM2_DR}$ is a 16-bit register, which requires to write the high byte first and then the low byte. The hardware ensures that the data in the preload register is not transferred to the shadow register after the high byte is written or before the low byte is written.

16.1.3.2 High-/Low-level Output Mode

When $\text{TIM2_CR0[T2OCM]} = 0$, if $\text{TIM2_DR} = \text{TIM2_ARR}$, the output signal is always low. When $\text{TIM2_CR0[T2OCM]} = 1$, if $\text{TIM2_DR} = \text{TIM2_ARR}$, the output signal is always high.

The output signal is always high/low only when $\text{TIM2_DR} = \text{TIM2_ARR}$. Configuring $\text{TIM2_DR} = 0$ generates a pulse of one clock cycle.

16.1.3.3 PWM Generation

In PWM generation mode, TIM2_ARR determines PWM cycle, TIM2_DR determines duty cycle, and $\text{duty cycle} = \text{TIM2_DR}/\text{TIM2_ARR} * 100\%$. If $\text{TIM2_CR0[T2OCM]} = 0$, the low level is output when

`TIM2_CNTR` \leq `TIM2_DR`, and the high level is output when `TIM2_CNTR` $>$ `TIM2_DR`. If `TIM2_CR0[T2OCM]` = 1, the high level is output when `TIM2_CNTR` \leq `TIM2_DR`, and the low level is output when `TIM2_CNTR` $>$ `TIM2_DR`.

16.1.3.4 Interrupt Event

- When `TIM2_CNTR` = `TIM2_DR`, a compare match event is generated and the interrupt flag bit `TIM2_CR1[T2IR]` is set to “1”. The timer continues.
- When `TIM2_CNTR` = `TIM2_ARR`, an overflow event is generated, and the interrupt flag bit `TIM2_CR1[T2IF]` is set to “1”. The timer is cleared to “0” and then restarts.




Figure 16-2 Output Mode Waveform

16.1.4 Input Signal Filtering and Edge Detection




Figure 16-3 Block Diagram of Input Signal Filtering and Edge Detection

The input signal `TI` of Timer2 comes from `GP07` or `GP10`, set by `PH_SEL[T2SEL]`. The filter of input signal is optional. The edge detection module detects filtered input signals and records rising edge and falling edge for use by the next module.




Figure 16-4 Timing Diagram of Filter Module

The filtering circuit removes the input noise with a pulse width of 4 clock cycles. The filtering feature is enabled when TIM2_CR1[T2_FE] is set to “1”. The filtered signal is 4 clock cycles later than the signal before filtering.

16.1.5 Input Capture Mode

When TIM2_CR0[T2MOD] = 00, Timer2 works in input capture mode.




Figure 16-5 Schematic Diagram of Input Capture Mode

The input capture mode detects duty cycle and period of the PWM signal. When TIM2_CR0[T2CES] = 0, the time between two adjacent rising edges forms one cycle, and the time from rising edge to falling edge forms the pulse width (HIGH). When TIM2_CR0[T2CES] = 1, the time between two adjacent falling edges forms one cycle, and the time from falling edge to rising edge forms the pulse width (LOW). When the predefined edge arrives, the count value TIM2_CNTR is stored in TIM2_DR and TIM2_ARR respectively to calculate the period and duty cycle of PWM waveform. The filter of input signal is optional.




Figure 16-6 Timing Diagram of Input Capture Mode (TIM2_CR0[T2CES] = 0)

For example, when $\text{TIM2_CR0[T2CES]} = 0$, TIM2_CR1[T2CEN] is set to “1” to enable the Base Timer. When the first rising edge of the input (falling edge is invalid) is detected, TIM2_CNTR is cleared and restarts.

When falling edge of the input is detected, the value of TIM2_CNTR is stored in TIM2_DR , and the interrupt flag TIM2_CR1[T2IR] is set to “1”, and TIM2_CNTR continues to count.

When the second rising edge of input is detected, the value of TIM2_CNTR is stored in TIM2_ARR . Meanwhile, the interrupt flag TIM2_CR1[T2IP] is set to “1”, and TIM2_CNTR is cleared to “0” and restarts.

An overflow event occurs if Timer2 does not detect the second rising edge of the input and TIM2_CNTR reaches 0xFFFF. In this case, the interrupt flag TIM2_CR1[T2IF] is set to “1”, and TIM2_CNTR is cleared to “0” and restarts.

16.1.6 Input Counter Mode

When $\text{TIM2_CR0[T2MOD]} = 10$, Timer2 works in input counter mode.




Figure 16-7 Schematic Diagram of Input Counter Mode

In input counter mode, TIM2_DR includes preload register and shadow register. When the software

writes TIM2_DR register, the data is saved in the preload register first, and then sent to the shadow register in case of compare match event (TIM2_CR1[T2IP] = 1), overflow event (TIM2_CR1[T2IF] = 1) or timer disable (TIM2_CR1[T2CEN] = 0). TIM2_DR is a 16-bit register, which requires the software writes the high byte first and then the low byte. The hardware ensures that the data in the preload register is not updated to the shadow register after the high byte is written and before the low byte is written.

The input counter mode is used to detect the time to input the set PWM wave. In this mode, TIM2_CNTR of the Base Timer is stored in TIM2_ARR. The filter of input signal is optional. When TIM2_CR0[T2CES] is set to “1”, the rising edge of the input PWM signal serves as the active counting edge of the special timer; when TIM2_CR0[T2CES] is set to “0”, the falling edge of the input signal as the active edge.




Figure 16-8 Timing Diagram of Input Counter Mode

The Basic Timer is enabled when TIM2_CR1[T2CEN] is set to “1”. If the first active edge of the input signal is detected, TIM2_CNTR is cleared to “0” and restarts.

Whenever active edge of the input signal arrives, one is added to the count value of the special timer CCNTR. When the count value reaches TIM2_DR, TIM2_CNTR is stored in TIM2_ARR. When TIM2_CR1[T2IP] is set to “1”, TIM2_CNTR and CCNTR are cleared to “0” and restart.

When the number of input PWM does not reach the set value and TIM2_CNTR reaches 0xFFFF, an overflow event generates, and the interrupt flag TIM2_CR1[T2IF] is set to “1”. TIM2_CNTR is cleared to “0” with CCNTR uncleared. TIM2_CNTR starts counting from 0, and CCNTR continues counting with the previous value.

16.1.7 QEP&RSD Mode

When TIM2_CR0[T2MOD] = 11, Timer2 works in QEP & RSD mode.




Figure 16-9 Schematic Diagram of QEP&RSD Mode

QEP & RSD mode obtains relative position, direction and speed of the motor by detecting orthogonal signals on two channels. GP07 and GP10 (QEP mode. Two inputs generally differ in phase by 90 degrees) or CMP0 and CMP1 (RSD mode. Two inputs generally differ in phase by 60 degrees) are the input signal sources, which are sent to the quadrature decoding module from the filtering module to obtain active edge and direction (TIM2_CR1[T2DIR]). TIM2_CR1[T2IF] interrupt flag is generated when the direction changes.




Figure 16-10 Timing Diagram of QEP Mode

(Phase of Orthogonal Input in RSD Mode Different from That in QEP Mode)

The special timer is an up/down timer, and the signal source is the active edge from orthogonal decoding module. If TIM2_CR1[T2DIR] = 0, the direction is positive, and special timer counts upward. When the active edge arrives, the timer increases by one. If TIM2_CR1[T2DIR] = 1, the direction is reverse and special timer counts down. When the active edge arrives, the timer decreases by one. The special timer can be cleared by external interrupt INT1 and the value held by the timer is stored in TIM2_DR, after mechanical zero of the encoder is connected with any port of INT1, INT1 interrupt is enabled and TIM2_CR0[T2CES] = 1. If count value of the special timer reaches 65535 from 0, it is automatically cleared to “0”. If it decreases from

65535 to 0, it is automatically set to 65535. TIM2_CTR is read to obtain the value of special timer.

The Base Timer is an up counter, which uses the output of prescaler as the clock source to record the time between two active counting edges. When active counting edge arrives, the value of Basic Timer is stored in TIM2_ARR and then cleared to “0”, and TIM2_CR1[T2IP] interrupt flag bit is set to “1”. When Base Timer counts to 0xFFFF, the count overflows and (TIM2_CR1[T2IF]) interrupt flag is generated.

16.1.7.1 RSD Comparator Sampling




Figure 16-11 PWM ON Sampling Mode

There is a delay from the PWM output to the output of the comparator, which is mainly affected by the following factors: resistance value of drive resistor, MOS on-off speed, and input delay and hysteresis settings of the comparator. As shown above, the delaytime is from the chip output to the comparator output. When high-level sampling is performed, the sampling interval shall be enveloped by actual high-level output of the comparator. First, the sampling ON-delayed time CMP_SAMR[CSOND] is set to overcome output delay and oscillation due to MOS on/off. At the end of the sampling interval, CMP_SAMR[CSOND] is delayed after the falling edge of PWM, at which time the actual sampling window has exceeded the corresponding high-level interval (PWM of CMP). The sampling OFF-lead time CMP_SAMR[CSOFFD] is set to stop sampling Toffdelay after PWM output falling edge, where $T_{offdelay} = \text{CMP_SAMR[CSOND]} - \text{CMP_SAMR[CSOFFD]}$.




Figure 16-12 PWM OFF Sampling Mode

Similarly, when low-level sampling is performed, sampling ON-delayed time CMP_SAMR[CSOND] and sampling OFF-lead time CMP_SAMR[CSOFFD] are set reasonably to ensure that the actual sampling interval is located in the actually low-level output interval of the comparator.

Method for measuring the delay of PWM output to comparator: Set CMP_CR3[SAMSEL] = 00 to disable the comparator sampling delay feature. Set CMP_CR3[CMPSEL] to select the corresponding comparator output. Enable the PWM output and comparator, manually rotate the motor to change the comparator value, and measure the delay between the PWM output and the comparator output.

16.1.8 Step Mode




Figure 16-13 Step Mode Schematic Diagram

In step mode, relative position, direction and speed of the step motor are obtained by detecting inputs of the two channel. P1.0 is direction input, and P0.7 is pulse input. Setting TIM2_CR0[T2CES] to select the rising edge or falling edge as the active edge. The input signals are sent to decoding module from the filtering module to obtain the active edge and direction TIM2_CR1[T2DIR]. TIM2_CR1[T2IF] interrupt flag is generated when the direction changes. Note: TIM2_CR1[T2DIR] and TIM2_CR1[T2IR] will not change unless transition occurs at GP10 and active edge is detected at P0.7. To generate an interrupt immediately after P1.0 changes, use INT1.




Figure 16-14 Timing Diagram of Step Mode

The special timer is an up/down-counter, and the signal source is active edge of the encoding module. When P1.0 = 0 and TIM2_CR1[T2DIR] = 0, the direction is forward. If active edge of P0.7 arrives, the special timer increases by 1. When P1.0 = 1 and TIM2_CR1[T2DIR] = 1, the direction is reverse. If active edge of P0.7 arrives, the special timer decreases by 1. If count value of the special timer reaches 65535 from 0, it is automatically cleared to “0”. If it decreases from 65535 to 0, it is automatically set to 65535. TIM2_CTR is read to obtain the value of special timer.

The Base Timer is an up counter, which uses the output of prescaler as the clock source to record the time between two active counting edges. When active counting edge arrives, the value of Basic Timer is stored in TIM2_ARR and then cleared to “0”, and TIM2_CR1[T2IP] interrupt flag bit is set to “1”. When Base Timer counts to 0xFFFF, the count overflows and (TIM2_CR1[T2IF]) interrupt flag is generated.

16.2 Timer2 Registers

16.2.1 TIM2_CR0 (0xA1)

Bit	7	6	5	4	3	2	1	0
Name	T2PSC			T2OCM	T2IRE	T2CES	T2MOD	
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:5]	T2PSC	Base Timer Clock Prescaler Selection It is configured to divide the system clock frequency and generate the clock source for Base Timer. When MCU clock runs at 24MHz(41.67ns), the prescaled clock rates are configured as follows: 000:0x1 (24MHz) 001:0x2 (12MHz) 010:0x4 (6MHz) 011:0x8 (3MHz) 100:0x10 (1.5MHz) 101:0x20 (750kHz) 110:0x40 (375kHz) 111:0x80 (187.5kHz)						
[4]	T2OCM	Output Mode: Output Mode Selection 0: “0” is output when TIM2_CTR≤TIM2_DR; “1” is output when TIM2_CTR > TIM2_DR. 1: “1” is output when TIM2_CTR≤TIM2_DR; “0” is output when TIM2_CTR > TIM2_DR. Input Counter Mode: No effect Input Capture Mode: No effect QEP&RSD Mode and Step Mode Selection 0: QEP&RSD Mode 1: Step Mode						
[3]	T2IRE	Output Mode: Match Interrupt Enable Input Capture Mode: Pulse Width Detection Interrupt Enable Input Counter Mode: No effect QEP&RSD Mode and Step Mode: Direction Change Interrupt Enable 0: Disable 1: Enable						
[2]	T2CES	Input Capture Mode: Counting Edge Selection 0: The time between two adjacent raising edges forms one cycle, and the time from rising edge to falling edge forms the pulse width (HIGH). 1: The time between two adjacent falling edges forms one cycle, and the time from falling edge to raising edge forms the pulse width (LOW). Input Counter Mode and Step Mode: Active Edge Selection						

		0: Falling Edge Count 1: Raising Edge Count QEP&RSD Mode: Pulse Counter Cleared Enable upon Z Signal Interrupt INT1 0: Disable 1: Enable
[1:0]	T2MOD	Mode Selection 00: Input Capture Mode 01: Output Mode 10: Input Counter Mode 11: QEP&RSD Mode or Step Mode

16.2.2 TIM2_CR1 (0xA9)

Bit	7	6	5	4	3	2	1	0
Name	T2IR	T2IP	T2IF	T2IPE	T2IFE	T2FE	T2DIR	T2EN
Type	R/W0	R/W0	R/W0	R/W0	R/W	R/W	R	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	T2IR	Output Mode: Match Interrupt Flag The bit is set to “1” by the hardware when TIM2__CNTR matches TIM2__DR. It is cleared to “0” by software. Input Capture Mode: Pulse Width Detection Interrupt Flag This bit is set to “1” when an input pulse width is detected (Setting TIM2_CR0[T2CES] to select the rising edge or falling edge as the active edge). It is cleared to “0” by software. Input Counter Mode: No effect QEP&RSD Mode and Step Mode: Direction Change Flag Bit 0: No Interrupt Pending 1: Interrupt Pending						
[6]	T2IP	Output Mode: No effect Input Capture Mode: PWM Cycle Detection Interrupt Flag This bit is set to “1” when an input PWM cycle is detected (Setting TIM2_CR0[T2CES] to select the rising edge or falling edge as the active edge). It is cleared to “0” by software. Input Counter Mode: PWM Input Counter Match Interrupt Flag This bit is set to “1” by hardware when the number of input PWM reaches TIM2__DR. It is cleared to “0” by software. QEP&RSD Mode and Step Mode: Active Edge Detection Interrupt Flag This bit is set to “1” by hardware when the input edge is detected as an active edge. It is cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending						
[5]	T2IF	Output Mode: Timer Overflow Interrupt Flag. This bit is set to “1” and TIM2__CNTR is cleared to “0” when TIM2__CNTR matches TIM2__ARR. It is cleared to “0” by software. Input Capture Mode: Timer Overflow Interrupt Flag Setting TIM2_CR0[T2CES] to select the rising edge or falling edge as the active edge. This bit is set to “1” and TIM2__CNTR is cleared to “0” when the Timer has not detected an input PWM cycle but the timer TIM2__CNTR reaches 0xFFFF (overflow occurs). It is cleared to “0” by software. Input Counter Mode: Base Timer Overflow Interrupt Flag This bit is set to “1” and TIM2__CNTR is cleared to “0” when the input PWM cycle has not reached the preset TIM2__DR value but Base Timer TIM2__CNTR value reaches 0xFFFF (overflow occurs). It is cleared to “0” by software. QEP&RSD Mode and Step Mode: Base Timer Overflow Interrupt Flag This bit is set to “1” and Basic Timer is cleared to “0” when Basic Timer reaches to 0xFFFF (overflow occurs). It is cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending						

[4]	T2IPE	Output Mode: No effect Input Capture Mode: PWM Cycle Detection Interrupt Enable Input Counter Mode: PWM Input Counter Match Interrupt Enable QEP&RSD Mode and Step Mode: Active Edge Detection Interrupt Enable 0: Disable 1: Enable
[3]	T2IFE	Output Mode: Timer Overflow Interrupt Enable Input Capture Mode: Timer Overflow Interrupt Enable Input Counter Mode: Base Timer Overflow Interrupt Enable QEP&RSD Mode and Step Mode: Base Timer Overflow Interrupt Enable 0: Disable 1: Enable
[2]	T2FE	Input Signal Filter Selection When input signals are filtered out as noise if the pulse width is less than 4 clock cycle. Assuming that MCU clock runs at 24MHz (41.67ns), then the pulse width for filtering is 166.67ns. 0: Disable 1: Enable
[1]	T2DIR	QEP&RSD Mode and Steo Mode: Indicator of Motor Rotation Direction 0: Forward 1: Backward
[0]	T2EN	Timer Enable 0: Disable 1: Enable

16.2.3 PI_LPF_CR (0xF9)

Bit	7	6	5	4	3	2	1	0
Name	T2SS	RSV				PIRANGE	PISTA	LPFSTA
Type	R/W	-	-	-	-	R/W	R/W	R/W
Reset	0	-	-	-	-	0	0	0
Bit	Name	Description						
[7]	T2SS	Input Mode Selection of TIM2 Stepper Motor 0: P1.0 is direction input and P0.7 is pulse input 1: P1.0 is reverse pulse input and P0.7 is the forward pulse input						
[6:3]	RSV	Reserved						
[2:0]		See section 11.3.1.						

16.2.4 TIM2__CNTR (0xAA, 0xAB)

TIM2__CNTRH(0xAB)								
Bit	15	14	13	12	11	10	9	8
Name	TIM2__CNTR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM2__CNTRL(0xAA)								
Bit	7	6	5	4	3	2	1	0
Name	TIM2__CNTR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	TIM2__CNTR	Output Mode/Input Capture Mode/Input Counter Mode: Count values held in the Base Timer QEP&RSD Mode/Step Mode: Count values held in the special timer When TIM2__CNTR is 0xFFFF, this bit is automatically cleared to "0".						

16.2.5 TIM2_DR (0xAC, 0xAD)

TIM2_DRH(0xAD)								
Bit	15	14	13	12	11	10	9	8
Name	TIM2_DR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM2_DRL(0xAC)								
Bit	7	6	5	4	3	2	1	0
Name	TIM2_DR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	TIM2_DR	Output Mode: Compare match value (written by software) Input Capture Mode: Count value of the detected input pulse width based on TIM2_CR0[T2CES] (written by hardware) Input Counter Mode: PWM cycles to be counted (written by software) QEP&RSD: Value of the special timer when TIM2_CR0[T2CES] = 1 and INT1 (zero point) is detected. Step Mode: No effect						

16.2.6 STIM2_ARR (0xAE, 0xAF)

TIM2_ARRH(0xAF)								
Bit	15	14	13	12	11	10	9	8
Name	TIM2_ARR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM2_ARRL(0xAE)								
Bit	7	6	5	4	3	2	1	0
Name	TIM2_ARR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	TIM2_ARR	Output Mode: Overload value (written by software) Input Capture Mode: Count value of a PWM cycle (written by hardware) Input Counter Mode: Count value held in Base Timer when the input PWM count matches (written by hardware) QEP&RSD Mode and Step Mode: Count value held in Base Timer when the input signal is detected as an active edge (written by hardware)						

17 Timer3/Timer4 (Timer4 supports timing only and does not support input and output)

17.1 Timer3 Instructions

Timer3 support output and input modes:

- Output mode: Generate PWM waveform (single mode)
- Input capture mode: Detect the duration of high and low level of input PWM, which can be used to calculate PWM duty cycle

Timer3 includes:

- 3-bit programmable prescaler divides system clock as the clock source for Base Timer
- 16-bit up-counting Base Timer; The output of the prescaler serves as the counting clock source
- Input filtering module
- Edge detection Module
- Output module generates PWM signal and outputs single compare results
- Interrupt event

17.2 Timer4 Instructions

Timer4 includes:

- 3-bit programmable prescaler divides system clock as the clock source for Base Timer
- Interrupt event

17.2.1 Prescaler

Prescaler divides the system clock frequency and generates counter clock source for Base Timer. 8 frequency division coefficients of prescaler are available and can be selected by TIMx_CR0[TxPSC]. Since this register has no buffer, the clock source frequency is updated immediately after TIMx_CR0[TxPSC] is written. Therefore, the frequency division coefficients shall be configured when Basic Timer is not working.

The clock source frequency formula:

$$f_{CK_CNT} = f_{CK_PSC}/TxPSC$$

when MCU clock runs at 24MHz(41.67ns).

Table 17-1 Mapping between Clock Rate and TIMx_CR0[TxPSC]

TIMx_CR0[TxPSC]	Coefficient (Hexadecimal)	CLK(Hz)
000	0x01	24M
001	0x02	12M
010	0x04	6M
011	0x08	3M
100	0x10	1.5M
101	0x20	750K
110	0x40	375K
111	0x80	187.5K

Note: In Input Capture Mode of Timer3, the clock rate is 48MHz when TIM234_CTRL[0] is set to “1”.

17.2.2 Reading, Writing and Counting of TIMx_CNTR

TIMx_CNTR starts when TIMx_CR1[TxEN] = 1. The write operation to TIMx_CNTR directly changes the value of the register, so it is required to disable the timer before the write operation. When reading TIMx_CNTR, the software reads high-order bits first and then low-order bits, and the hardware caches the low-order bits simultaneously. When reading the low-order bits, the software reads the cached data.

17.2.3 Output Mode

When TIMx_CR0[TxMOD] = 1, Timer3 works in output mode.




Figure 17-1 Output Mode Block Diagram

The output mode generate output signals according to TIMx_CR0[TxOCM] and the comparison results from the comparator. Meanwhile, corresponding interrupts is generated.

17.2.3.1 High-/Low-level Output Mode

When TIMx_CR0[TxOCM] = 0 and TIMx_DR = TIMx_ARR, the output signals are always low.

When TIMx_CR0[TxOCM] = 1 and TIMx_DR = TIMx_ARR, the output signals are always high.

The output signal is always high/low only when TIMx_DR = TIMx_ARR. Configuring TIMx_DR = 0 generates a pulse of one clock cycle.

17.2.3.2 PWM Generation

In PWM generation mode, TIMx_ARR determines PWM cycle, and TIMx_DR determines the duty cycle, and duty cycle = $\text{TIMx_DR}/\text{TIMx_ARR} \times 100\%$. If TIMx_CR0[TxOCM] = 0, the low level is output when $\text{TIMx_CNTR} \leq \text{TIMx_DR}$, and the high level is output when $\text{TIMx_CNTR} > \text{TIMx_DR}$. If TIMx_CR0[TxOCM] = 1, the high level is output when $\text{TIMx_CNTR} \leq \text{TIMx_DR}$, and low level is output when $\text{TIMx_CNTR} > \text{TIMx_DR}$.

17.2.3.3 Interrupt Event

- When $\text{TIMx_CNTR} = \text{TIMx_DR}$, a compare match interrupt is generated. The interrupt flag TIMx_CR1[TxIR] is set to “1”, and the timer continues.
- When $\text{TIMx_CNTR} = \text{TIMx_ARR}$, an overflow event is generated. The interrupt flag TIMx_CR1[TxIF] is set to “1”, and the timer is cleared to “0”. TIMx_CR0[TxOPM] determines

whether the timer recounts. The timer stops when $\text{TIMx_CR0[TxOPM]}=1$, and restarts when $\text{TIMx_CR0[TxOPM]}=0$.




Figure 17-2 Output Waveform of Output Mode

17.2.4 Input Signal Filtering and Edge Detection




Figure 17-3 Block Diagram of Input Signal Filtering and Edge Detection

The input signal TI of Timer3 comes from P1.1/P0.1. The filter of input signal is optional. The edge detection module detects filtered input signals and records rising edge and falling edge for use by the next module.




Figure 17-4 4clk Timing Diagram of Filter Module

The filtering circuit removes the input noise with a pulse width of 4/8/16 clock cycles. The filtering feature is enabled when $\text{TIMx_CR1[TxFE]}=01/10/11$. The filtered signal is 4 ~ 5/8 ~ 9/16 ~ 17 clock cycles later than the signal before filtering.

17.2.5 Input Capture Mode

When $\text{TIMx_CR0[TxMOD]} = 0$, Timer3 works in input capture mode.




Figure 17-5 Schematic Diagram of Input Capture Mode

The Input Capture Mode detects pulse width and waveform period of the input PWM signals. When $\text{TIMx_CR0[TxOCM]} = 0$, the time between two adjacent rising edges forms one cycle, and the time from rising edge to falling edge forms the pulse width (HIGH). When $\text{TIMx_CR0[TxOCM]} = 1$, the time between two adjacent falling edges forms one cycle, and the time from falling edge to rising edge forms the pulse width (LOW). The pulse width and the period obtained by TIMx_CNTR are stored in TIMx_DR and TIMx_ARR respectively.




Figure 17-6 Timing Diagram of Input Capture Mode ($\text{TIMx_CR0[TxOCM]} = 0$)

For example, when $\text{TIMx_CR0[TxOCM]} = 0$, TIMx_CR1[TxEN] is set to “1” to enable the timer.

When the falling edge is detected, the value of TIMx_CNTR is stored into TIMx_DR . Meanwhile, the interrupt flag TIMx_CR1[TxIR] is set to “1”, and TIMx_CNTR continues to count.

When the second rising edge is detected, the value of TIMx_CNTR is saved into TIMx_ARR . The interrupt flag TIMx_CR1[TxIP] is set to “1” and TIMx_CNTR is cleared to “0”. TIMx_CR0[TxOPM] determines whether the timer restarts. If $\text{TIMx_CR0[TxOPM]} = 1$, the timer stops; and if $\text{TIMx_CR0[TxOPM]} = 0$, it restarts.

An overflow event occurs if Timer3/Timer4 does not detect the second rising edge of the input and TIMx_CNTR reaches 0xFFFF. In this case, the interrupt flag bit TIMx_CR1[TxIF] is set to “1”, and TIMx_CNTR is cleared to “0”. TIMx_CR0[TxOPM] determines whether the timer restarts. If TIMx_CR0[TxOCM]= 1, the timer stops counting, and if TIMx_CR0[TxOPM] = 0, it restarts.

17.3 Timer3/Timer4 Registers

17.3.1 TIMx_CR0 (0x9C/0x9E) (x=3/4)

Bit	7	6	5	4	3	2	1	0
Name	TxPSC			TxOCM	TxIRE	RSV	TxOPM	TxMOD
Type	R/W	R/W	R/W	R/W	R/W	R	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:5]	TxPSC	Base Timer Clock Prescaler Selection It is configured to divide the system clock frequency and generate the clock source for Base Timer. When MCU clock runs at 24MHz(41.67ns), the prescaled clock rates are configured as follows: 000:0x1(24MHz) 001:0x2(12MHz) 010:0x4(6MHz) 011:0x8(3MHz) 100:0x10(1.5MHz) 101:0x20(750kHz) 110:0x40(375kHz) 111:0x80(187.5kHz)						
[4]	TxOCM	Output Mode: Output Mode Selection 0: “0” is output when TIMx_CNTR≤TIMx_DR; “1” is output when TIMx_CNTR>TIMx_DR. 1: “1” is output when TIMx_CNTR≤TIMx_DR; “0” is output when TIMx_CNTR>TIMx_DR. Input Capture Mode: Active Edge Selection 0: The time between two adjacent raising edges forms one cycle, and the time from rising edge to falling edge forms the pulse width (HIGH). 1: The time between two adjacent falling edges forms one cycle, and the time from falling edge to raising edge forms the pulse width (LOW).						
[3]	TxIRE	Output Mode: Compare Match Interrupt Enable Input Capture Mode: Pulse Width Detection Interrupt Enable 0: Disable 1: Enable						
[2]	RSV	Reserved						
[1]	TxOPM	Single Mode The timer stops in any of the following events: Output Mode: Timer overflow event Input Capture Mode: PWM Cycle Detection or Timer Overflow Event 0: The Timer does not stop 1: The Timer stops (TIMx_CR1[TxEN] is reset to “0”)						
[0]	TxMOD	Working Mode Selection 0: Input Capture Mode 1: Output Mode						

17.3.2 TIM3_CR1 (0x9D/0x9F)

Bit	7	6	5	4	3	2	1	0
Name	TxIR	TxIP	TxIF	TxIDE	TxIFE	TxFE		TxEN
Type	R/W0	R/W0	R/W0	R/W0	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	TxIR	Output Mode: Match Interrupt Flag						

		The bit is set to “1” by the hardware when TIM3__CNTR matches TIM3__DR. It is cleared to “0” by software. Input Capture Mode: Pulse Width Detection Interrupt Flag This bit is set to “1” when an input pulse width is detected (Setting TIM3__CR0[T2CES] to select the rising edge or falling edge as the active edge). This bit is cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending
[6]	TxIP	Output Mode: No effect Input Capture Mode: PWM Cycle Detection Interrupt Flag This bit is set to “1” when an input PWM cycle is detected (Setting TIMx__CR0[T2CES] to select the rising edge or falling edge as the active edge). It is cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending
[5]	TxIF	Output Mode: Timer Overflow Interrupt Flag. This bit is set to “1” and TIMx__CNTR is cleared to “0” when TIMx__CNTR matches TIMx__ARR. It is cleared to “0” by software. Input Capture Mode: Timer Overflow Interrupt Flag This bit is set to “1” and TIMx__CNTR is cleared to “0” when the timer does not detect an input PWM cycle but the timer TIMx__CNTR reaches 0xFFFF (overflow occurs). It is cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending
[4]	TxIPE	Output Mode: No effect Input Capture Mode: PWM Cycle Detection Interrupt Enable 0: Disable 1: Enable
[3]	TxIFE	Output Mode: Timer Overflow Interrupt Input Capture Mode: Timer Overflow Interrupt Enable 0: Disable 1: Enable
[2:1]	TxFE	Input Signal Filtering Pulse Width Selection Input signals are filtered as noise if pulse width is less than the defined value. Assuming that MCU clock runs at 24MHz(41.67ns): 00: Disable 01: 4 system clock cycles, 4 x 41.67ns 10: 8 system clock cycles, 8 x 41.67ns 11: 16 system clock cycles, 16 x 41.67ns
[0]	TxEN	Base Timer Enable 0: Disable 1: Enable

17.3.3 TIM3__CNTR (0xA2,0xA3/0x92,0x93)

TIM3__CNTRH(0xA3/0x93)								
Bit	15	14	13	12	11	10	9	8
Name	TIM3__CNTR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM3__CNTRL(0xA2/0x92)								
Bit	7	6	5	4	3	2	1	0
Name	TIM3__CNTR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					

[15:0]	TIM3__CNTR	Count values held in the Base Timer When TIM3__CNTR reaches 0xFFFF, this bit is automatically cleared to "0".
--------	------------	--

17.3.4 TIM3__DR (0xA4,0xA5/0x94,0x95)

TIM3__DRH(0xA5/0x95)								
Bit	15	14	13	12	11	10	9	8
Name	TIM3__DR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM3__DRL(0xA4/0x94)								
Bit	7	6	5	4	3	2	1	0
Name	TIM3__DR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	TIM3__DR	Output Mode: Compare match values (written by software) Input Capture Mode: Count value of the detected input pulse width based on TIMx_CR0[TxOCM] (written by hardware)						

17.3.5 TIM3__ARR (0xA6,0xA7/0x96,0x97)

TIM3__ARRH(0xA7/0x97)								
Bit	15	14	13	12	11	10	9	8
Name	TIM3__ARR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
TIM3__ARRL(0xA6/0x96)								
Bit	7	6	5	4	3	2	1	0
Name	TIMx__ARR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	TIM3__ARR	Output Mode: Overload value (written by software) Input Capture Mode: Count value of a PWM cycle based on TIMx_CR0[TxOCM] (written by hardware)						

18 Systick

18.1 Systick Instructions

The chip can generate Systick interrupts at a fixed interval, and the interrupt cycle is controlled by SYST_ARR. Systick interrupt is enabled when DRV_SR[SYSTIE] is set to “1”, and the interrupts are accessed by P10 (multiplexed with TIM4 interrupt input).

18.2 Systick Registers

18.2.1 DRV_SR (0x4061)

Bit	7	6	5	4	3	2	1	0
Name	SYSTIF	SYSTIE	FGIF	DCIF	FGIE	DCIP	DCIM	
Type	R/W0	R/W	R/W0	R/W0	R	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	SYSTIF	Systick Interrupt Flag This bit is set to “1” by hardware, and cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending						
[6]	SYSTIE	Systick Interrupt Enable 0: Disable 1: Enable						
[5:0]		See section 19.2.2.						

18.2.2 SYST_ARR (0x4064,0x4065)

SYST_ARRH(0x4064)								
Bit	15	14	13	12	11	10	9	8
Name	SYST_ARR[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	1	0	1	1	1	0	1
SYST_ARRL(0x4065)								
Bit	7	6	5	4	3	2	1	0
Name	SYST_ARR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	1	0	1	1	1	1	1	1
Bit	Name	Description						
[15:0]	SYST_ARR	Systick Cycle This bit determines the cycle at which Systick interrupts are generated, which defaults to 1ms. Calculation formula is as follows: Systick rate = 24M/(SYST_ARR + 1) Range (0,65535)						

19 Driver

19.1 Driver Instructions

19.1.1 Driver Introduction




Figure 19-1 Block Diagram of ES9676AH Driver Module

FOC_CMPU/V/W is the three-way comparison value output by FOC module, and DRV_DR is the comparison value set by the software. The above comparison value outputs three sets of level signals U/V/W to HV Level Shifter(ES9676AH) after passing through the output control module. The U/V/W three-way output is applied to BLDC motor control.

DRVOE is the enable signal of HV Level Shifter, and the output of HV Level Shifter is connected with 6 NMOS to drive phase-U/V/W respectively.

Table 19-1 Input and Output of HV Level Shifter

Input		Output	
UH/VH/WH	UL/VL/WL	HU/HV/HW	LU/LV/LW
L	L	L	L
L	H	L	H
H	L	H	L
H	H	L	L

19.1.2 Output Control Module




Figure 19-2 Block Diagram of Output Control Module

Before Driver module works, `DRV_CR[MESEL]` is set to “1” to select FOC/SVPWM/SPWM mode or to “0” to select square-wave control mode.

When `DRV_CR[OCS] = 0`, comparison value of PWM comes from `DRV_DR`, and `OCTxH` serves as the reference for output PWM signal. If `OCxH` and `OCxL` are output at the same time, `OCTxL` is output in reverse phase. When `DRV_CR[OCS] = 1`, comparison value of PWM comes from FOC module, and `OCTxL` serves as the reference for output PWM signal. If `OCxH` and `OCxL` are output at the same time, `OCTxH` is output in reverse phase.

19.1.2.1 Count and Compare Module

`DRV_CR[OCS]` is configured to select the comparison value of PWM from `FOC_CMPU/V/W` of FOC module or `DRV_DR` set by software. The comparison value is sent to the counter for comparison to obtain a 4-way PWM signal `OCxREF`, and `DRV_DR` is used for motor pre-charging, braking and square-wave control. If `DRV__CNTR` is smaller than the comparison value, `OCxREF` outputs high-level signal, and if `DRV__CNTR` is larger than `DRV_DR`, `OCxREF` outputs low-level signal.

When `DRV_CR[OCS] = 1`, `FOC_CMPU/V/W` is compared with the count value to generate the duty cycle `OC1REF/OC2REF/OC3REF`.




Figure 19-3 PMW Generation

When $\text{DRV_CR}[\text{OCS}] = 0$, DRV_DR set by software is compared with the count value to generate $\text{OC1REF}/\text{OC2REF}/\text{OC3REF}$ with the same duty cycle.

Duty cycle = $\text{DRV_DR}/\text{DRV_ARR} \times 100\%$ (For example, if $\text{DRV_ARR}=750$ and $\text{DRV_DR} = 375$, then duty cycle = 50%)

19.1.2.2 Deadtime Module

OCxREF supports deadtime insertion. For complementary outputs, the deadtime insertion is enabled when DRV_DTR is not “0”. Each channel has an 8-bit deadtime generator, and four channels have the same deadtime, which is set by DRV_DTR . When rising edge signals are detected, output high level of OCxL is delayed for a period of time set in DRV_DTR . When falling edge signals are detected, output high level of OcxH is delayed for a period of time set in DRV_DTR .




Figure 19-4 Complementary Outputs with Deadtime Insertion

19.1.2.3 Enable and Polarity of Output Signals

$\text{DRV_CMR}[\text{xHE}]$ and $\text{DRV_CMR}[\text{xLE}]$ are configured by software to enable high and low sides of the bridge, and $\text{DRV_CMR}[\text{xHP}]$ and $[\text{xLP}]$ to select the polarity of output. For square-wave control, Timer1 automatically controls DRV_CMR to implement phase commutation. Configuring $\text{DRV_CR}[\text{MESEL}] = 0$

enables the Square Wave Drive Mode. After Timer1 generates a phase commutation event, the data stored in the corresponding TIM1_DBRx are transferred to DRV_CMRA and CMP_CR2[4:3].




Figure 19-5 Timer1 Automatic Control of DRV_CMRA and CMP_CR2[4:3]

With DRV_DR and DRV_ARR registers, DRV_CMRA[xHE] and DRV_CMRA[xLE] can be configured to implement pre-charging brake, etc. DRV_DR and DRV_ARR control the duty cycle and DRV_CMRA[xHE] and DRV_CMRA[xLE] control six outputs.




Figure 19-6 Pre-charge Waveform




Figure 19-7 Brake Waveform

19.1.2.4 Main Output Enable (MOE)




Figure 19-8 Block Diagram of Output Control Module

When `DRV_OUT[MOE]` is enabled, MOE module uses comparison value of the counter for motor control. When `DRV_OUT[MOE]` is disabled, the module outputs idle level set by the software to keep the motor at shutdown state.

19.1.2.5 Interrupt

19.1.2.5.1 Compare Match Interrupt

The generation conditions and time for compare match interrupt are configured by `DRV_SR[DCIM]` and `DRV_COMR` respectively. When the timer reaches the value set in `DRV_COMR` and the conditions set by `DRV_SR[DCIM]` are met, a compare match interrupt is generated and the interrupt flag `DRV_SR[DCIF]`

is set to “1” by hardware. A write of “0” to DRV_SR[DCIF] by software clears the interrupt flag, and a write of “1” has no effect.




Figure 19-9 Driver Compare Match Interrupt

19.1.2.5.2 FG Interrupt

FG interrupt is enabled when DRV_SR[FGIE] is set to “1”. The motor generates an interrupt for every electrical cycle. After an interrupt event is generated, the interrupt flag is cleared to “0” by software.

19.2 Driver Registers

19.2.1 DRV_CR (0x4062)

Bit	7	6	5	4	3	2	1	0
Name	DRVEN	DDIR	FOCEN	DRPE	OCS	MESEL	RSV	DRV OE
Type	R/W	R/W	R/W	R/W	R/W	R/W	-	R/W
Reset	0	0	0	0	0	0	-	0
<hr/>								
Bit	Name	Description						
[7]	DRVEN	Counter Enable 0: Disable 1: Enable						
[6]	DDIR	Output Direction (Forward/Reverse) This bit controls motor rotation directions and is valid in both square-wave drive and FOC drive modes. In sensorless FOC mode, setting this bit changes motor rotation. In Hall-sensored FOC mode, it is also required to modify the angle by the software. In square-wave control mode, parameters related to Timer1 shall be configured. 0: Forward 1: Reverse						
[5]	FOCEN	FOC Module Enable 0: Disable 1: Enable						
[4]	DRPE	DRV_DR Pre-load Enable When preload is enabled, the data written to DRV_DR is updated after a timer underflow event occurs. When preload is disabled, the data written to DRV_DR is updated immediately. 0: Disable 1: Enable						
[3]	OCS	Comparison Source Selection 0: DRV_DR 1: FOC Module						
[2]	MESEL	ME Operating Mode Selection 0: Square Wave Drive 1: FOC Drive						
[1]	RSV	Reserved						
[0]	DRV OE	Driver Enable 0: Disable 1: Enable						

19.2.2 DRV_SR (0x4061)

Bit	7	6	5	4	3	2	1	0
Name	SYSTIF	SYSTIE	FGIF	DCIF	FGIE	DCIP	DCIM	
Type	R/W0	R/W	R/W0	R/W0	R	R/W	R/W	R/W0
Reset	0	0	0	0	0	0	0	0
<hr/>								
Bit	Name	Description						
[7]	SYSTIF	SYS TICK Interrupt Flag This bit is set to “1” by hardware, and cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending						
[6]	SYSTIE	SYS TICK Interrupt Enable 0: Disable 1: Enable						
[5]	FGIF	FG Interrupt Flag FG interrupt is enabled when DRV_SR[FGIE] is set to “1”.						

		The interrupt flag is generated in every electrical cycle under FOC/square-wave control mode. This bit is set to “1” by hardware, and cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending
[4]	DCIF	Driver Match Interrupt Flag When the Driver count value is equal to DRV_COMR, the system decides whether to generate an interrupt according to DRV_SR[DCIM]. This bit is set to “1” by hardware, and cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending
[3]	FGIE	FG Interrupt Enable After the interrupt feature is enabled, an FG Interrupt is generated in each electrical cycle under FOC/square-wave control mode. 0: Disable 1: Enable
[2]	DCIP	Number of PWM cycles to generate an interrupt 0: 1 PWM cycle 1: 2 PWM cycles
[1:0]	DCIM	DRV Compare Match Interrupt Mode Selection When the Driver count value is equal to DRV_COMR, the system decides whether to generate an interrupt according to DRV_SR[DCIM]. 00: No interrupt is generated. 01: An interrupt is generated when the timer counts up. 10: An interrupt is generated when the timer counts down. 11: An interrupt is generated when the timer counts up/down.

19.2.3 DRV_OUT (0xF8)

Bit	7	6	5	4	3	2	1	0
Name	MOE	RSV	OISWXL	OISWXH	OISVL	OISVH	OISUL	OISUH
Type	R/W	-	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	-	0	0	0	0	0	0

Bit	Name	Description
[7]	MOE	Main Output Enable This bit selects the sources for high and low sides of the bridge of phase-U/V/W/X output signals. It can be set to “1” and “0” by software. When bus current protection occurs, it is automatically cleared to “0” to turn off the output (see section 29.1.1.1). 0: Disable, with output sourced from the idle levels set by DRV_OUT[OISUH]/DRV_OUT[OISVH]/DRV_OUT[OISWH] and DRV_OUT[OISUL]/DRV_OUT[OISVL]/DRV_OUT[OISWL]. 1: Enable, with output sourced from the comparison value of the timer.
[6]	RSV	Reserved
[5]	OISWXL	Output idle level of WL/XL See descriptions on OISUH register
[4]	OISWXH	Output idle level of WH/XH See descriptions on OISUH register
[3]	OISVL	Output idle level of VL See descriptions on OISUH register
[2]	OISVH	Output idle level of VH See descriptions on OISUH register
[1]	OISUL	Output idle level of UL See descriptions on OISUH register
[0]	OISUH	Output idle level of UH This bit sets the UH output in idle state. When DRV_OUT[MOE] = 0, it outputs idle level to disable MOS. 0: Low 1: High

19.2.4 DRV_CMRL (0x405C, 0x405D)

Note: For square-wave control, Timer1 automatically controls DRV_CMRL register.

DRV_CMRL(0x405D)							
Bit	15	14	13	12	11	10	9
Name	XHP	XLP	XHE	XLE	WHP	WLP	VHP
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
DRV_CMRRH(0x405C)							
Bit	7	6	5	4	3	2	1
Name	UHP	ULP	WHE	WLE	VHE	VLE	UHE
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0
Bit	Name	Description					
[15]	XHP	High-side Polarity Control of phase-X 0: Active High 1: Active Low					
[14]	XLP	Low-side Polarity Control of phase-X 0: Active High 1: Active Low					
[13]	XHE	High-side Output of phase-X Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-X are complementary and deadtime is automatically added when XLE and XHE are set to “1”. Low-side output is the reference polarity.					
[12]	XLE	Low-side Output of phase-X Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-X are complementary and deadtime is automatically added when XLE and XHE are set to “1”. Low-side output is the reference polarity.					
[11]	WHP	High-side Polarity Control of W-phase 0: Active High 1: Active Low					
[10]	WLP	Low-side Polarity Control of W-phase 0: Active High 1: Active Low					
[9]	VHP	High-side Polarity Control of V-phase 0: Active High 1: Active Low					
[8]	VLP	Low-side Polarity Control of V-phase 0: Active High 1: Active Low					
[7]	UHP	High-side Polarity Control of U-phase 0: Active High 1: Active Low					
[6]	ULP	Low-side Polarity Control of U-phase 0: Active High 1: Active Low					
[5]	WHE	High-side Output of phase-W Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-W are complementary and deadtime is automatically added when WLE and WHE are set to “1”. Low-side output is the reference polarity.					

[4]	WLE	Low-side Output of phase-W Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-W are complementary and deadtime is automatically added when WLE and WHE are set to “1”. Low-side output is the reference polarity.
[3]	VHE	High-side Output of phase-V Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-V are complementary and deadtime is automatically added when VLE and VHE are set to “1”. Low-side output is the reference polarity.
[2]	VLE	Low-side Output of phase-V Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-V are complementary and deadtime is automatically added when VLE and VHE are set to “1”. Low-side output is the reference polarity.
[1]	UHE	High-side Output of phase-U Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-U are complementary and deadtime is automatically added when ULE and UHE are set to “1”. Low-side output is the reference polarity.
[0]	ULE	Low-side Output of phase-U Enable 0: Disable 1: Enable Note: The high-side and low-side outputs of phase-U are complementary and deadtime is automatically added when ULE and UHE are set to “1”. Low-side output is the reference polarity.

19.2.5 DRV_ARR (0x405E, 0x405F)

DRV_ARR(0x405E)								
Bit	15	14	13	12	11	10	9	8
Name	DRV_ARR[15:8]							
Type	R	R	R	R	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	7	6	5	4	3	2	1	0
Name	DRV_ARR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:0]	DRV_ARR	Timer reload value, which determines PWM frequency (center-aligned) Driver timer up-counts from 0 to DRV_ARR and an overflow event occurs. Then it down-counts to 0. Calculation formula: $f_{carrier} = f_{mcu}/2/(DRV_ARR)$ Range (0,4095)						

19.2.6 DRV_COMR (0x405A, 0x405B)

DRV_COMRH(0x405A)								
Bit	15	14	13	12	11	10	9	8
Name	DRV_COMR[15:8]							
Type	R	R	R	R	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

DRV_COMRL(0x405B)								
Bit	7	6	5	4	3	2	1	0
Name	DRV_COMR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	DRV_COMR	<p>Timer Compare Match Value</p> <p>The compare match interrupt is generated when the count value is equal to DRV_COMR and the conditions set in DRV_SR[DCIM] are met.</p> <p>Range (0, 4095)</p>

19.2.7 DRV_DR (0x4058, 0x4059)

DRV_DRH(0x4058)								
Bit	15	14	13	12	11	10	9	8
Name	DRV_DR[15:8]							
Type	R	R	R	R	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DRV_DRL(0x4059)								
Bit	7	6	5	4	3	2	1	0
Name	DRV_DR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[15:0]	DRV_DR	<p>PWM Duty Cycle Setting in Software</p> <p>When DRV_CR[OCS] = 0, DRV_CNTR is compared with DRV_DR to output PWM. “1” is output when DRV_CNTR is smaller than DRV_DR, and “0” is output when DRV_CNTR is larger than DRV_DR.</p> <p>Note: When this register is used as a comparison source, PWM is referenced to high side of the bridge and a deadtime is inserted in the complementary output of the low side of bridge.</p> <p>Range (0, 4095)</p>

19.2.8 DRV_DTR (0x4060)

Bit	7	6	5	4	3	2	1	0
Name	DRV_DTR							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0

Bit	Name	Description
[7:0]	DRV_DTR	<p>Deadtime Setting</p> <p>This bit controls deadtime duration between complementary outputs.</p> <p>Assuming that MCU clock runs at 24MHz(41.67ns), DT = (DTR+1) x 41.67ns.</p> <p>Note: When DRV_DTR = 0, deadtime insertion is disabled.</p>

20 WDT

The watchdog timer (WDT) is a timer that works on the internal slow clock (LS_OSC) to monitor the master program operation and prevent the MCU running out. Watchdog works as follows: After watchdog operates, WDT starts counting. When WDT overflows, watchdog sends a signal to reset the MCU and the program restarts running from address 0. During the operation of master program, WDT has to be initialized at regular intervals to prevent WDT overflowing.

After being enabled, WDT starts counting from 0. When it reaches 0xFFFF, watchdog outputs a signal that is 4 internal slow clock cycles wide to reset MCU, and the program starts running from address 0. WDT has to be initialized at regular intervals during operation, and cannot reset the MCU.

20.1 WDT Notes

- When MCU enters standby or sleep mode, WDT stops counting, but the count values are retained.
- WDT is automatically disabled during emulation.
- RST_SR[RSTWDT] is set to “1” when MCU is reset by WDT timer overflow.

20.2 WDT Operations

1. Set CCFG1[WDT_EN] = 1 to start WDT, which then starts counting from 0;
2. Set WDT_REL (this operation can also be performed before starting WDT);
3. Set WDT_CR[WDTRF] = 1 in the running of program to initialize WDT.

20.3 WDT Registers

20.3.1 WDT_CR (0x4026)

Bit	7	6	5	4	3	2	1	0	
Name	RSV								WDTRF
Type	-	-	-	-	-	-	-	R/W	
Reset	-	-	-	-	-	-	-	0	
Bit									
[7:1]	Name	Description							
[7:1]	RSV	Reserved							
[0]	WDTRF	0: No effect 1: WDT is initialized.							

20.3.2 WDT_REL (0x4027)

Bit	7	6	5	4	3	2	1	0
Name	WDT_REL							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	WDT_REL	This bit sets 8 high-order bits of WDT after initialization.						

21 RTC and Clock Calibration

21.1 RTC Functional Block Diagram




Figure 21-1 RTC Functional Block Diagram

21.2 RTC Operations

A write to RTC_TMH and RTC_TML sets RTC reload value.

RTC is enabled when RTC_STA[RTC_EN] is set to “1”.

21.3 RTC Registers

21.3.1 RTC_TM (0x402c, 0x402d)

RTC_TM(0x402C)								
Bit	15	14	13	12	11	10	9	8
Name	RTC0TM[15:8]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	1	1	1	1	1	1	1	1
RTC_TML(0x402D)								
Bit	7	6	5	4	3	2	1	0
Name	RTC0TM[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	1	1	1	1	1	1	1	1
Bit	Name	Description						
[15:0]	RTC_TM	RTC Count Register Write: RTC timer up-counts at a rate of 32768Hz from 0 to RTC_TM[15:0] and becomes overflowed. Meanwhile, an interrupt request is generated, causing the timer to be cleared and restart counting. Read: Instantaneous value of the timer						

21.3.2 RTC_STA (0x402e)

RTC_STA(0x402E)									
Bit	7	6	5	4	3	2	1	0	
Name	RTC_EN	RTCIF	ISOSCSEL	ISOSCEN	RSV				
Type	R/W	R/W	R/W	R/W	-	-	-	-	
Reset	0	0	0	0	-	-	-	-	
Bit	Name	Description							
7	RTC_EN	RTC Enable 0: Disable 1: Enable							
6	RTCIF	RTC Interrupt Flag When IE[RTCIE] is “1”, an interrupt event is generated after this bit get overflowed. This bit is cleared to “0” by software. When IE[RTCIE] is “0”, an interrupt flag, instead of an interrupt event, is generated after this bit get overflowed. MCU can read and clear the flag.							
5	ISOSCSEL	External Source for Clock Calibration 0: Internal Slow Clock 1: P11 Input							
4	ISOSCEN	Internal Slow Clock Enable 0: Disable 1: Enable							
[3:0]	RSV	Reserved							

21.4 Clock Calibration

21.4.1 Introduction

Clock calibration is a feature that uses internal slow clock to calibrate the internal fast clock. Register ISOSCSEL controls the slow clock source, internal slow clock or external clock input. Working principles: A 13-bit timer is used to count the length of 8 slow clock cycles with the fast clock as the clock source.

Calibration operations: Set CAL_CR0[CAL_STA] = 1 in software to start the calibration. Read CAL_CR0[CAL_BUSY] flag bit to check if the calibration process is completed. When the calibration is completed (CAL_CR0[CAL_BUSY] = 0), the readout of CAL_CR0[CAL_ARR] is the value of the length of counting 8 slow clock cycles.

21.4.2 Clock Calibration Register

21.4.2.1 CAL_CR (0x4044, 0X4045)

CAL_CR0, CAL_CR1(0x4040, 0x4041)								
CAL_CR0(0x4040)								
Bit	15	14	13	12	11	10	9	8
Name	CAL_STA/ CAL_BUSY	RSV		CAL_ARR[12:8]				
Type	R/W	-	-	R	R/W	R/W	R/W	R/W
Reset	1	-	-	0	0	0	0	0
CAL_CR1(0x4041)								
Bit	7	6	5	4	3	2	1	0
Name	CAL_ARR[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15]	CAL_STA/ CAL_BUSY	Clock Calibration Enable Read: 0: Calibration is completed. 1: Calibration is in progress. Write: 0: No effect 1: Clock Calibration starts.						
[14:13]	RSV	Reserved						
[12:0]	CAL_ARR	Calibration Counts The count values of the fast clock to continuously count eight slow clock cycles When this value is 0, it indicates that no corresponding slow clock input exists, and when this value is 0xFFFF, it indicates that the count overflows (slow clock is too slow or fast clock is too fast).						

22 IO

22.1 IO Introduction

ES9676AH has up to 18 GPIO pins, including P0.5 ~ P0.7, P1.0 ~ P1.6, P2.1, P2.4, P2.6 ~ P2.7, P3.0 ~ P3.2 and P3.4 ~ P3.5. Among them, P0.7 and P1.0 share the same pin.

22.2 IO Operations

Each GPIO port pin has relevant configuration registers to meet different application requirements. For example, P0.0 is mapped to register P0, and P1.0 to register P1. P0_OE and P1_OE registers are configured for digital input and output.

Notes:

- The enable bits of pull-up resistors and pull-down resistors are configured to “1”. See 22.3.8 P0_PU (0x4053 ~ 22.3.11 P3_PU (0x4056) for port pins and registers.
- See 5.4 GPIO Electrical Characteristics for the values of pull-up resistors and pull-down resistors.
- Pull-up resistors of P1.3 ~ P1.6 and P2.1 are automatically disabled when the port pins are configured as analog mode.
- The relevant bits of P1_AN, P2_AN and P3_AN registers are configured to “1”. See 22.3.5 P1_AN (0x4050) ~ 22.3.7 P3_AN (0x4052) for port pins and registers. After the port pins are configured to analog mode, all their digital features are disabled and the port state is 0 by reading relevant bits in P1, P2 and P3 registers.
- IO Priority:
 - GPIO has the lowest priority
 - P0.5: SPI > UART > GPIO
 - P0.6: SPI > UART > GPIO
 - P0.7: TIMER2 > CMP > SPI >GPIO

22.3 IO Registers

22.3.1 P0_OE (0xFC)

Bit	7	6	5	4	3	2	1	0
Name	P0_OE			RSV				
Type	R/W	R/W	R/W	-	-	-	-	-
Reset	0	0	0	-	-	-	-	-

Bit	Name	Description
[7:5]	P0_OE	P0.7 ~ P0.5 Digital I/O Selection 0: Input 1: Output
[4:0]	RSV	Reserved

22.3.2 P1_OE (0xFD)

Bit	7	6	5	4	3	2	1	0
Name	RSV	P1_OE						
Type	-	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	0	0	0	0	0	0	0

Bit	Name	Description
[7]	RSV	Reserved
[6:0]	P1_OE	P1.6 ~ P1.0 Digital I/O Selection 0: Input 1: Output

22.3.3 P2_OE (0xFE)

Bit	7	6	5	4	3	2	1	0
Name	P2_OE		RSV	P2_OE	RSV		P2_OE	RSV
Type	R/W	R/W	-	R/W	-	-	R/W	-
Reset	0	0	-	0	-	-	0	-

Bit	Name	Description
[7:6]	P2_OE	P2.7 ~ P2.6 Digital I/O Selection 0: Input 1: Output
[5]	RSV	Reserved
[4]	P2_OE	P2.4 Digital I/O Selection 0: Input 1: Output
[3:2]	RSV	Reserved
[1]	P2_OE	P2.1 Digital I/O Selection 0: Input 1: Output
[0]	RSV	Reserved

22.3.4 P3_OE (0xFF)

Bit	7	6	5	4	3	2	1	0
Name	RSV		P3_OE		RSV	P3_OE		
Type	-	-	R/W	R/W	-	R/W	R/W	R/W
Reset	-	-	0	0	-	0	0	0
Bit Name Description								
[7:6]	RSV	Reserved						
[5:4]	P3_OE	P3.5 ~ P3.4 Digital I/O Selection 0: Input 1: Output						
[3]	RSV	Reserved						
[2:0]	P3_OE	P3.2 ~ P3.0 Digital I/O Selection 0: Input 1: Output						

22.3.5 P1_AN (0x4050)

Bit	7	6	5	4	3	2	1	0															
Name	RSV	P1_AN			HBMOD	RSV																	
Type	-	R/W	R/W	R/W	R/W	-	-	-															
Reset	-	0	0	0	0	-	-	-															
Bit Name Description																							
[7]	RSV	Reserved																					
[6:4]	P1_AN	P1.6 ~ P1.4 Analog Mode Enable 0: Disable 1: Enable																					
[3]	HBMOD	P1.3 mode configuration, which determines the functional mode of P1.3 in combination with P1_OE.3. <table border="1"><thead><tr><th>HBMODE</th><th>P1_OE.3</th><th>P1.3 Pin Mode</th></tr></thead><tbody><tr><td>0</td><td>0</td><td>Digital Input (DI)</td></tr><tr><td>0</td><td>1</td><td>Digital Output (DO)</td></tr><tr><td>1</td><td>0</td><td>Analog Input (AI)</td></tr><tr><td></td><td>1</td><td>Digital enhanced drive output mode. The drive mode of high level output provides enhanced drive, and the drive mode of low level output is the same as that of the digital output mode “01”.</td></tr></tbody></table>							HBMODE	P1_OE.3	P1.3 Pin Mode	0	0	Digital Input (DI)	0	1	Digital Output (DO)	1	0	Analog Input (AI)		1	Digital enhanced drive output mode. The drive mode of high level output provides enhanced drive, and the drive mode of low level output is the same as that of the digital output mode “01”.
HBMODE	P1_OE.3	P1.3 Pin Mode																					
0	0	Digital Input (DI)																					
0	1	Digital Output (DO)																					
1	0	Analog Input (AI)																					
	1	Digital enhanced drive output mode. The drive mode of high level output provides enhanced drive, and the drive mode of low level output is the same as that of the digital output mode “01”.																					
[2:0]	RSV	Reserved																					

22.3.6 P2_AN (0x4051)

Bit	7	6	5	4	3	2	1	0
Name	P2_AN		RSV	P2_AN	RSV		P2_AN	RSV
Type	R/W	R/W	-	R/W	-	-	R/W	-
Reset	0	0	-	0	-	-	0	-
Bit Name Description								
[7:6]	P2_AN	P2.7 ~ P2.6 Analog Mode Enable 0: Disable 1: Enable						
[5]	RSV	Reserved						
[4]	P2_AN	P2.4 Analog Mode Enable 0: Disable 1: Enable						

[3: 2]	RSV	Reserved
[1]	P2_AN	P2.1 Analog Mode Enable 0: Disable 1: Enable
[0]	RSV	Reserved

22.3.7 P3_AN (0x4052)

Bit	7	6	5	4	3	2	1	0
Name	RSV		P3_AN		RSV		P3_AN	
Type	-	-	R/W	R/W	-	R/W	R/W	R/W
Reset	-	-	0	0	-	0	0	0

Bit	Name	Description
[7:6]	RSV	Reserved
[5:4]	P3_AN	P3.5 ~ P3.4 Analog Mode Enable 0: Disable 1: Enable
[3]	RSV	Reserved
[2:0]	P3_AN	P3.2 ~ P3.0 Analog Mode Enable 0: Disable 1: Enable

22.3.8 P0_PU (0x4053)

Bit	7	6	5	4	3	2	1	0
Name		P0_PU			RSV			
Type	R/W	R/W	R/W	-	-	-	-	-
Reset	0	0	0	-	-	-	-	-

Bit	Name	Description
[7:5]	P0_PU	P0.7 ~ P0.5 Pull-up Resistor Enable 0: Disable 1: Enable
[4:0]	RSV	Reserved

22.3.9 P1_PU (0x4054)

Bit	7	6	5	4	3	2	1	0
Name	RSV		P1_PU					
Type	-	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	0	0	0	0	0	0	0

Bit	Name	Description
[7]	RSV	Reserved
[6:0]	P1_PU	P1.6 ~ P1.0 Pull-up Resistor Enable 0: Disable 1: Enable

22.3.10 P2_PU (0x4055)

Bit	7	6	5	4	3	2	1	0
Name		P2_PU	RSV	P2_PU	RSV	P2_PU	RSV	
Type	R/W	R/W	-	R/W	-	-	R/W	-
Reset	0	0	-	0	-	-	0	-

Bit	Name	Description

[7:6]	P2_PU	P2.7 ~ P2.6 Pull-up Resistor Enable 0: Disable 1: Enable
[5]	RSV	Reserved
[4]	P2_PU	P2.4 Pull-up Resistor Enable 0: Disable 1: Enable
[3: 2]	RSV	Reserved
[4]	P2_PU	P2.1 Pull-up Resistor Enable 0: Disable 1: Enable
[0]	RSV	Reserved

22.3.11 P3_PU (0x4056)

Bit	7	6	5	4	3	2	1	0
Name	RSV		P3_PU		RSV		P3_PU	
Type	-	-	R/W	R/W	-	R/W	R/W	R/W
Reset	-	-	0	0	-	0	0	0
Bit	Name	Description						
[7:6]	RSV	Reserved						
[5:4]	P3_PU	P3.5 ~ P3.4 Pull-up Resistor Enable 0: Disable 1: Enable						
[3]	RSV	Reserved						
[2:0]	P3_PU	P3.2 ~ P3.0 Pull-up Resistor Enable 0: Disable 1: Enable						

22.3.12 PH_SEL (0x404C)

Bit	7	6	5	4	3	2	1	0
Name	SPITMOD	UARTEN	UARTCH	RSV	T3SEL	T2SEL	T2SSEL	RSV
Type	R/W	R/W	R/W	-	R/W	R/W	R/W	-
Reset	0	0	0	-	0	0	0	-
Bit	Name	Description						
[7]	SPITMOD	MISO port status after SPI slave device completes transmission 0: Output State 1: High-impedance State						
[6]	UARTEN	UART Enable 0: Disable 1: Enable						
[5]	UARTCH	UART Function Switching 0: No function switching with P0.6 serving as RXD and P0.5 as TXD. 1: Function switching, with P3.3 serving as RXD and P3.4 as TXD.						
[4]	RSV	Reserved						
[3]	T3SEL	Port Pins Multiplexed as Timer3 0: P1.1 is multiplexed as GPIO. 1: P1.1 is multiplexed as Timer3 I/O pins.						
[2]	T2SEL	Port Pins Multiplexed as Timer2 0: P1.0 is multiplexed as GPIO. 1: P1.0 is multiplexed as Timer2 I/O pins.						
[1]	T2SSEL	Port Pins Multiplexed as Timer2 Port 2 0: P0.7 is multiplexed as GPIO. 1: P0.4 is multiplexed as I/O pins of Timer2 port 2. Note: Timer2 has the highest priority, then the comparator output and SPI MISO.						
[0]	RSV	Reserved						

22.3.13 P0 (0x80)/P1 (0x90)/P2 (0xA0)/P3 (0xB0) /P4 (0xE8)

Port output register P0/1/2/3/4 supports read and write access. RMW commands are used to access the register value (see Table 22-2 for RMW commands), and other commands are used to access PORT pin.

Table 22-1 P0/P1/P2/P3

Bit	7	6	5	4	3	2	1	0
Name	GPx[7]	GPx[6]	GPx[5]	GPx[4]	GPx[3]	GPx[2]	GPx[1]	GPx[0]
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
<hr/>								
Register Name	Function Description				R/W	Initial Value		
P0[7:0]	GPIO Register0				R/W	0x00		
P1[7:0]	GPIO Register1				R/W	0x00		
P2[7:0]	GPIO Register2				R/W	0x00		
P3[7:0]	GPIO Register3				R/W	0x00		

Table 22-2 RMW Commands

Command	Description
ANL	Bitwise logical AND operation
ORL	Bitwise logical OR operation
XRL	Bitwise logical XOR operation
JBC	Jump if the bit is set to “1” and then cleared to “0”
CPL	Bitwise logical converse operation
INC, DEC	+1, -1 logical operation
DJNZ	Jump if the bit is not “0”
MOV Px, y, C	Assign carry bit C to Px, y
CLR Px, y	Px, y is cleared to “0”
SETB Px, y	Px, y is set to “1”

23 ADC

23.1 ADC Block Diagram




Figure 23-1 ADC Block Diagram

23.2 ADC Operations

ADC module is a 12-bit successive approximation register ADC with 12 channels inside. The sampling mode supports sequential sampling and trigger sampling. The result of sequential sampling are stored in ADCx_DR, and that triggered sampling is sent to FOC module for motor control. If both triggered sampling and sequential sampling are applied at the same time, the triggered sampling is performed first, and ADC automatically stores sequential sampling mode upon completion of triggered sampling.

23.2.1 Sequential Sampling Mode




Figure 23-2 ADC Sequential Sampling Timing

ADC operations:

1. Set the appropriate ADC VREF;

2. Configure ADC_MASK to enable the corresponding channel required to sample;
3. Set sampling delay for each channel (minimum value is 3);
4. Configure ADC_CR[ADCEN] = 1 to enable ADC;
5. Configure ADC_CR[ADCBSY] = 1 to start ADC;
6. ADC results are read after ADC_CR[ADCBSY] = 0.
7. The ADC conversion sequence is from low to high based on the enabled channel (i.e., when channel 2/3/4 is enabled, the signal is sampled in order of 2/3/4, and then a single conversion result is read after confirming ADC_CR[ADCBSY] = 0).

The chip integrates a 12-bit ADC with 12 channels. Before using ADC module, ADC_MASK shall be properly configured to enable the corresponding channel required to sample, and sampling delay for each channel (minimum value is 3) shall be defined as well. ADC module starts operating after ADC_CR[ADCEN] and ADC_CR[ADCBSY] are set to “1”.

In addition, ADC module supports ADC triggered sampling, and the priority (triggered by FOC module) is higher than that of sequential sampling (controlled by software).

After FOC module is enabled (DRV_CR[FOCEN] = 1), FOC module automatically starts ADC module and triggers ADC sampling when necessary. The result of triggered sampling is sent to FOC module for motor control.

Note: ADC triggered sampling has a higher priority. If sequential sampling (controlled by software) is being processed and ADC sampling is triggered, ADC module stops sequential sampling to perform ADC triggered sampling, and then continues sequential sampling. If ADC triggered sampling is being processed and sequential sampling is requested, ADC module continues current ADC triggered sampling and performs sequential sampling upon completion of ADC triggered sampling.

23.2.2 ADC Triggered Sampling Mode

After FOC module is enabled, ADC module can initiate ADC triggered sampling when required. ADC triggered sampling and sequential sampling can be requested at the same time. Internal circuit automatically matches the timing for the two different sampling modes, but different ADC channels shall be configured.

After FOC module is enabled (DRV_CR[FOCEN] = 1), FOC module automatically starts ADC module and triggers ADC sampling when necessary. The result of triggered sampling is sent to FOC module for motor control.




Figure 23-3 ADC Triggered Sampling Process

As shown above, after ADC channel 0/1/4 is enabled and FOC module is enabled, FOC module can trigger ADC triggered sampling and directly read the results.

23.3 ADC Registers

23.3.1 ADC_CR (0x4039)

Bit	7	6	5	4	3	2	1	0
Name	ADCEN	ADCBSY	RSV			ADCALIGN	ADCIE	ADCIF
Type	R/W	R/W1	-	-	-	R/W	R/W	R/W
Reset	0	0	-	-	-	0	0	0
<hr/>								
Bit	Name	Description						
[7]	ADCEN	ADC Enable 0: Disable 1: Enable						
[6]	ADCBSY	ADC Busy Flag ADC_CR[ADCEN] shall be configured first to enable the ADC module, and then ADC_CR[ADCBSY] for ADC conversion. A write of “1” to this bit starts ADC conversion. After ADC conversion, this bit is automatically cleared to “0” by hardware. MCU can read this bit to check the operating status of ADC conversion. When this bit is set to “1”, it has no effect to write “1” to this bit. A write of “0” to this bit has no effect when ADC_MASK=0.						
[5:3]	RSV	Reserved						
[2]	ADCALIGN	ADC Data Format Selection 0: ADC output is right-aligned 1: ADC output is left-second-high-aligned (invalid in triggered sampling mode)						
[1]	ADCIE	ADC Interrupt Enable (excluding triggered sampling mode interrupt) This bit determines whether ADC_CR[ADCIF] sends ADC interrupt to MCU. 0: Disable 1: Enable						
[0]	ADCIF	ADC Interrupt Flag After the ADC conversion is completed, if ADC_CR[ADCIE] = 1, an ADC interrupt is generated and sent to MCU. 0: The ADC conversion is not completed. 1: The ADC conversion is completed.						

23.3.2 ADC_MASK (0x4036, 0x4037)

ADC_MASKH(0x4036)								
Bit	15	14	13	12	11	10	9	8
Name	ADC_SCYCH[11:8]				CH11EN	CH10EN	CH9EN	CH8EN
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	1	1	0	0	0	0
<hr/>								
Bit	7	6	5	4	3	2	1	0
Name	CH7EN	CH6EN	CH5EN	CH4EN	CH3EN	CH2EN	CH1EN	CH0EN
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
<hr/>								
Bit	Name	Description						
[11]	CH11EN	ADC Channel 11 Enable See ADC MASK[CH0EN].						
[10]	CH10EN	ADC Channel 10 Enable See ADC MASK[CH0EN].						
[9]	CH9EN	ADC Channel 9 Enable See ADC MASK[CH0EN].						
[8]	CH8EN	ADC Channel 8 Enable See ADC MASK[CH0EN].						

[7]	CH7EN	ADC Channel 7 Enable See ADC MASK[CH0EN].
[6]	CH6EN	ADC Channel 6 Enable See ADC MASK[CH0EN].
[5]	CH5EN	ADC Channel 5 Enable See ADC MASK[CH0EN].
[4]	CH4EN	ADC Channel 4 Enable See ADC MASK[CH0EN].
[3]	CH3EN	ADC Channel 3 Enable See ADC MASK[CH0EN].
[2]	CH2EN	ADC Channel 2 Enable See ADC MASK[CH0EN].
[1]	CH1EN	ADC Channel 1 Enable See ADC MASK[CH0EN].
[0]	CH0EN	ADC Channel 0 Enable 0: Disable 1: Enable

23.3.3 ADC_MASKH (0x4036)

ADC_MASKH(0x4036)								
Bit	7	6	5	4	3	2	1	0
Name	ADC_SCYCH[7:4]				CH11EN	CH10EN	CH9EN	CH8EN
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	1	1	0	0	0	0
Bit	Name		Description					
[7:4]	ADC_SCYCH[7:4]		ADC Sampling Cycle for ADC Channel 8, 9, 10 and 11 ADC_SCYCH[7] = 0: The sampling cycle is ADC_SCYCH[7:4] ADC clock cycles. ADC_SCYCH[7] = 1: The sampling cycle is (ADC_SCYC [7:4]*8 + 7) ADC clock cycles.					
[3]	CH11EN		ADC Channel 11 Enable					
[2]	CH10EN		ADC Channel 10 Enable					
[1]	CH9EN		ADC Channel 9 Enable					
[0]	CH8EN		ADC Channel 8 Enable					

23.3.4 ADC_SCYCL (0x4038)

ADC_SCYCL(0x4038)								
Bit	7	6	5	4	3	2	1	0
Name	ADC_SCYC[7:4]				ADC_SCYC[3:0]			
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	1	1	0	0	1	1
Bit	Name		Description					
[7:4]	ADC_SCYC[7:4]		ADC Sampling Cycle for ADC Channel 5 and 7 ADC_SCYC[7] = 0: The sampling cycle is ADC_SCYC [6:4] ADC clock cycles. ADC_SCYC[7] = 1: The sampling cycle is (ADC_SCYC [6:4]*8 + 7) ADC clock cycles.					
[3:0]	ADC_SCYC[3:0]		ADC Sampling Cycle for ADC Channel 0, 1, 2 and 4 ADC_SCYC[3] = 0: The sampling cycle is ADC_SCYC[2:0] ADC clock cycles. ADC_SCYC[3] = 1: The sampling cycle is (ADC_SCYC[2:0]*8 + 7) ADC clock cycles.					

23.3.5 ADC0_DR (0x0300, 0x0301)

ADC0 DRH(0x0300)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC0 DRL(0x0301)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 0 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 0 after ADC conversion						

23.3.6 ADC1_DR (0x0302, 0x0303)

ADC1 DRH(0x0302)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	R	R	R	R	R
Reset	-	-	-	0	0	0	0	0
ADC1 DRL(0x0303)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 1 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 1 after ADC conversion						

23.3.7 ADC2_DR (0x0304, 0x0305)

ADC2 DRH(0x0304)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC2 DRL(0x0305)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 2 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 2 after ADC conversion						

23.3.8 ADC4_DR (0x0308, 0x0309)

ADC4 DRH(0x0308)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC4 DRL(0x0309)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 4 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 4 after ADC conversion						

23.3.9 ADC5_DR (0x030A, 0x030B)

ADC5 DRH(0x030A)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC5 DRL(0x030B)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 5 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 5 after ADC conversion						

23.3.10 ADC7_DR (0x030E, 0x030F)

ADC7 DRH(0x030E)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC7 DRL(0x030F)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 7 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 7 after ADC conversion						

23.3.11 ADC8_DR (0x0310, 0x0311)

ADC8 DRH(0x0310)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC8 DRL(0x0311)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 8 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 8 after ADC conversion						

23.3.12 ADC9_DR (0x0312, 0x0313)

ADC9 DRH(0x0312)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC9 DRL(0x0313)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 9 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 9 after ADC conversion						

23.3.13 ADC10_DR (0x0314, 0x0315)

ADC10 DRH(0x0314)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC10 DRL(0x0315)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 10 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 10 after ADC conversion						

23.3.14 ADC11_DR (0x0316, 0x0317)

ADC11 DRH(0x0316)								
Bit	15	14	13	12	11	10	9	8
Name	RSV					DH[11:8]		
Type	-	-	-	-	R	R	R	R
Reset	-	-	-	-	0	0	0	0
ADC11 DRL(0x0317)								
Bit	7	6	5	4	3	2	1	0
Name	DL[7:0]							
Type	R	R	R	R	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:12]	RSV	Reserved						
[11:8]	DH	4 high-order bits of the result by ADC channel 11 after ADC conversion						
[7:0]	DL	8 low-order bits of the result by ADC channel 11 after ADC conversion						

24 DAC

24.1 DAC Functional Block Diagram




Figure 24-1 DAC Functional Block Diagram

Notes:

- DAC0 output has no current drive capability and can only carry capacitive load. To carry resistive load, operational amplifiers are used to follow the voltage output.
- Configure P2_AN[6] = 1 and P2_OE[6] = 1, and DAC0 output to P2.6/DAC pin;
- Configure VREF_CR[VREFEN] = 1 and DAC_CR[DACEN] = 1, and VREF is used as DAC0 reference voltage.

24.2 DAC Registers

24.2.1 DAC_CR (0x4035)

Bit	7	6	5	4	3	2	1	0
Name	DACEN	DACMO D	RSV					
Type	R/W	R/W	-	-	-	-	-	-
Reset	0	0	-	-	-	-	-	-
<hr/>								
Bit	Name	Description						
[7]	DACEN	DAC Enable 0: Disable 1: Enable						
[6]	DACMO D	DAC Mode Setting 0: Full-voltage Output Mode. DAC output voltage ranges from 0 to VREF. 1: Half-voltage Output Mode. DAC output voltage ranges from VHALF to VREF.						
[5:0]	RSV	Reserved						

24.2.2 DAC_DR (0x404B)

Bit	7	6	5	4	3	2	1	0
Name	DAC DR							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	DAC DR	Data Input of DAC Controller						

25 DMA

25.1 DMA Instructions




Figure 25-1 DMA Functional Block Diagram

The DMA module is a dual-channel DMA controller, which performs direct data transfer between peripherals (SPI and UART) and XRAM (IRAM data invalid). DMA accessing to XRAM does not interfere with the normal CPU read/write operation to XRAM. The length of the transferred data and the start address of XRAM access is configurable. Data transfer mode is configurable and interrupt can be enabled.

DMA instructions are as follows: Configure and enable the peripheral, and set input and output channels taken over by DMA by DMAx_CR0[DMACFG]; and then configure DMA interrupt enable, transfer order, transfer length and XRAM start address. Write “1” to DMAx_CR0[DMAEN] and DMAx_CR0[DMABSY] to start DMA. Clear the interrupt flag bit after data transfer, and set DMAx_CR0[DMABSY] to “1” to start DMA again.

25.2 DMA Registers

25.2.1 DMA0_CR0 (0x403A)

Bit	7	6	5	4	3	2	1	0
Name	DMAEN	DMABSY	DMACFG			DMAIE	ENDIAN	DMAIF
Type	R/W	R/W1	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	DMAEN	DMA Channel 0 Enable 0: Disable 1: Enable						
[6]	DMABSY	DMA Channel 0 Start/Busy Flag Read: 0: Channel 0 is idle. 1: Channel 0 is busy. Write: 0: No effect 1: Channel 0 starts for data transfer						
[5:3]	DMACFG [2:0]	DMA Channel 0 Peripherals and Transfer Direction Selection 000: From UART to XRAM 001: From XRAM to UART 100: From SPI to XRAM 101: From XRAM to SPI Note: It cannot be configured when Channel 0 is busy.						
[2]	DMAIE	DMA Interrupt Request Enable 0: Disable 1: Enable. When the interrupt flag CH0INT or CH1INT is “1”, DMA module sends the interrupt request to MCU.						
[1]	ENDIAN	DMA Data Transfer Sequence 0: High bytes are received or sent first 1: Low bytes are received or sent first Note: This bit is set for 16-bit data mode, and shall be configured to “0” for 8-bit data mode. It cannot be configured when Channel 0 or 1 is busy.						
[0]	DMAIF	DMA Channel 0 Transfer Interrupt Event Flag This bit is set to “1” by hardware, and cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending (When INTEN = 1, DMA module sends the interrupt request to MCU. Otherwise, only an interrupt flag is generated.)						

25.2.2 DMA1_CR0 (0x403B)

Bit	7	6	5	4	3	2	1	0
Name	DMAEN	DMABSY	DMACFG			DBGSW	DBGEN	DMAIF
Type	R/W	R/W1	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	DMAEN	DMA Channel 1 Enable 0: Disable 1: Enable						
[6]	DMABSY	DMA Channel 1 Start/Busy Flag Read: 0: Channel 1 is idle. 1: Channel 1 is busy. Write: 0: No effect 1: Channel 1 starts for data transfer						

[5:3]	DMACFG [2:0]	DMA Channel 1 Peripherals and Transfer Direction Selection 000: From UART to XRAM 001: From XRAM to UART 100: From SPI to XRAM 101: From XRAM to SPI Note: It cannot be configured when Channel 1 is busy.
[2]	DBGSW	Sector Targeted in Debug Mode 0: XSFR as the Debug area (export address space: 0x4020 ~ 0x40FF) 1: XRAM as the Debug area (export address space: 0x0000 ~ 0x0317)
[1]	DBGEN	Debug Mode Enabled 0: Disable 1: Enable DMA module works in Debug mode when DMA1[DMACFG] is set to “101” and DMA1_CR0[DBGEN] to “1”. After SPI is enabled (SPI_CR1[SPIEN] = 1), DMA automatically sends relevant data in the sector defined by DMA1_CR0[DBGSW] via MOSI. CH1BA/CH1LEN defines the start address and range of the relevant data. NSS is automatically pulled low during data transmission. After each transmission, NSS is automatically pulled high. DMA Channel 1 Interrupt is automatically disabled in debug mode.
[0]	DMAIF	DMA Channel 1 Transfer Interrupt Event Flag This bit is set to “1” by hardware, and cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending (When INTEN = 1, DMA module sends the interrupt request to MCU. Otherwise, only an interrupt flag is generated.)

25.2.3 DMA0_CR1 (0x403C)

DMA0_CR1H(0x403C)								
Bit	15	14	13	12	11	10	9	8
Name	CH0LEN							CH0BA[9:8]
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DMA0_CR1L(0x403D)								
Bit	7	6	5	4	3	2	1	0
Name	CH0BA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name		Description					
[15:10]	CH0LEN [5:0]		Read: The number of the byte that is currently transferred by DMA Channel 0 (0 denotes the first byte) Write: XRAM data transfer length of DMA Channel 0 Note: It cannot be configured when Channel 0 is busy. When DMA0_CR0[ENDIAN] = 1 (low bytes are received or transmitted first), it is recommended that CH0LEN be set to an odd number.					
[9:0]	CH0BA [9:0]		Start address of XRAM data transfer by DMA Channel 0 It cannot be configured when Channel 0 is busy. Note: XRAM address space for data transfer by Channel 0: CH0BA[9:0] ~ (CH0BA[9:0] + CH0LEN[5:0])					

25.2.4 DMA1_CR1 (0x403E)

DMA1_CR1H(0x403E)								
Bit	15	14	13	12	11	10	9	8
Name	CH1LEN						CH1BA[9:8]	
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
DMA1_CR1L(0x403F)								
Bit	7	6	5	4	3	2	1	0
Name	CH1BA[7:0]							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[15:10]	CH1LEN [5:0]	Read: The number of the byte that is currently transferred by DMA Channel 1 (0 denotes the first byte) Write: XRAM data transfer length of DMA Channel 1 Note: It cannot be configured when Channel 1 is busy. When DMA_CR0[ENDIAN] = 1, it is recommended that CH1LEN be set to an odd number.						
[9:0]	CH1BA [9:0]	Start address of XRAM data transfer by DMA Channel 1 It cannot be configured when Channel 1 is busy. Note: XRAM address space for data transfer by Channel 1: CH1BA[9:0] ~ (CH1BA[9:0] + CH1LEN[5:0]).						

26 VREF

26.1 VREF Instructions




Figure 26-1 I/O Pins of VREF Module

The input and output ports of the VREF module are shown in Figure 26-1. VREF is the voltage reference generation block that provides internal voltage reference to ADC and DAC modules.

VREF is enabled when VREF_VHALF_CR[VREFEN] is set to “1”. The output voltage is selected by configuring VREF_VHALF_CR bit. See section 26.2.1 VREF_VHALF_CR (0x404F) for details. When P3_AN[5] = 1, VREF is output to P3.5 pin.

26.2 VREF Register

26.2.1 VREF_VHALF_CR (0x404F)

Bit	7	6	5	4	3	2	1	0
Name	VREFVSEL	RSV	VREFEN	RSV			VHALF EN	
Type	R/W	-	R/W	-	-	-	-	R/W
Reset	0	0	-	0	-	-	-	0
<hr/>								
Bit	Name		Description					
[7: 6]	VREFVSEL		VREF Module Output Voltage Selection 01: VDD5 00: 4.5V 11: 4V 10: 3V					
[5]	RSV		Reserved					
[4]	VREFEN		VREF Module Enable 0: Disable. P3_AN[5] is set to “1”, and external VREF is input from P3.5 pin. 1: Enable. P3_AN[5] is set to “1”, and internal VREF is output to P3.5 pin. A 0.1μF ~ 1μF external capacitor is added to improve the stability of VREF.					
[3:1]	RSV		Reserved					
[0]	VHALFEN		VHALF Enable 0: Disable 1: Enable					

27 VHALF

27.1 VHALF Instructions




Figure 27-1 I/O Pins of VHALF Module

The input and output ports of VHALF module are shown in Figure 27-1. This module generates the voltage reference.

VHALF is enabled when VREF_VHALF_CR[VHALFEN] is set to “1”. If P3_AN[2] = 1, the voltage is output to P3.2.

27.2 VHALF Register

See section 26.2.1.

28 Operational Amplifier

The chip integrates three high-speed independent operational amplifiers, AMP0, AMP1 and AMP2. Each operational amplifier has a separate enable bit.




Figure 28-1 Schematic Diagram of Operational Amplifier Module

28.1 Operational Amplifier Instructions

28.1.1 Bus Current Sampling Operational Amplifier (AMP0)

Connection diagram of AMP0 is shown in Figure 28-2.




Figure 28-2 AMP0 I/O Pins

AMP0 is enabled when $\text{AMP_CR}[\text{AMP0EN}] = 1$.

The I/O pins of AMP0 are shown in Figure 28-2. Before AMP0 is enabled, P2.7, P3.0 and P3.1 shall be automatically configured to analog signal mode, $\text{P2_AN}[7]$ to “1” and $\text{P3_AN}[1:0]$ to “11”.

28.1.2 Phase Current Operational Amplifier (AMP1/AMP2)

28.1.2.1 AMP1




Figure 28-3 AMP1 I/O Pins

AMP1 is enabled when $\text{AMP_CR}[\text{AMP1EN}] = 1$.

The I/O pins of AMP1 are shown in Figure 28-3. Before AMP1 is enabled, P1.6 shall be automatically configured to analog signal mode, P1_AN[6] to “11” and P2_AN[0] to “1”.

28.1.2.2 AMP2




Figure 28-4 AMP2 I/O Pins

AMP2 is enabled when $\text{AMP_CR}[\text{AMP2EN}] = 1$.

The I/O pins of AMP2 are shown in Figure 28-4. Before AMP2 is enabled, P2.1 shall be automatically configured to analog signal mode and P2_AN[1] to “111”.

28.1.3 PGA Differential Input Mode




Figure 28-5 AMP0 Operating in PGA Differential Input Mode

In PGA differential input mode, positive and negative inputs of AMP0 are connected with a $1k\Omega$ resistor respectively. The magnification gain can be configured as shown in the figure above.




Figure 28-6 AMP0 Operating in PGA Single-ended Input Mode (Negative Input Connected to GND)




Figure 28-7 AMP1 Operating in PGA Single-ended Input Mode (Negative Input Connected to GND)




Figure 28-8 AMP2 Operating in PGA Single-ended Input Mode (Negative Input Connected to GND)

When PGA Single-ended Input Mode is selected, negative input of the operational amplifier shall be left floating or connected to GND (after AMP12M_GND/AMP0M_GND is configured in software). In this case, VHALF is equal to $25/64 \times VREF$.

When negative input of the operational amplifier is connected to GND, the output voltage is calculated as follows:

- When $AMP_GAIN = 2X$, $V_{out} = 7/6 \times V_{half} + 7/3 \times V_1$
- When $AMP_GAIN = 4X$, $V_{out} = 6/5 \times V_{half} + 24/5 \times V_1$
- When $AMP_GAIN = 8X$, $V_{out} = 11/9 \times V_{half} + 88/9 \times V_1$
- When $AMP_GAIN = 16X$, $V_{out} = 21/17 \times V_{half} + 336/17 \times V_1$

28.2 Operational Amplifier Registers

28.2.1 AMP_CR (0x404E)

Bit	7	6	5	4	3	2	1	0
Name	RSV					AMP2EN	AMP1EN	AMPOEN
Type	-	-	-	-	-	R/W	R/W	R/W
Reset	-	-	-	-	-	0	0	0
Bit	Name	Description						
[7:3]	RSV	Reserved						
[2]	AMP2EN	AMP2 Enable						
[1]	AMP1EN	AMP1 Enable						
[0]	AMPOEN	AMP0 Enable						

28.2.2 CMP_AMP (0x40f2)

Bit	7	6	5	4	3	2	1	0
Name	DAC_D_0	AMP_PH_GAIN[2:0]			AMP0_GAIN[2:0]			CMP3P4 M_FS
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	DAC_D_0	LSB of the 9-bit DAC data						
[6:4]	AMP_PH_GAIN[2:0]	Amplification Gain Setting of AMP1&2 (with a 1kΩ external resistor) 000: The gain is configured by external circuit 001: 2X 010: 4X 011: 8X 100: 16X 101: Reserved 110/111: The gain is configured by external circuit						
[3:1]	AMP0_GAIN[2:0]	Amplification Gain Setting of AMP0 (with a 1kΩ external resistor) 000: The gain is configured by external circuit 001: 2X 010: 4X 011: 8X 100: 16X 101: Reserved 110/111: The gain is configured by external circuit						
[0]	CMP3P4M_FS	Function of CMP3 Positive End/CMP4 Negative End P27 Transferred to P34 0: Disable 1: Enable						

28.2.3 TSD_ADJ (0x40f3)

TSD_ADJ(0x40f3)								
Bit	7	6	5	4	3	2	1	0
Name	RSV			AMP12M_GND	AMP0M_GND	TSDADJ3	TSDADJ0_0	
Type	-	-	-	-	R/W	R/W	R/W	R/W
Reset	-	-	-	-	0	0	0	0
Bit	Name	Description						

[7:4]	RSV	Reserved																																		
[3]	AMP12M_GND	After this bit is enabled, negative input P17/P22 of AMP1/AMP2 is connected to GND internally in PGA input mode, and VHALF = 25/64*VREF. 0: Disable 1: Enable																																		
[2]	AMP0M_GND	After this bit is enabled, negative input P30 of AMP0 is connected to GND internally in PGA input mode, and VHALF = 25/64*VREF. 0: Disable 1: Enable																																		
[1:0]	TSDADJ3/ TSDADJ0_0	<p>After combined with EVT_FILT, TSDADJ3 are the most significant bits, EVT_FILT[6:5] are the medium significant bits and TSDADJ0_0 are the least significant bits.</p> <table border="1"> <thead> <tr> <th>TSD_ADJ[3:0]</th> <th>Temperature (°C)</th> </tr> </thead> <tbody> <tr><td>1000</td><td>65</td></tr> <tr><td>1001</td><td>70</td></tr> <tr><td>1010</td><td>75</td></tr> <tr><td>1011</td><td>80</td></tr> <tr><td>1100</td><td>86</td></tr> <tr><td>1101</td><td>91</td></tr> <tr><td>1110</td><td>97</td></tr> <tr><td>1111</td><td>103</td></tr> <tr><td>0000</td><td>105</td></tr> <tr><td>0001</td><td>115</td></tr> <tr><td>0010</td><td>120</td></tr> <tr><td>0011</td><td>128</td></tr> <tr><td>0100</td><td>135</td></tr> <tr><td>0101</td><td>142</td></tr> <tr><td>0110</td><td>150</td></tr> <tr><td>0111</td><td>Reserved</td></tr> </tbody> </table>	TSD_ADJ[3:0]	Temperature (°C)	1000	65	1001	70	1010	75	1011	80	1100	86	1101	91	1110	97	1111	103	0000	105	0001	115	0010	120	0011	128	0100	135	0101	142	0110	150	0111	Reserved
TSD_ADJ[3:0]	Temperature (°C)																																			
1000	65																																			
1001	70																																			
1010	75																																			
1011	80																																			
1100	86																																			
1101	91																																			
1110	97																																			
1111	103																																			
0000	105																																			
0001	115																																			
0010	120																																			
0011	128																																			
0100	135																																			
0101	142																																			
0110	150																																			
0111	Reserved																																			

29 Comparator

29.1 Comparator Operations

29.1.1 Comparator CMP3




Figure 29-1 CMP3 I/O Pins

The I/O pins of CMP3 are shown in Figure 29-1.

CMP3 configurations:

- Set P2_AN[6] and P2_OE[6] to “1” to enable CMP3 and VREF on the negative input. The VREF source can be on-chip DAC0 output voltage or external circuit input voltage. Select DAC0 output, and place an external capacitor between P2.6 pin and GND (the recommended capacitance value is 100pF, and the output voltage stabilizes after DAC0 output for a period of time);
- Configure CMP_CR1[CMP3MOD] to select single-comparator input, dual-comparator input or triple-comparator input mode;
 - When CMP_CR1[CMP3MOD] = 00, CMP3 works in single-comparator input mode. The connection of input and output pins are shown in Figure 29-2.
 - When CMP_CR1[CMP3MOD] = 01, CMP3 works in dual-comparator input mode. The connection of input and output pins are shown in Figure 29-3.
 - When CMP_CR1[CMP3MOD] = 1X, CMP3 works in triple-comparator input mode. The connection of input and output pins are as shown in Figure 29-4.
- Configure CMP_CR1[CMP3HYS] to enable or disable hysteresis;
- Set CMP_CR1[CMP3EN] = 1 to enable CMP3.




Figure 29-2 Single-comparator Input Mode (CMP_CR1[CMP3MOD] = 00)




Figure 29-3 Dual-comparator Input Mode (CMP_CR1[CMP3MOD] = 01)




Figure 29-4 Triple-comparator Input Mode (CMP_CR1[CMP3MOD] = 1X)

29.1.1.1 Overcurrent Protection (OCP)

When an overcurrent protection signal is generated, DRV_OUT[MOE] is automatically cleared output idle voltage to stop motor drive for chip and motor protection. OCP feature is enabled when EVT_FILT[MOEMD] = 01, which automatically turns off the output and generates an OCP interrupt request if the current exceeds the threshold. When EVT_FILT[MOEMD]=00, the output is not automatically turned off if the current exceeds the threshold. However, an OCP request is generated by the hardware.

The source of OCP interrupt is selected by configuring EVT_FILT[EFSRC], namely CMP3 interrupt or external interrupt INT0. When EVT_FILT[EFSRC] = 1, TCON[IT0] bit is programmed to select the trigger edge of the external interrupt INT0 which generates an OCP output. At this time, the source of OCP interrupt is INT0. When EVT_FILT[EFSRC] = 0 and CMP_CR0[CMP3IM] = 11, the OCP output is generated on the raising edge of CMP3. At this time, the source of OCP interrupt is CMP3. In triple-shunt current sampling mode, CMP_CR1[CMP3MOD] is configured to select triple-comparator input mode. When current of any phase is over the threshold, CMP3 generates an OCP signal. For other sampling modes, CMP_CR1[CMP3MOD] is configured to choose single-comparator input mode. When bus current is over the threshold, CMP3 generates an OCP signal.

Configuring EVT_FILT[EFDIV] enables the filtering of interrupt signals for OCP, and programming EVT_FILT[EFDIV] = 01/10/11 selects filter width of 4/8/16 clock cycles. When the filtering feature is enabled, the filtered signal is delayed by 4/8/16 clock cycles compared to the signal before filtering.




Figure 29-5 MOE Disabled upon Bus Overcurrent Protection

When $\text{CMP_CR0}[\text{CMP3IM}] = 11$, the OCP output is generated on the raising edge of CMP3. If $\text{EVT_FILT}[\text{MOEMD}] = 01$, the output is automatically turned off when a protection event occurs and a protection interrupt is reported. If $\text{EVT_FILT}[\text{EFSRC}] = 0$, the bus current protection signal is generated by CMP3, and sampled voltage on the bus is compared to generate the protection signal. Setting $\text{EVT_FILT}[\text{EFDIV}] = 01/10/11$ selects filter width of 4/8/16 clock cycles. When the filtering feature is enabled, the filtered signal is delayed by $4 \sim 5/8 \sim 9/16 \sim 17$ clock cycles compared to the signal before filtering. As shown in Figure 29-5, when voltage on positive input of the comparator is higher than that on negative input, CMP3_OUT1 is set to “1” to generate CMP3 comparison interrupt for filtering (based on $\text{EVT_FILT}[\text{EFDIV}]$). MOE (DRV_OUT[MOE]) is automatically cleared to “0” to turn off six-way outputs to implement overcurrent protection.

29.1.1.2 Cycle-by-cycle Current Limiting

The cycle-by-cycle current limiting feature is applied to square-wave-based drive control of BLDC motors. When $\text{EVT_FILT}[\text{MOEMD}] = 10$, MOE is automatically enabled to turn off outputs and DRV_OUT[MOE] is automatically enabled upon DRV timer overflow events. When $\text{EVT_FILT}[\text{MOEMD}] = 11$, MOE is automatically enabled to turn off outputs and DRV_OUT[MOE] is automatically enabled upon DRV timer overflow/underflow events or every 5 μs .

$\text{CMP_CR0}[\text{CMP3IM}]$ must be configured for cycle-by-cycle current limiting, which generates CMP3 interrupt. The priority of CMP3 interrupt can be set to the lowest with an empty process function if the interrupt is not required.




Figure 29-6 Cycle-by-cycle Current Limiting Waveform at $EVT_FILT[MOEMD] = 10$




Figure 29-7 Cycle-by-cycle Current Limiting Waveform at $EVT_FILT[MOEMD] = 11$

29.1.2 Comparator CMP0

CMP0 supports multiple comparison modes for real-time detection on rotor position and motor speed. CMP0, CMP1 and CMP2 are automatically enabled according to the configurations.

Since the three-way output signals CMP0OUT ~ CMP2OUT of CMP0 are first sent to input signal filtering and edge detection modules of Timer1, TIM1_CR3[T1TIS] must be configured as “01” to ensure comparison results held by CMP_SR is generated based on CMP0, instead of Hall signals.

When CMP_CR2[CMP0MOD] = 00, CMP0 works in the mode of three comparators without built-in resistor. The I/O pins are shown in Figure 29-8. It is used for BEMF detection with the external virtual neutral point resistors. The negative inputs of the comparators are connected together to P1.5/CMP0M pin, and the positive inputs are connected to P1.4/CMP0P, P1.6/CMP1P and P2.1/CMP2P respectively. The outputs are transferred to CMP0OUT, CMP1OUT and CMP2OUT respectively.

Configurations are as follows:

1. Set TIM1_CR3[T1TIS] = 01 to select the comparator as the input;
2. Configure CMP_CR2[CMP0MOD] = 00 to select the mode of three comparators without built-in resistor;
3. Set P1_AN[6:4] = 111 and P2_AN[1] = 1 to configure the port pins as analog mode;
4. Set P1_PU[5:4] = 00 and Reset as 00. Skip this step if no modification is required;

5. Configure CMP_CR1[CMP0HYS] select the hysteresis voltage and Reset as 000;
6. Configure CMP_CR2[CMP0EN] = 1 to enable the comparator;
7. Configure CMP_CR2[CMP0SEL] to select one-way or multiple-way output(s). See Table 29-1;
8. The outputs results are sent to registers CMP2OUT ~ CMP0OUT.




Figure 29-8 CMP0 with Built-in Three Comparators

(without Built-in Resistor)

When CMP_CR2[CMP0MOD] = 01, CMP0 works in the mode of three comparators with built-in resistor. The I/O pins are shown in Figure 29-9. It is used for BEMF detection with the internal virtual neutral point resistors. The negative inputs of the comparators are connected the center point of the built-in resistor, and the positive inputs are connected to P1.4/CMP0P, P1.6/CMP1P and P2.1/CMP2P respectively. The outputs are transferred to CMP0OUT, CMP1OUT and CMP2OUT respectively.

Configurations are as follows:

1. Set TIM1_CR3[T1TIS] = 01 to select the comparator as the input;
2. Configure CMP_CR2[CMP0MOD] = 01 to select the mode of three comparators with built-in resistor;
3. Set P1_AN[6] = 1, P1_AN[4] = 1 and P2_AN[1] = 1 to configure the port pins as analog mode;
4. Set P1_PU[4] = 0 and Reset as 0. Skip this step if no modification is required;
5. Configure CMP_CR1[CMP0HYS] select the hysteresis voltage and Reset as 000;
6. Configure CMP_CR2[CMP0EN] = 1 to enable the comparator;
7. Configure CMP_CR2[CMP0SEL] to select one-way or multiple-way output(s). See Table 29-1;
8. The outputs results are sent to registers CMP2OUT ~ CMP0OUT.




Figure 29-9 CMP0 with Built-in Three Comparators and Resistor

When $\text{CMP_CR2}[\text{CMP0MOD}] = 11$, CMP0 works in the mode of dual-comparator. The I/O pins are shown in Figure 29-10. The negative inputs of the comparators are connected together to P1.5/CMP0M, and the positive inputs are connected to P1.4/CMP0P and P1.3/CMP1PS respectively. The outputs are transferred to CMP0OUT and CMP1OUT respectively.

Configurations are as follows:

1. Set $\text{TIM1_CR3}[\text{T1TIS}] = 01$ to select the comparator as the input;
2. Configure $\text{CMP_CR2}[\text{CMP0MOD}] = 11$ to select dual-comparator mode;
3. Set $\text{P1_AN}[5:3] = 111$ and $\text{P1_OE}[3] = 0$ to configure the port pins as analog mode;
4. Pull-up resistor of P1[5:3] can be enabled ($\text{P1_PU}[5:3] = 111$) or disabled ($\text{P1_PU}[5:3] = 000$) as required, and set Reset as 0. Skip this step if no modification is required. In dual-comparator mode, pull-up resistor of P1[5:3] is generally disabled and used for special applications.
5. Configure $\text{CMP_CR1}[\text{CMP0HYS}]$ select the hysteresis voltage and Reset as 000;
6. Configure $\text{CMP_CR2}[\text{CMPOEN}] = 1$ to enable the comparator;
7. Configure $\text{CMP_CR2}[\text{CMPOSEL}]$ to select one-way or multiple-way output(s). See Table 29-1;
8. The outputs results are sent to registers CMP1OUT and CMP0OUT.




Figure 29-10 CMP0 with Dual-comparator Mode

Hysteresis voltage of CMP0 can be set by register, and shall be properly configured according to actual demand.




Figure 29-11 CMP0 Input and Output under Positive and Negative Hysteresis Voltage

29.1.3 Comparator Sampling

The comparator sampling feature is mainly used for square-wave control and RSD (tailwind/headwind detection), which eliminates the switching interference from driving circuit. See section Sampling for square-wave control and section RSD Comparator Sampling for RSD.




Figure 29-12 PWM ON Sampling Mode

There is a delay from the PWM output to the output of the comparator, which is mainly affected by the following factors: resistance value of drive resistor, MOS on-off speed, and input delay and hysteresis settings of the comparator. As shown in Figure 29-13, the delaytime is from the chip output to the comparator output. When high-level sampling is performed, the sampling interval shall be enveloped by actual high-level output of the comparator. First, the sampling ON-delayed time CMP_SAMR[CSOND] is set to overcome output delay and ringing due to MOS on/off. At the end of the sampling interval, CMP_SAMR[CSOND] is delayed after the falling edge of PWM, at which time the actual sampling window has exceeded the corresponding high-level interval (PWM of CMP). The sampling OFF-lead time CMP_SAMR[CSOFFD] is set to stop sampling Toffdelay after PWM output falling edge, where $T_{offdelay} = \text{CMP_SAMR[CSOND]} - \text{CMP_SAMR[CSOFFD]}$.




Figure 29-13 PWM OFF Sampling Mode

Similarly, when low-level sampling is performed, ON-delayed time CMP_SAMR[CSOND] and OFF-

lead time CMP_SAMR[CSOFFD] are set reasonably to ensure that the actual sampling interval is located in the actually low-level output interval of the comparator.

Method for measuring the delay of PWM output to comparator: Set CMP_CR3[SAMSEL] = 00 to disable the comparator sampling delay feature. Set CMP_CR3[CMPSEL] to select the corresponding comparator output. Enable the PWM output and comparator, manually rotate the motor to change the comparator value, and measure the delay between the PWM output and the comparator output.

29.1.4 Comparator Output

CMP_CR3[CMPSEL] is configured to output results of one comparator to a specific pin.

29.2 Comparator Registers

29.2.1 CMP_CR0 (0xD5)

Bit	7	6	5	4	3	2	1	0
Name	CMP3IM		CMP2IM		CMP1IM		CMP0IM	
Type	R/W		R/W		R/W		R/W	
Reset	0	0	0	0	0	0	0	0
<hr/>								
Bit	Name	Description						
[7:6]	CMP3IM	CMP3 Interrupt Mode See descriptions on CMP_CR0[CMP0IM].						
[5:4]	CMP2IM	CMP2 Interrupt Mode See descriptions on CMP_CR0[CMP0IM].						
[3:2]	CMP1IM	CMP1 Interrupt Mode See descriptions on CMP_CR0[CMP0IM].						
[1:0]	CMP0IM	CMP0 Interrupt Mode 00: No interrupt is generated. 01: An interrupt is generated upon rising edge. 10: An interrupt is generated upon falling edge. 11: An interrupt is generated upon both rising/falling edges.						

29.2.2 CMP_CR1 (0xD6)

Bit	7	6	5	4	3	2	1	0
Name	HALLSEL	CMP3MOD	CMP3EN	CMP3HYS		CMP0HYS		
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
<hr/>								
Bit	Name	Description						
[7]	HALLSEL	Hall Input Selection 0: Reserved 1: P1.4/P1.6/P2.1						
[6:5]	CMP3MOD	Positive Input of CMP3. See Figure 29-1 for details. The negative input is connected to P2.6 or DAC output. 00: Single-comparator mode, where P2.7 is connected to the positive input, as shown in Figure 29-2. 01: Dual-comparator mode, where P2.0 and P2.3 are connected to the positive input, as shown in Figure 29-3. 1X: Triple-comparator mode, where P2.0, P2.3 and P2.7 are connected to the positive input, as shown in Figure 29-4.						
[4]	CMP3EN	CMP3 Enable 0: Disable 1: Enable						

[3]	CMP3HYS	CMP3 Hysteresis Voltage Selection 0: No hysteresis 1: Hysteresis voltage is selected
[2:0]	CMP0HYS	CMP0 Hysteresis Voltage Selection: 000: No hysteresis 001: ±2.5mV 010: -5mV 011: +5mV 100: ±5mV 101: -10mV 110: +10mV 111: ±10mV

29.2.3 CMP_CR2 (0xDA)

Bit	7	6	5	4	3	2	1	0
Name	CMP4EN		CMP0MOD		CMP0SEL		RSV	CMP0EN
Type	R/W		R/W	R/W	R/W	-	-	R/W
Reset	0	0	0	0	0	-	-	0

Bit	Name	Description		
[7]	CMP4EN	CMP4 Enable 0: Disable 1: Enable		
[6:5]	CMP0MOD	CMP0/1/2 Mode Setting 00: CMP0 with built-in three comparators (without built-in resistor), as shown in Figure 29-8. 01: CMP0 with built-in three comparators and resistors, as shown in Figure 29-9. 11: CMP0 with dual-comparator mode, where only CMP0 and CMP1 work, as shown in Figure 29-10.		
[4:3]	CMP0SEL	CMP0 Pin Combination Selection, used with CMP_CR2[CMP0MOD] bit. It is set to 00 by default. In square-wave drive application, TIM1_DBRx[T1CPE] automatically controls CMP_CR2[CMP0SEL] to enable or disable each comparator. Table 29-1 Function Description of CMP0 Port and CMP_CR2[CMP0MOD] Combination		
		CMP0MOD	CMP0SEL	Function Description
		00	00	CMP0/1/2 work simultaneously. The negative input of these comparators are connected to CMP0M. The hardware automatically compares the positive inputs CMP0P, CMP1P and CMP2P with CMP0M, and the output results are transferred to CMP0OUT, CMP1OUT and CMP2OUT respectively.
			01	Only CMP0 works. The positive input is connected to CMP0P, and the negative input to CMP0M. The output results are transferred to CMP0OUT.
			10	Only CMP1 works. The positive input is connected to CMP1P, and the negative input to CMP0M. The output results are transferred to CMP1OUT.
			11	Only CMP2 works. The positive input is connected to CMP2P, and the negative input to CMP0M. The output results are transferred to CMP2OUT.
		01	00	CMP0/1/2 work simultaneously. The negative inputs of these comparators are connected to the center of built-in resistor. The hardware

				automatically compares the positive inputs CMP0P, CMP1P and CMP2P with CMP0M. The output results are transferred to CMP0OUT, CMP1OUT and CMP2OUT respectively.
		01		Only CMP0 works. The positive input is connected to CMP0P, and the negative input to the center of BEMF built-in resistor. The output results are transferred to CMP0OUT.
		10		Only CMP1 works. The positive input is connected to CMP1P, and the negative input is connected to the center of BEMF built-in resistor. The output results are transferred to CMP1OUT.
		11		Only CMP2 works. The positive input is connected to CMP2P, and the negative input is connected to the center of BEMF built-in resistor. The output results are transferred to CMP2OUT.
	10	00		CMP0/1/2 work simultaneously. The positive inputs of these comparators are connected to CMP0P, CMP1P and CMP2P respectively, and the negative inputs are connected to CMP0M, CMP1M and CMP2M respectively. The output results are transferred to CMP0OUT, CMP1OUT and CMP2OUT respectively.
	10	01		Only CMP0 works. The positive input is connected to CMP0P, and the negative input to CMP0M, and the output results are transferred to CMP0OUT.
	10	10		Only CMP1 works. The positive input is connected to CMP1P, and the negative input to CMP1M. The output results are transferred to CMP1OUT.
	10	11		Only CMP2 works. The positive input is connected to CMP2P, and the negative input to CMP2M. The output results are transferred to CMP2OUT.
	11	00		CMP0/1 work simultaneously. The positive inputs are connected to CMP0P and CMP1PS respectively, and the negative inputs to CMP0M. The outputs results are transferred to CMP0OUT and CMP1OUT respectively.
	11	01		Only CMP0 works. The positive input is connected to CMP0P, and the negative input to CMP0M. The output results are transferred to CMP0OUT.
	11	10		Only CMP1 works. The positive input is connected to CMP1PS, and the negative input to CMP0M. The output results are transferred to CMP1OUT.
	11	11		Reserved
[2:1]	RSV	Reserved		
[0]	CMP0EN	CMP0 Enable 0: Disable 1: Enable		

29.2.4 CMP_CR3 (0xDC)

Bit	7	6	5	4	3	2	1	0
Name	CMPDTEN	DBGSEL		SAMSEL		CMPSEL		
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	CMPDTEN	Comparator Deadtime Sampling Enable 0: Disable 1: Enable						
[6:5]	DBGSEL	Debug Output Selection, connected to P01 pin 00: Debug Output Disable 01: Freewheeling shielding is completed and ZCP signal is detected 10: ADC Trigger Signal 11: Comparator Sampling Interval						
[4:3]	SAMSEL	Sampling delay enable of CMP0, CMP1, CMP2 and ADC in PWM ON/OFF modes 00: Sampling at both PWM ON and OFF modes without time delay 01: Sampling at PWM OFF mode, with time delay according to CMP_SAMR 10: Sampling at PWM ON mode, with time delay according to CMP_SAMR 11: Sampling at both PWM ON and OFF, with time delay according to CMP_SAMR						
[2:0]	CMPSEL	Comparator Output Selection Signals of one selected comparator is output to the pin. See Comparator Debugging for details. 000: No output 001: CMP0 010: CMP1 011: CMP2 100: CMP3 101: CMP4 110: Reserved 111: ADC result comparison						

29.2.5 CMP_SAMR (0x40AD)

Bit	7	6	5	4	3	2	1	0
Name	CMP SAMR							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	1
Bit	Name	Description						
[7:4]	CSOND	CMP0/CMP1/CMP2 ON-delayed Sampling Time When PWM module switches from OFF to ON or from ON to OFF, turn-on/off of the power IC affects input signal of the comparator. In this case, CMP_SAMR[CSOND] is configured to delay the sampling of CMP0/CMP1/CMP2. The delay generated by drive circuit shall be taken into account when CMP_SAMR[CSOND] is calculated. If MCU clock runs at 24MHz(41.67ns) ON-delayed Sampling Time = CSOND x 41.67 x 8ns Notes: ■ CMP_SAMR[CSOND] must be greater than or equal to CMP_SAMR[CSOFFD]. ■ See section Sampling for square-wave control and section RSD Comparator Sampling for RSD.						
[3:0]	CSOFFD	CMP0/CMP1/CMP2 OFF-delayed Sampling Time When PWM module switches from OFF to ON or from ON to OFF, turn-on/off of the power IC affects input signal of the comparator. In this case,						

		CMP_SAMR[CSOFFD] is configured to reduce comparator interference. If MCU clock runs at 24MHz(41.67ns) OFF-lead Sampling Time = CSOFFD x 41.67 x 8ns Notes: <ul style="list-style-type: none">■ CMP_SAMR[CSOND] must be greater than or equal to CMP_SAMR[CSOFFD].■ See section Sampling for square-wave control and section RSD Comparator Sampling for RSD.
--	--	--

29.2.6 CMP_SR (0xD7)

Bit	7	6	5	4	3	2	1	0
Name	CMP3IF	CMP2IF	CMP1IF	CMP0IF	CMP3O UT	CMP2O UT	CMP1O UT	CMP0O UT
Type	R/W0	R/W0	R/W0	R/W0	R	R	R	R
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	CMP3IF	CMP3 Interrupt Flag This bit is set to “1” when CMP3 interrupt is generated. It is cleared to “0” by software. 0: No Interrupt Pending 1: Interrupt Pending						
[6]	CMP2IF	CMP2 Interrupt Flag This bit is set to “1” when CMP2 interrupt is generated. It is cleared to “0” by software. TIM1_CR3[T1TIS] must be configured to “01”, otherwise, it is the Hall interrupt flag. 0: No Interrupt Pending 1: Interrupt Pending						
[5]	CMP1IF	CMP1 Interrupt Flag This bit is set to “1” when CMP1 interrupt is generated. It is cleared to “0” by software. TIM1_CR3[T1TIS] must be configured to “01”, otherwise, it is the Hall interrupt flag. 0: No Interrupt Pending 1: Interrupt Pending						
[4]	CMP0IF	CMP0 Interrupt Flag This bit is set to “1” when CMP0 interrupt is generated. It is cleared to “0” by software. TIM1_CR3[T1TIS] must be configured to “01”, otherwise, it is the Hall interrupt flag. 0: No Interrupt Pending 1: Interrupt Pending						
[3]	CMP3OUT	CMP3 Comparison Result 0: CMP3 comparison result is 0. 1: CMP3 comparison result is 1.						
[2]	CMP2OUT	CMP2 Comparison Result TIM1_CR3[T1TIS] must be configured to “01”, otherwise, the results are generated by Hall signals. 0: CMP2 comparison result is 0. 1: CMP2 comparison result is 1.						
[1]	CMP1OUT	CMP1 Comparison Result TIM1_CR3[T1TIS] must be configured to “01”, otherwise, the results are generated by Hall signals. 0: CMP1 comparison result is 0. 1: CMP1 comparison result is 1.						
[0]	CMP0OUT	CMP0 comparison result TIM1_CR3[T1TIS] must be configured to “01”, otherwise, the results are generated by Hall signals. 0: CMP0 comparison result is 0. 1: CMP0 comparison result is 1.						

29.2.7 EVT_FILT (0xD9)

Bit	7	6	5	4	3	2	1	0	
Name	TSDEN	TSDADJ			MOEMD		EFSRC	EFDIV	
Type	R/W	R/W			R/W	R/W	R/W	R/W	
Reset	0	1	1	0	0	0	0	0	
Bit	Name	Description							
[7]	TSDEN	TSD Enable 0: Disable 1: Enable							
[6:5]	TSDADJ	TSD Temperature Selection. See section 0.							
[4:3]	MOEMD	MOE Cleared and Enabled by Hardware MOE is cleared and enabled by hardware upon over-/under-current protection event. 00: MOE is not automatically cleared. 01: MOE is automatically cleared. 10: MOE is automatically cleared and enabled by hardware upon DRV timer overflow events (for square-wave drive). 11: MOE is automatically cleared and enabled automatically upon DRV timer overflow/underflow events or every 5 µs (for square-wave drive).							
[2]	EFSRC	Input Source of Filtering Module Upon Current Protection Event 0: CMP3 interrupt 1: INTO interrupt							
[1:0]	EFDIV	Filter Width for Current Protection 00: Not to filter 01: 4 system clock cycles 10: 8 system clock cycles 11: 16 system clock cycles							

30 Power Supply

30.1 LDO

MCU contains two built-in LDO output modules: VDD5 and VDD18.

30.1.1 LDO Operations






Figure 30-1 Functional Block Diagram of Power Supply

The I/O pins of LDO module is shown in Figure 30-1. The LDO module converts the input supply voltage to 5V VDD5 or 1.8V VDD18 as the power supply for built-in analog and digital modules. Internal LDO5 or external supply for VDD5 is selected by configuring VCC_MODE. In high-voltage single-power supply mode, VCC = 12 ~ 20V as shown in Figure 30-2.



30.2 Low Voltage Detector (LVD)

30.2.1 LVD Introduction



Configuring CCFG1[LVDENB] = 0 enables LVD module.

30.2.2 LVD Registers

30.2.2.1 CCFG2:RST_MOD (0x401D)

Bit	7	6	5	4	3	2	1	0
Name	LVRSEL		WDTBTEN	WDTRSTEN	RSV		LVWSEL	
Type	R/W	R/W	R/W	R/W	-	-	R/W	R/W
Reset	0	0	0	0	-	-	0	0
Bit	Name	Description						
[7:6]	LVRSEL	Low Voltage Reset Threshold Voltage. VDD5 is detected for the low voltage reset. 00: Low voltage reset is enabled when VDD5 is lower than 2.8V. 01: Low voltage reset is enabled when VDD5 is lower than 3.0V. 10: Low voltage reset is enabled when VDD5 is lower than 3.5V. 11: Low voltage reset is enabled when VDD5 is lower than 3.8V.						
[5:2]		See section 35.1.2.						
[1:0]	LVWSEL	Low Voltage Warning Threshold Voltage. VCC is detected for the low voltage warning. 00: Low voltage warning is enabled when VCC is lower than 7V. 01: Low voltage warning is enabled when VCC is lower than 8V. 10: Low voltage warning is enabled when VCC is lower than 9V. 11: Low voltage warning is enabled when VCC is lower than 10V.						

30.2.2.2 CCFG1:CK_RST_CFG (0x401E)

Bit	7	6	5	4	3	2	1	0
Name	LVWENB	LVWIE	WDTEN	RSV		FCK SEL		RSV
Type	R/W	R/W	R/W	-	-	R/W	R/W	-
Reset	0	0	0	-	-	0	0	-
Bit	Name	Description						
[7]	LVWENB	Low Voltage Warning Enable 0: Disable 1: Enable						
[6]	LVWIE	VCC Low Voltage Warning Interrupt Enable. CCFG2[LVWSEL] decides VCC LV warning voltage threshold. 0: Disable 1: Enable. LV reset detection circuit shall be enabled as well (i.e. CCFG1[LVDENB] = 0).						
[5:0]		See section 35.1.1.						

30.2.2.3 LVSR(0xDB)

Bit	7	6	5	4	3	2	1	0
Name	RSV		EXT0CFG			TSDF	LVWF	LVWIF
Type	-	-	R/W	R/W	R/W	R	R	R/W
Reset	-	-	0	0	0	0	0	0
Bit	Name	Description						
[7:6]	RSV	Reserved						
[5:3]	EXT0CFG	INT0 Pin Selection 000: Reserved 001: Reserved 010: Reserved 011: Reserved 100: Reserved 101: P0.5 110: P0.6 111: CMP4 Output						

[2]	TSDF	<p>Over Temperature State Indicator 0: The current temperature does not exceed the threshold 1: The current temperature exceeds the threshold Note: This flag bit often works with TSD interrupt flag TCON[5], and reflects the dynamic over-temperature state.</p>
[1]	LVWF	<p>VCC Low Voltage(LV) Flag This bit indicates whether the chip is in the low voltage state. 0: The chip is not in the LV warning state. 1: The chip is in the LV warning state.</p>
[0]	LVWIF	<p>VCC LV Interrupt Flag This bit indicates whether a low voltage event occurs. It is set to “1” by hardware after low voltage detection interrupt is enabled and an low voltage detection interrupt is detected. A write of “0” in software clears this bit. 0: No Interrupt Pending 1: Interrupt Pending</p>

31 Flash

31.1 Flash Introduction

- 16kB Flash ROM;
- 128 sectors in total, each with a size of 128 bytes
- The first 127 sectors support erasure, write, on-line programing and in-application programming.
- Last sector (the 128th sector) cannot be erased at any time

31.2 Flash Operations

- All interrupts must be disabled before programming to ensure the security of Flash operations and avoid mis-operation of Flash using MOVX instruction during interrupt processing.
- Sector Erasure Operations:
 1. Disable all interrupts by IE[EA];
 2. Write 0x03 to FLA_CR;
 3. Write 5A to FLA_KEY, and then 0x1F to unlock Flash;
 4. Write any value to the Flash sector that is to be erased with MOVX instruction;
 5. Write “1” to FLA_CR[FLAACT] to perform sector erasure. After the command is executed, the Flash is automatically locked.
- Flash Programming Operations:
 1. Disable all interrupts by IE[EA];
 2. Write 0x01 to FLA_CR;
 3. Write 0x5A to FLA_KEY, and then 0x1F to unlock Flash;
 4. Write data to the specified Flash sector with MOVX instruction;
 5. Write “1” to FLA_CR[FLAACT] to program 1-byte data. After this command is executed, data is written and Flash is automatically locked.

Notes:

- All interrupts must be disabled before programming to ensure your program is secured and prevent rom_code is written with MOVX instruction.
- It requires quite a long time for the internal circuit to completed Flash operations. For example, it costs about 120ms~150ms to erase a section.
- Each sector has a size of 128 bytes and the last sector (address range: 0x3F80 ~ 0x3FFF) cannot erased at any time. MCU is reset when any instruction in unprotected areas accesses the protected areas (including read, write or erase operations).

31.3 Flash Registers

31.3.1 FLA_CR (0x85)

Bit	7	6	5	4	3	2	1	0
Name	RSV			FLAERR	FLAACT	RSV	FLAERS	FLAWEN
Type	-	-	-	R/W	R/W	-	R/W	R/W
Reset	-	-	-	0	0	-	0	0
Bit	Name	Description						
[7:5]	RSV	Reserved						
[4]	FLAERR	Programming Error Flag 0:Programming or sector erasure succeeds. 1:Programming or sector erasure fails.						
[3]	FLAACT	Flash Erase/Write Trigger A write of “0” has no effect and a write of “1” starts Flash operations, including programing, sector erasure, etc.						
[2]	RSV	Reserved						
[1]	FLAERS	Erase Enable 0: Disable 1: Enable Note: This bit works only when FLA_CR[FLAEN] = 1.						
[0]	FLAWEN	Programming Enable 0: Disable 1: Enable						

31.3.2 FLA_KEY (0x84)

Bit	7	6	5	4	3	2	1	0
Name	FLA KEY							
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	0	0	0	0	0	0	0	0
Bit	Name	Description						
[7:0]	FLA_KEY	Flash Erase/Write Release The Flash software programming feature is activated after “0x5A” and “0x1F” are written to register FLA_KEY in sequence. If the sequence is incorrect or other values are written, Flash space is frozen until the next reset. After unlocking, any write to the FLA_CR register causes the FLA_KEY to be locked again. Read: The lowest 2 bits reflect internal status, and 6 high-order bits obtains 0x00: 00: Locked 01: Write of 0x5A is done, waiting for 0x1F 10: Frozen 11: Released						

32 CRC

32.1 CRC Functional Block Diagram




Figure 30-4 CRC Functional Block Diagram

CRC module outputs the result of CRC calculation for any 8-bit data based on a fixed polynomial. As shown in Figure 30-4, CRC receives the 8-bit data from **CRC_DIN** and sends the 16-bit result to the internal register after the calculation is completed. The result can be indirectly accessed through **CRC_CR[CRCPNT]** and **CRC_DR**.

Table 30-1 CRC Criteria and Polynomials

S/N.	CRC Criteria	Polynomial	Hexadecimal Representation
1	CRC12	$x^{12}+x^{11}+x^3+x^2+x+1$	80F
2	CRC16	$x^{16}+x^{15}+x^2+1$	8005
3	CRC16-CCITT-FALSE	$x^{16}+x^{12}+x^5+1$	1021
4	CRC32	$x^{32}+x^{26}+x^{23}+x^{22}+x^{16}+x^{12}+x^{11}+x^{10}+x^8+x^9+x^5+x^4+x+1$	04C11DB7

32.2 CRC16 Polynomial

The chip uses CRC16/CCITT-FALSE polynomial: $x^{16}+x^{12}+x^5+1$.

32.3 CRC16 Logic Diagram

The schematic diagram of CRC16 is shown in Figure 30-5. The chip implementation is based on parallel algorithm. For each input byte, MCU calculates the results within one system clock cycle.




Figure 30-5 CRC16 Schematic Diagram

32.4 CRC Operations

32.4.1 CRC Calculation of Single Byte

CRC of a single byte is calculated as follows:

1. Initialize CRC_DR with two options: Configure CRC_CR[CRCVAL] and set CRC_CR[CRCDINI] to “1”, with an initial value of 0x0000 or 0xFFFF. Or configure CRC_CR[CRCPNT] and CRC_DR, where any initial value can be set.
2. Write data (0x63 for example) to CRC_DIN, and the CRC calculation is completed in the next clock cycle;
3. Read CRC results: Configure CRC_CR[CRCPNT] = 1, and read off CRC_DR in software to gets the high bytes. Configure CRC_CR[CRCPNT] = 0, and read off CRC_DR to get the low bytes.

32.4.2 CRC Calculation of ROM Sector

CRC of a continuous area of data in the ROM is calculated as follows:

1. Initialize CRC_DR, in the same way as that of single-byte CRC calculation;
2. Configure CRC_BEG to define starting sector of the ROM to be calculated;
3. Configure CRC_CNT to set the offset from the starting sector to the ending sector;
4. Write “1” to CRC_CR[AUTOINT] and keep other bits unchanged. The calculation starts automatically;
5. Read the CRC results.




Figure 30-6 ROM Sectors

As shown in Figure 30-6, ROM contains 16k bytes and is divided into 128 sectors, numbered from sector0 to sector127. Each sector contains 128 bytes. For CRC calculation of sectors, the value of CRC_BEG (the starting sector) can be any value falling between 0x00 and 0x00 ~ 0x7F, including 0x00 and 0x7F. The CRC_CNT (total number of sectors to be calculated) can be any value between 0x00~0x7F, including 0x00 and 0x7F.

As CRC_BEG increases, CRC_CNT decreases accordingly. For example, if CRC_BEG is 0x7F, CRC_CNT can be 0x00 only, i.e., the CRC value of the data in the last sector is calculated. In this case, if CRC_CNT is large (0x01 or larger), CRC controller will automatically limit the number of sectors to be calculated. Finally, CRC module only calculates CRC value of the last sector.

32.5 CRC Registers

32.5.1 CRC_CR (0x4022)

Bit	7	6	5	4	3	2	1	0
Name	RSV			CRCDONE	CRCDINI	CRCVAL	AUTOINT	CRCPNT
Type	-	-	-	R	R/W	R/W	R/W	R/W
Reset	-	-	-	1	0	0	0	0
Bit	Name	Description						
[7:5]	RSV	Reserved						
[4]	CRCDONE	CRC Sector Calculation Completion Flag During the calculation, this bit is automatically set to “0” and the software program stops. In other cases, this bit is automatically set to “1” by the hardware, so the software always returns “1” when reading this bit.						
[3]	CRCDINI	CRC Result Initialization Trigger 0: No effect 1: CRC result initialization is triggered.						

		When “1” is written to this bit by software, the hardware does not actually write “1” to this bit but synchronously generates a high level pulse of a clock cycle, which is sent to CRC engine for the initialization of CRC results. Therefore, it always returns “0” when it reads, no matter what value is written by the software.
[2]	CRCVAL	CRC Result Initialization Selection 0: CRC result is initialized to 0x0000. 1: CRC result is initialized to 0xFFFF.
[1]	AUTOINT	CRC Sector Calculation Launch A write of “1” to this bit launches CRC batch calculation with CRC_BEG as the start block. A total of CRC_CNT blocks are to be calculated. Note: Other bits shall be configured first. In other words, this bit cannot be configured at the same time as other bits.
[0]	CRCPNT	CRC Result Pointer 0: Read CRC_DR to access 8 low-order bits of the 16-bit CRC result 1: Read CRC_DR to access 8 high-order bits of the 16-bit CRC result

Note: CRC calculation can be performed on single byte or ROM sector. When CRC_CR[AUTOINT] is set to “1”, ROM sector CRC calculation is implemented. When CRC_CR[AUTOINT] is set to “0”, single-byte CRC calculation is implemented.

32.5.2 CRC_DIN (0x4021)

Bit	7	6	5	4	3	2	1	0	
Name	CRC DIN								
Type	W	W	W	W	W	W	W	W	
Reset	0	0	0	0	0	0	0	0	
Bit	Name	Description							
[7:0]	CRC_DIN	CRC Input Data Each time a data frame is written to this register, CRC module automatically calculates a new CRC result based on the existing CRC result, and overwrites the original one. Note: It is a virtual register, so the written data is not saved. 0x00 is returned when the address is accessed.							

32.5.3 CRC_DR (0x4023)

Bit	7	6	5	4	3	2	1	0	
Name	CRC DR								
Type	R/W	R/W	R/W	R/W	R/W	R/W	R/W	R/W	
Reset	0	0	0	0	0	0	0	0	
Bit	Name	Description							
[7:0]	CRC_DR	CRC Result Output Each time this register is read or written, the configuration of CRC_CR[CRCPNT] determines whether to access the high-order or low-order bits of the CRC result.							

Note: Because the value of this register can be changed by other signals, this register is placed directly inside the CRC module, instead of register-specific module.

32.5.4 CRC_BEG (0x4024)

Bit	7	6	5	4	3	2	1	0
Name	RSV				CRC BEG			
Type	-	-	-	-	R/W	R/W	R/W	R/W
Reset	-	-	-	-	0	0	0	0

Bit	Name	Description
[7]	RSV	Reserved
[6:0]	CRC_BEG	First ROM Sector Pending Automatic CRC Calculation Example: If CRC_BEG is set to “1”, CRC calculation starts from location $1*128 = 128$, or rather from the first byte of sector 2.

32.5.5 CRC_CNT (0x4025)

Bit	7	6	5	4	3	2	1	0
Name	RSV	CRC_CNT						
Type	-	R/W	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	0	0	0	0	0	0	0
Bit	Name	Description						
[7]	RSV	Reserved						
[6:0]	CRC_CNT	Offset of Sector Pending Automatic CRC Calculation This bit defines the offset of ROM sector for CRC calculation and determines the last sector pending CRC calculation.						

33 Sleep Mode

33.1 Introduction

The chip operates in three modes: normal mode, standby mode and sleep mode. These modes are selected by setting PCON[IDLE] and PCON[STOP].

The operating states of the module under different power modes are summarized in Table 30-2.

Table 30-2 Power Consumption Modes

Power Mode	Description	Wakeup Source	Power Consumption Performance
Normal	All modules work at full speed except for peripherals that are disabled	NA	High power consumption with best performance
Standby	CPU clock stops and other functional modules are either enabled or disabled depending on their control bit setting. WDT stops.	Any interrupt Reset/Debug on external interrupt	Low power performance with flexible performance
Sleep	The analog fast clock circuit is disconnected and software shall ensure that ADC, FOC, and driver modules are disabled before the chip enters the Sleep Mode. WDT is disabled.	External interrupt, RTC interrupt, Reset/Debug on external interrupt	Extremely low power performance with flexible performance

Note: It is recommended to insert 3 null statements in the Sleep mode.

PCON = 0x02;

```
_nop_();  
_nop_();
```

33.2 Sleep Mode Register

33.2.1 PCON (0x87)

Bit	7	6	5	4	3	2	1	0
Name	RSV		GF3	GF2	GF1	RSV	STOP	IDLE
Type	-	-	R/W	R/W	R/W	R/W	R/W	R/W
Reset	-	-	0	0	0	0	0	0

Bit	Name	Description
[7:6]	RSV	Reserved
5	GF3	General-purpose flag bit 3
4	GF2	General-purpose flag bit 2
3	GF1	General-purpose flag bit 1
2	RSV	Reserved
1	STOP	A write of “1” makes the chip enter the sleep mode. The bit is automatically cleared to “0” by hardware after wakeup.
0	IDLE	A write of “1” makes the chip enter the sleep mode. The bit is automatically cleared to “0” by hardware after wakeup. Power Consumption Mode: {STOP, IDLE} = 1x, the system is in sleep mode. {STOP, IDLE} = 01, the system is in standby mode. {STOP, IDLE} = 00, the system is operates normally.

34 Code Protection




Figure 30-7 Code Protection Configurations




Figure 30-8 Full Code Protection Mode




Figure 30-9 Partial Code Protection Mode

The chip supports Flash space encryption to protect your software intellectual property. Operation steps are as follows:

1. Start 8051 IDE, enter Target Options and select Debug tab. As shown in Figure 30-7, click Settings to proceed with the setting;
2. Select the options as shown in Figure 30-8, and click OK. Then compile the project and download it. Get the BIN file and program it to Flash.

The chip support full code protection mode and partial code protection mode. After Full Encrypt is selected as shown in Figure 30-8, all codes in Flash are protected. After Partial Encrypt is selected as shown in Figure 30-9, the codes from sector 0 to END SECTOR are protected. The last sector is always protected in any case.

The size of each sector is 128 bytes.

35 Configuration Registers

35.1 CCFG

35.1.1 CCFG1 (0x401E)

Bit	7	6	5	4	3	2	1	0
Name	LVDENB	LVWIE	WDTEN	RSV		FCK_SEL	RSV	
Type	R/W	R/W	R/W	-	-	R/W	R/W	R
Reset	0	0	0	-	-	0	0	0
Bit Name Description								
[7]	LVDENB	LV Reset Detection Enable 0: Enable. The system resets if VDD5 is lower than the threshold voltage set by CCFG2[LVRSEL]. 1: Disable. Note: The low voltage detector has two main features: low voltage reset and low voltage warning. The chip is reset when VDD5 is lower than the threshold voltage set by CCFG2[LVRSEL], and LV warning interrupt is generated when VCC is lower than the threshold voltage set by CCFG2[LVWSEL]. The above two features work only after LV Reset Detection is enabled (CCFG1[LVDENB]=0) and LVW Detection Interrupt is enabled (CCFG1[LVWIE]=1).						
[6]	LVWIE	LVW Detection Interrupt Enable. CCFG2[LVWSEL] decides VCC LV warning voltage threshold. 0: Disable 1: Enable. LV reset detection circuit shall be enabled as well (i.e. CCFG1[LVDENB] = 0).						
[5]	WDTEN	WDT Enable 0: Disable 1: Enable						
[4:3]	RSV	Reserved						
[2:1]	FCK_SEL	System Clock Rate Selection 00: 24MHz 01: 12MHz 10: 6MHz 11: 3MHz						
[0]	RSV	Reserved						

Note: This register can be directly accessed by software. It is recommended that you set these parameters in the IDE, so that you do not have to configure them again in software.

35.1.2 CCFG2 (0x401D)

This register can be configured by IDE only. The register configurations are compiled and merged with ROM_CODE to produce a BIN file for programming. The register can be read by software only.

Bit	7	6	5	4	3	2	1	0
Name	LVRSEL		WDTBTEN	WDTRSTEN	RSV		LVWSEL	
Type	R/W		R/W	R/W	-	-	R/W	R/W
Reset	0		0	0	-	-	0	0
Bit	Name		Description					
[7:6]	LVRSEL		Low Voltage Reset Threshold Voltage. VDD5 is detected for the low voltage reset. 00: Low voltage reset is enabled when VDD5 is lower than 2.8V. 01: Low voltage reset is enabled when VDD5 is lower than 3.0V. 10: Low voltage reset is enabled when VDD5 is lower than 3.5V. 11: Low voltage reset is enabled when VDD5 is lower than 3.8V.					
[5]	WDTBTEN		1: BOOT is activated when WDT is reset.					
[4]	WDTRSTEN		WDT Reset Enable after Overflow 1: WDT is rest after it is overflowed.					
[3:2]	RSV		Reserved					
[1:0]	LVWSEL		Low Voltage Warning Threshold Voltage. VCC is detected for the low voltage warning. 00: Low voltage warning is enabled when VCC is lower than 7V. 01: Low voltage warning is enabled when VCC is lower than 8V. 10: Low voltage warning is enabled when VCC is lower than 9V. 11: Low voltage warning is enabled when VCC is lower than 10V.					

36 Revision History

Rev.	Description	Date	Prepared By
V0.1	Preliminary datasheet, translated from Chinese version 0.1	2023/07/12	Eric Deng
V1.0	<p>Final datasheet.</p> <ol style="list-style-type: none"> 1. Added chapters 6 ~ 35; 2. Modified the package name “QHF120120-54L” as “WBQHFBP-45L”; 3. Deleted descriptions on CMP4M and CMP4MS for P2.7 and P3.4; 4. Deleted I²C, LIN and EEPROM from Abbreviations, and deleted descriptions on I²C. 5. Modified the number of interrupt sources as “15” from “16” and the number of ADC channels as “10” from “8” in section 1.1 Features; Added descriptions on SPI in communication interfaces; Modified “3-channel analog comparator” as “2-channel analog comparator”; 6. Modified “PID” as “PI” in sections 1.1 Features, 1.3 Overview, 1.4 Functional Block Diagram; 7. Renamed comparators and operational amplifiers in sections 1.4 Functional Block Diagram and 2 Pin Definitions, and added SPI and deleted INT0 in Figure 1-1 ES9676AH Functional Block Diagram ; 8. Deleted registers I2C_CR, I2C_ID, I2C_DR and I2C_SR with the address 0x4028, and deleted repeated registers with the address 0x0310, 0x0308 and 0x0300 in Table 1-2 XSFR Address Mapping. 9. Updated section 2 Pin Definitions; 10. Added SPI to Table 4-1 Model Selections; Modified the number of ADC channel as “10” from “8” and the number of comparator as “2” from “3”. 	2023/11/15	Eric Deng

Copyright Notice

Copyright by Fortior Technology Co., Ltd. All Rights Reserved.

Right to make changes — Fortior Technology Co., Ltd. reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. The information contained in this manual is provided for the general use by our customers. Our customers shall ensure that they take appropriate action so that their use of our products does not infringe upon any patents. It is the policy of Fortior Technology Co., Ltd. to respect the valid patent rights of third parties and not to infringe upon or assist others to infringe upon such rights.

This manual is copyrighted by Fortior Technology Co., Ltd. You may not reproduce, transmit, transcribe, store in a retrieval system, or translate into any language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual, or otherwise, any part of this publication without the expressly written permission from Fortior Technology Co., Ltd. You may not alter or remove any copyright or other notice from copies of this content.

If there are any differences between the Chinese and the English contents, please take the Chinese version as the standard.

Fortior Technology Co., Ltd.

Customer service:info@fortiortech.com

URL: <http://www.fortiortech.com/global/>

Contained herein

Copyright by Fortior Technology Co., Ltd. All rights reserved.